

# Package ‘GGIR’

August 27, 2020

**Type** Package

**Title** Raw Accelerometer Data Analysis

**Version** 2.1-0

**Date** 2020-08-27

**Maintainer** Vincent T van Hees <v.vanhees@accelting.com>

**Description** A tool to process and analyse data collected with wearable raw acceleration sensors as described in Migueles and colleagues (JMPB 2019), and van Hees and colleagues (JApplPhysiol 2014; PLoS ONE 2015). The package has been developed and tested for binary data from 'GENEActiv' <<https://www.activinsights.com/>> and GENE devices (not for sale), .csv-export data from 'Actigraph' <<https://actigraphcorp.com>> devices, and .cwa and .wav-format data from 'Axivity' <<https://axivity.com>>. These devices are currently widely used in research on human daily physical activity. Further, the package can handle accelerometer data file from any other sensor brand providing that the data is stored in csv format and has either no header or a two column header. Also the package allows for external function embedding.

**URL** <https://github.com/wadpac/GGIR/>,  
<https://groups.google.com/forum/#!forum/RpackageGGIR>

**BugReports** <https://github.com/wadpac/GGIR/issues>

**License** LGPL (>= 2.0, < 3) | file LICENSE

**Suggests** testthat, covr, knitr, rmarkdown

**Imports** data.table, Rcpp (>= 0.12.10), foreach, doParallel, signal,  
zoo, bitops, matlab, GENEAREad, tuneR, unisensR

**Depends** stats, utils, R (>= 3.2.0)

**NeedsCompilation** yes

**LinkingTo** Rcpp

**VignetteBuilder** knitr

**ByteCompile** yes

**Author** Vincent T van Hees [aut, cre],  
Zhou Fang [ctb],  
Jing Hua Zhao [ctb],  
Joe Heywood [ctb],

Evgeny Mirkes [ctb],  
 Severine Sabia [ctb],  
 Joan Capdevila Pujol [ctb],  
 Jairo H Migueles [ctb],  
 Matthew R Patterson [ctb],  
 Dan Jackson [ctb]

**Repository** CRAN

**Date/Publication** 2020-08-27 16:00:35 UTC

## R topics documented:

GGIR-package . . . . .	4
applyExtFunction . . . . .	5
chartime2iso8601 . . . . .	6
check_myfun . . . . .	7
createConfigFile . . . . .	7
create_test_acc_csv . . . . .	8
create_test_sleeplog_csv . . . . .	9
data.calibrate . . . . .	9
data.getmeta . . . . .	10
data.inspectfile . . . . .	10
datadir2fnames . . . . .	11
g.abr.day.names . . . . .	12
g.analyse . . . . .	12
g.analyse.avy . . . . .	15
g.analyse.perday . . . . .	17
g.analyse.perfile . . . . .	19
g.applymetrics . . . . .	21
g.binread . . . . .	22
g.calibrate . . . . .	23
g.create.sp.mat . . . . .	25
g.createcoordinates . . . . .	25
g.cwared . . . . .	26
g.detecmidnight . . . . .	27
g.dotorcomma . . . . .	28
g.downsample . . . . .	29
g.extractheadervars . . . . .	29
g.getbout . . . . .	30
g.getidfromheaderobject . . . . .	31
g.getM5L5 . . . . .	32
g.getmeta . . . . .	33
g.getstarttime . . . . .	37
g.impute . . . . .	37
g.inspectfile . . . . .	39
g.intensitygradient . . . . .	40
g.IVIS . . . . .	40
g.loadlog . . . . .	41

g.metric . . . . .	42
g.part1 . . . . .	43
g.part2 . . . . .	47
g.part3 . . . . .	50
g.part4 . . . . .	52
g.part5 . . . . .	55
g.part5.addfirstwake . . . . .	59
g.part5.addsib . . . . .	60
g.part5.definedays . . . . .	60
g.part5.fixmissingnight . . . . .	61
g.part5.onsetwaketiming . . . . .	62
g.part5.savetimeseries . . . . .	63
g.part5.wakesleepwindows . . . . .	64
g.plot . . . . .	65
g.plot5 . . . . .	66
g.readaccfile . . . . .	67
g.readtemp_movisens . . . . .	68
g.report.part2 . . . . .	69
g.report.part4 . . . . .	70
g.report.part5 . . . . .	71
g.shell.GGIR . . . . .	72
g.sib.det . . . . .	75
g.sib.plot . . . . .	77
g.sib.sum . . . . .	77
g.wavread . . . . .	78
g.weardec . . . . .	79
getFirstTimestamp . . . . .	80
getfolderstructure . . . . .	80
getStartEnd . . . . .	81
getStartEndNumeric . . . . .	82
get_nw_clip_block_params . . . . .	82
get_starttime_weekday_meantemp_truncdata . . . . .	83
identify_levels . . . . .	84
is.ISO8601 . . . . .	85
isfilelist . . . . .	86
ismovisens . . . . .	86
iso8601chartime2POSIX . . . . .	87
is_this_a_dst_night . . . . .	87
numUnpack . . . . .	88
POSIXtime2iso8601 . . . . .	89
read.myacc.csv . . . . .	89
resample . . . . .	92
updateBlocksize . . . . .	93

---

GGIR-package

*A package to process multi-day raw accelerometer data*

---

## Description

Disclaimer: If you are a new GGIR user then please see [package vignette](#) for an introduction to GGIR.

This document is primarily aimed at documenting the functions and their input arguments.

Please note that there is google discussion group for this package ([link below](#)).

You can thank us for sharing the code in this package and for developing it as a generic purpose tool by citing the package name and by citing the supporting publications (e.g. Migueles et al. 2019) in your publications.

## Details

Package:	GGIR
Type:	Package
Version:	2.1-0
Date:	2020-08-27
License:	LGPL (>= 2.0, < 3)
Discussion group:	<a href="https://groups.google.com/forum/#!forum/rpackageggir">https://groups.google.com/forum/#!forum/rpackageggir</a>

## Author(s)

- Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)> main developer
- Zhou Fang co-developed function [g.calibrate](#)
- Jing Hua Zhao <[jinghua.zhao@mrc-epid.cam.ac.uk](mailto:jinghua.zhao@mrc-epid.cam.ac.uk)> co-developed function [g.binread](#)
- Joe Heywood helped develop the functionality to process only specific days
- Evgeny Mirkes developed function [g.cwared](#)
- Severine Sabia tested and provided feedback on various functions
- Joan Capdevila Pujol helped to improve various function
- Jairo H Migueles <[jairohm@ugr.es](mailto:jairohm@ugr.es)> helped to improve various functions
- Dan Jackson helped with unpack function for AX3 data.
- Matthew R Patterson helped with enhancing the visual report.

## References

- Migueles JH, Rowlands AV, et al. GGIR: A Research Community-Driven Open Source R Package for Generating Physical Activity and Sleep Outcomes From Multi-Day Raw Accelerometer Data. *Journal for the Measurement of Physical Behaviour*. 2(3) 2019. doi:10.1123/jmpb.2018-0063.
- van Hees VT, Gorzelniak L, Dean Leon EC, Eder M, Pias M, et al. (2013) Separating Movement and Gravity Components in an Acceleration Signal and Implications for the Assessment of Human Daily Physical Activity. *PLoS ONE* 8(4): e61691. doi:10.1371/journal.pone.0061691
- van Hees VT, Fang Z, Langford J, Assah F, Mohammad A, da Silva IC, Trenell MI, White T, Wareham NJ, Brage S. Auto-calibration of accelerometer data for free-living physical activity assessment using local gravity and temperature: an evaluation on four continents. *J Appl Physiol* (1985). 2014 Aug 7
- van Hees VT, Sabia S, et al. (2015) A novel, open access method to assess sleep duration using a wrist-worn accelerometer, *PLoS ONE*, November 2015

## Examples

```
## Not run:
#inspect file:
I = g.inspectfile(datafile)

#autocalibration:
C = g.calibrate(datafile)

#get meta-data:
M = g.getmeta(datafile)

## End(Not run)
data(data.getmeta)
data(data.inspectfile)
data(data.calibrate)

#impute meta-data:
IMP = g.impute(M = data.getmeta, I = data.inspectfile)
#analyse and produce summary:
A = g.analyse(I = data.inspectfile, C = data.calibrate, M = data.getmeta, IMP)
#plot data
g.plot(IMP, M = data.getmeta, I = data.inspectfile, durplot=4)
```

---

applyExtFunction      *Apply external function to acceleration data.*

---

## Description

Applies external function to the raw acceleration data within GGIR. This makes it easier for new algorithms developed to be piloted on accelerometer data while taking advantage of the existing comprehensive GGIR data management and analysis infrastructure. This function is not for direct interaction by user, please supply object myfun to [g.shell.GGIR](#) or [g.part1](#). Object myfun is a list as detailed below.

**Usage**

```
applyExtFunction(data, myfun, sf, ws3)
```

**Arguments**

data	Data data.frame as present internally in <a href="#">g.getmeta</a> . It has at least four columns of which the first is the timestamp followed by the x, y, and z acceleration.
myfun	See details, in short: myfun is a list object that holds the external function to be applied to the data and various parameters to aid in the process.
sf	Sample frequency (Hertz) of the data object
ws3	Short epoch size (first value of windowsizes in <a href="#">g.getmeta</a> ).

**Details**

See package vignette for detailed tutorial with examples on how to use the function embedding: <https://cran.r-project.org/web/package=GGIR/vignettes/applyExtFunction.pdf> Function applyExtFunction is typically not used by the GGIR user directly.

**Value**

The output of the external algorithm aggregated or repeated to fit the short epoch length of GGIR. Therefore, the short epoch length of GGIR should be a multitude of the resolution of the external function output, or visa versa.

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

chartime2iso8601

*Convert character timestamps to iso8601 timestamp*

---

**Description**

To avoid ambiguities when sharing and comparing timestamps. All timestamps are expressed in iso8601 format: [https://en.wikipedia.org/wiki/ISO\\_8601](https://en.wikipedia.org/wiki/ISO_8601)

**Usage**

```
chartime2iso8601(x, tz)
```

**Arguments**

x	Vector of timestamps in character format: year-month-date and optional followed by hour:minute:second For example, "1980-01-01 18:00:00"
tz	Timezone of data collection, e.g. "Europe/London". See <a href="https://en.wikipedia.org/wiki/List_of_tz_databases">https://en.wikipedia.org/wiki/List_of_tz_databases</a> for full list

**Examples**

```
x = "1980-1-1 18:00:00"
tz = "Europe/Amsterdam"
x_converted = chartime2iso8601(x, tz)
```

---

check\_myfun

*Checks myfun object before it is passed to applyExtfunction*


---

**Description**

Checks that object myfun is a list and check the elements of the list for: that element names are as expected, that value of each element is of the expected type and length.

**Usage**

```
check_myfun(myfun, windowsizes)
```

**Arguments**

myfun            See [applyExtFunction](#)  
windowsizes      See [g.getmeta](#)).

**Value**

0 if all checkes passed, 1 if one or more checks did not pass. Error message are printed to the console with feedback on which checks did not pass.

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

createConfigFile

*Creates Config File based on variables in g.shell.GGIR environment*


---

**Description**

Only used inside [g.shell.GGIR](#). Not intended for direct use by user.

**Usage**

```
createConfigFile(config.parameters = c())
```

**Arguments**

config.parameters  
List with all arguments used in [g.shell.GGIR](#).

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

create\_test\_acc\_csv     *Creates csv data file for testing purposes*

---

**Description**

Creates file in the Actigraph csv data format with dummy data that can be used for testing. The file includes accelerometer data with bouts of higher acceleration, variations non-movement periods in a range of accelerometer positions to allow for testing the auto-calibration functionality.

**Usage**

```
create_test_acc_csv(sf=3,Nmin=2000,storagelocation=c())
```

**Arguments**

sf	Sample frequency in Hertz, the default here is low to minimize file size
Nmin	Number of minutes (minimum is 2000)
storagelocation	Location where the test file named testfile.csv will be stored If no value is provided then the function uses the current working directory

**Value**

The function does not produce any output values. Only the file is stored

**Examples**

```
## Not run:  
  create_test_acc_csv()  
  
## End(Not run)
```



---

`create_test_sleeplog_csv`*Creates csv sleeplog file for testing purposes*

---

**Description**

Creates sleeplog file in the format as expected by `g.part4` with dummy data (23:00 onset, 07:00 waking time for every night).

**Usage**

```
create_test_sleeplog_csv(Nnights=7,storagelocation=c())
```

**Arguments**

`Nnights`            Number of nights (minimum is 1)

`storagelocation`

Location where the test file named `testfile.csv` will be stored. If no value is provided then the function uses the current working directory.

**Value**

The function does not produce any output values. Only the file is stored.

**Examples**

```
## Not run:  
  create_test_sleeplog_csv()  
  
## End(Not run)
```

---

`data.calibrate`*Example output from `g.calibrate`*

---

**Description**

`data.calibrate` is example output from [g.calibrate](#)

**Usage**

```
data(data.calibrate)
```

**Format**

The format is: `chr "data.calibrate"`

**Source**

The data was collected on one individual for testing purposes

**Examples**

```
data(data.calibrate)
```

---

data.getmeta	<i>Example output from g.getmeta</i>
--------------	--------------------------------------

---

**Description**

data.getmeta is example output from [g.getmeta](#)

**Usage**

```
data(data.getmeta)
```

**Format**

The format is: chr "data.getmeta"

**Source**

The data was collected on one individual for testing purposes

**Examples**

```
data(data.getmeta)
```

---

data.inspectfile	<i>Example output from g.inspectfile</i>
------------------	--

---

**Description**

data.inspectfile is example output from [g.inspectfile](#)

**Usage**

```
data(data.inspectfile)
```

**Format**

The format is: chr "data.inspectfile"

**Source**

The data was collected on one individual for testing purposes

**Examples**

```
data(data.inspectfile)
```

---

datadir2fnames	<i>Generates vector of file names out of datadir input argument</i>
----------------	---

---

**Description**

Uses input argument `datadir` from [g.part1](#) and the output from [isfilelist](#) to generate vector of file-names

**Usage**

```
datadir2fnames(datadir, filelist)
```

**Arguments**

<code>datadir</code>	See <a href="#">g.part1</a>
<code>filelist</code>	Produced by <a href="#">isfilelist</a>

**Value**

Character vector of filenames

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
## Not run:  
datadir2fnames(datadir = "C:/mydatafolder", filelist=TRUE)  
  
## End(Not run)
```

---

<code>g.abr.day.names</code>	<i>Abbreviates daynames to numbers, needed for report generation in <a href="#">g.plot5</a></i>
------------------------------	---

---

**Description**

Abbreviates daynames Monday becomes MON and Sunday becomes SUN

**Usage**

```
g.abr.day.names(daynames)
```

**Arguments**

daynames            Vector of daynames in character format

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
daynames = c("Monday", "Friday")
daynames_converted = g.abr.day.names(daynames)
```

---

<code>g.analyse</code>	<i>function to analyse meta-data generated by <a href="#">g.getmeta</a> and <a href="#">g.impute</a></i>
------------------------	--

---

**Description**

Analyses the output from other functions within the packages to generate a basic descriptive summary for each accelerometer data file. Analyses include: Average acceleration per day, per measurement, L5M5 analyses (assessment of the five hours with lowest acceleration and with highest acceleration). Further, the traditionally popular variable MVPA is automatically extracted in six variants: without bout criteria in combination with epoch = epoch length as defined in `g.getmeta` (first value of the input argument `window sizes`), 1 minute, and 5 minutes, and for bout durations 1 minute, 5 minutes or 10 minutes in combination with the epoch length as defined in `g.getmeta`.

**Usage**

```
g.analyse(I, C, M, IMP, qllevels = c(), qwindow = c(0, 24),
quantiletype = 7, L5M5window = c(0, 24), M5L5res = 10,
includedaycrit = 16, ilevels = c(),
winhr = 5, idloc = 1, snloc=1, mvpathreshold = c(),
boutcriter=c(), mvpadur=c(1,5,10),
selectdaysfile=c(), window.summary.size=10,
```

```

dayborder=0,bout.metric = 1,
closedbout=FALSE,desiredtz = c(),
IVIS_windowsize_minutes = 60,
IVIS_epochsize_seconds = 3600, iglevels = c(),IVIS.activity.metric=1,
qM5L5=c(), myfun=c())

```

## Arguments

I	the output from function <a href="#">g.inspectfile</a>
C	the output from function <a href="#">g.calibrate</a>
M	the output from function <a href="#">g.getmeta</a>
IMP	the output from function <a href="#">g.impute</a>
qllevels	array of percentiles for which value needs to be extracted. These need to be expressed as a fraction of 1, e.g. c(0.1, 0.5, 0.75). There is no limit to the number of percentiles. If left empty then percentiles will not be extracted. Distribution will be derived from short epoch metric data, see <a href="#">g.getmeta</a> .
qwindow	To specify windows over which all variables are calculated. If value = c(0,24) all variables will only be calculated over the full 24 hours in a day, If value =c(8,24) variables will be calculated over the window 0-8, 8-24 and 0-24. Previously this functionality was limited to the distribution in acceleration metric values, but now it also derives N valid hours, L5M5 analysis and MVPA.
quantiletype	type of quantile function to use (default recommended). For details, see quantile function in STATS package
L5M5window	Argument deprecated after version 1.5-24. This argument used to define the start and end time, in 24 hour clock hours, over which L5M5 needs to be calculated. Now this is done with argument qwindow.
M5L5res	resolution of L5 and M5 analysis in minutes (default: 10 minutes)
includedaycrit	minimum required number of valid hours in day specific analysis (NOTE: there is no minimum required number of hours per day in the summary of an entire measurement, every available hour is used to make the best possible inference on average metric value per average day)
ilevels	Levels for acceleration value frequency distribution in mg, e.g. c(0,100,200) There is no constricton to the number of levels.
winhr	Vector of window size(s) (unit: hours) of L5 and M5 analysis (dedault = 5 hours)
idloc	If value = 1 (default) the code assumes that ID number is stored in the obvious header field. If value = 2 the code uses the character string preceding the character '_' in the filename as the ID number
snloc	If value = 1 (default) the code assumes that device serial number is stored in the obvious header field. If value = 2 the code uses the character string between the first and second character '_' in the filename as the serial number
mvpathreshold	Threshold for MVPA estimation. This can be a single number or an array of numbers, e.g. c(100,120). In the later case the code will estimate MVPA seperately for each threshold. If this variable is left blank c() then MVPA is not estimated

boutcriter	The variable boutcriter is a number between 0 and 1 and defines what fraction of a bout needs to be above the mvpathreshold
mvpadur	default = c(1,5,10). Three bout duration for which MVPA will be calculated
selectdaysfile	Functionality designed for the London Centre of Longitudinal studies. Csv file holding the relation between device serial numbers and measurement days of interest.
dayborder	Hour at which days start and end (default = 0), value = 4 would mean 4am
window.summary.size	Functionality designed for the London Centre of Longitudinal studies. Size in minutes of the summary window
bout.metric	This argument used to be called mvpa.2014 and had TRUE or FALSE as its value. However, it has now become clear that this aspect of the analyses is still very much open for debate. Therefore, I have changed it into an argument where you can specify a metric for bout detection based on a number. A description of these bout metrics can be found in the new function <a href="#">g.getbout</a>
closedbout	If TRUE then count breaks in a bout towards the bout duration. If FALSE then only count time spent above the threshold towards the bout duration.
desiredtz	see <a href="#">g.getmeta</a>
IVIS_windowsize_minutes	Window size of the Intradaily Variability (IV) and Interdaily Stability (IS) metrics in minutes
IVIS_epochsize_seconds	Epoch size of the Intradaily Variability (IV) and Interdaily Stability (IS) metrics in seconds
iglevels	Levels for acceleration value frequency distribution in mg used for intensity gradient calculation (according to the method by Rowlands 2018). By default this is argument is empty and the intensity gradient calculation is not done. The user can either provide a single value (any) to make the intensity gradient use the bins c(seq(0,4000,by=25),8000) or the user could specify their own distribution. There is no constriction to the number of levels.
IVIS.activity.metric	see function <a href="#">g.IVIS</a>
qM5L5	see function <a href="#">g.getM5L5</a>
myfun	External function object to be applied to raw data, see <a href="#">g.getmeta</a> .

## Value

g.analyse generated two data.frames

summary	summary for the file that was analysed
daysummary	summary per day for the file that was analysed

These data.frames are used by function `g.report.part2` to generate csv reports. An explanation of all the columns in the data.frame and subsequent csv reports can be found in the package vignette (Output part 2).

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
data(data.getmeta)
data(data.inspectfile)
data(data.calibrate)
## Not run:
  #inspect file:
  I = g.inspectfile(datafile)

  #autocalibration:
  C = g.calibrate(datafile)

  #get meta-data:
  M = g.getmeta(datafile, desiredtz = "Europe/London",
    window sizes = c(5, 900, 3600),
    daylimit = FALSE, offset = c(0, 0, 0),
    scale = c(1, 1, 1), tempoffset = c(0, 0, 0))

## End(Not run)

#impute meta-data:
IMP = g.impute(M = data.getmeta, I = data.inspectfile)

#analyse and produce summary:
A = g.analyse(I = data.inspectfile, C = data.calibrate,
  M = data.getmeta, IMP)
```

---

g.analyse.avy

*Function supports [g.analyse](#). Not intended for direct use by user.*

---

**Description**

Generates average day analyses and fills corresponding output matrix, [g.analyse](#).

**Usage**

```
g.analyse.avday(qlevels, doquan, averageday, M, IMP,
  t_TWDI, quantiletype, winhr, L5M5window, M5L5res,
  ws3, IVIS_epochsize_seconds,
  IVIS_windowsize_minutes, IVIS.activity.metric, doiglevels,
  firstmidnighti, ws2, midnightsi, iglevels, qM5L5)
```

**Arguments**

qlevels	see <a href="#">g.analyse</a>
doquan	Boolean whether quantile analysis should be done
averageday	As produced by <a href="#">g.impute</a>
M	As produced by <a href="#">g.getmeta</a>
IMP	As produced by <a href="#">g.impute</a>
t_TWDI	Same as qwindow as described in <a href="#">g.analyse</a>
quantiletype	see <a href="#">g.analyse</a>
winhr	see <a href="#">g.analyse</a>
L5M5window	see <a href="#">g.analyse</a>
M5L5res	see <a href="#">g.analyse</a>
ws3	Epoch size in seconds
IVIS_epochsize_seconds	see <a href="#">g.IVIS</a>
IVIS_windowsize_minutes	see <a href="#">g.IVIS</a>
IVIS.activity.metric	see <a href="#">g.IVIS</a>
doiglevels	Boolean to indicate whether iglevels should be calculated
firstmidnighti	see <a href="#">g.detecmidnight</a>
ws2	see <a href="#">g.weardec</a>
midnightsi	see <a href="#">g.detecmidnight</a>
iglevels	see <a href="#">g.analyse</a>
qM5L5	see <a href="#">g.getM5L5</a>

**Value**

InterdailyStability  
  
IntradailyVariability  
  
igfullr\_names  
igfullr  
QUAN  
qlevels\_names  
ML5AD  
ML5AD\_names

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>



---

`g.analyse.perday`      *Function supports [g.analyse](#). Not intended for direct use by user.*

---

### Description

Generates day specific analyses and fills corresponding output matrix, [g.analyse](#).

### Usage

```
g.analyse.perday(selectdaysfile, ndays, firstmidnighti,
  time, nfeatures, window.summary.size, qwindow, midnightsi,
  metashort, averageday, ENMOi, LFENMOi, BFENi, ENi,
  HFENi, HFENplusi, MADi, ENMOai, doiglevels, nfulldays, lastmidnight,
  ws3, ws2, qcheck, fname, idloc, BodyLocation, wdayname,
  tooshort, includedaycrit, winhr,L5M5window, M5L5res,
  doquan, qllevels, quantiletype, doilevels,
  ilevels, iglevels, domvpa,
  mvpathreshold, boutcriter, closedbout,
  bout.metric, mvpadur, mvpanames, wdaycode, IDd, ID, ID2,
  deviceSerialNumber, qM5L5, ExtFunColsi, myfun)
```

### Arguments

<code>selectdaysfile</code>	see <a href="#">g.analyse</a>
<code>ndays</code>	Number of days in file
<code>firstmidnighti</code>	see <a href="#">g.deteomidnight</a>
<code>time</code>	timestamp column from metalong converted to character
<code>nfeatures</code>	estimate of number of variables that need to be stored in the output matrix
<code>window.summary.size</code>	see <a href="#">g.analyse</a>
<code>qwindow</code>	see <a href="#">g.analyse</a>
<code>midnightsi</code>	see <a href="#">g.deteomidnight</a>
<code>metashort</code>	see <a href="#">g.impute</a>
<code>averageday</code>	As produced by <a href="#">g.impute</a>
<code>ENMOi</code>	column index of metahosrt where metric is stored
<code>LFENMOi</code>	column index of metahosrt where metric is stored
<code>BFENi</code>	column index of metahosrt where metric is stored
<code>ENi</code>	column index of metahosrt where metric is stored
<code>HFENi</code>	column index of metahosrt where metric is stored
<code>HFENplusi</code>	column index of metahosrt where metric is stored
<code>MADi</code>	column index of metahosrt where metric is stored
<code>ENMOai</code>	column index of metahosrt where metric is stored

doiglevels	Boolean to indicate whether iglevels should be calculated
nfulldays	Number of days between the first and last midnight in the recording
lastmidnight	see <a href="#">g.detecmidnight</a>
ws3	Epoch size in seconds
ws2	see <a href="#">g.weardec</a>
qcheck	vector with zeros and ones for each epoch, respenting the quality check derived with <a href="#">g.impute</a>
fname	RData filename produced by <a href="#">g.part1</a>
idloc	see <a href="#">g.analyse</a>
BodyLocation	as produced by <a href="#">g.extractheadervars</a>
wdayname	character with weekdayname
tooshort	0 (file not too short) or 1 (file too short)
includedaycrit	see <a href="#">g.analyse</a>
winhr	see <a href="#">g.analyse</a>
L5M5window	see <a href="#">g.analyse</a>
M5L5res	see <a href="#">g.analyse</a>
doquan	Boolean whether quantile analysis should be done
qlevels	see <a href="#">g.analyse</a>
quantiletype	see <a href="#">g.analyse</a>
doilevels	Boolean whether to generate ilevels, see <a href="#">g.analyse</a>
ilevels	see <a href="#">g.analyse</a>
iglevels	see <a href="#">g.analyse</a>
domvpa	Boolean whether to do mvpa analysis
mvpathreshold	see <a href="#">g.analyse</a>
boutcriter	see <a href="#">g.analyse</a>
closedbout	see <a href="#">g.analyse</a>
bout.metric	see <a href="#">g.analyse</a>
mvpadur	see <a href="#">g.analyse</a>
mvpanames	Matrix with 6 columns and 1 row holding the names for the six mvpa variables
wdaycode	Equal to M\$wday as produced by <a href="#">g.getmeta</a>
IDd	As produced by <a href="#">g.extractheadervars</a>
ID	As produced by <a href="#">g.extractheadervars</a>
ID2	generated inside <a href="#">g.analyse</a> either a copy of ID, or as character string before the first hyphen
deviceSerialNumber	As produced by <a href="#">g.extractheadervars</a>
qM5L5	see <a href="#">g.getM5L5</a>
ExtFunColsi	column index of metahosrt where metric is stored
myfun	External function object to be applied to raw data, see <a href="#">g.getmeta</a> .

**Value**

daysummary	Summary per day for the file that was analysed
ds_names	Variable names in daysummary
windowsummary	Window summary, only used when selectdayfile is specified
ws_names	Variable names in windowsummary

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.analyse.perfile      *Function supports [g.analyse](#). Not intended for direct use by user.*

---

**Description**

Generates recording specific analyses and fills corresponding output matrix, [g.analyse](#).

**Usage**

```
g.analyse.perfile(ID, ID2, IDd, fname, deviceSerialNumber,
  BodyLocation, startt, I, LC2, LD, dcompscore,
  Lmp, LWp, C, lookat, AveAccAve24hr,
  colnames_to_lookat, QUAN, ML5AD,
  ML5AD_names, igfullr, igfullr_names,
  daysummary, ds_names, includedaycrit, strategy, hrs.del.start,
  hrs.del.end, maxdur, windowsizes, idloc, snloc, wdayname, doquan,
  qlevels_names, doiglevels, tooshort, InterdailyStability,
  IntradailyVariability,
  IVIS_windowsize_minutes, IVIS_epochsize_seconds, qwindow, longitudinal_axis_id)
```

**Arguments**

ID	see <a href="#">g.analyse.perday</a>
ID2	see <a href="#">g.analyse.perday</a>
IDd	see <a href="#">g.analyse.perday</a>
fname	see <a href="#">g.analyse.perday</a>
deviceSerialNumber	As produced by <a href="#">g.extractheadervars</a>
BodyLocation	as produced by <a href="#">g.extractheadervars</a>
startt	First timestamp in metalong
I	output <a href="#">g.inspectfile</a>
LC2	see <a href="#">g.impute</a>
LD	length data in minutes

dcompscore	see <a href="#">g.impute</a>
LMp	length measurement based on study protocol (minutes)
LWp	length of sensor worn based on study protocol (minutes)
C	output <a href="#">g.calibrate</a>
lookat	indices of metashort column to analyse
AveAccAve24hr	Average acceleration in an average 24 hour cycle
colnames_to_lookat	Names of columns to look at, corresponding to argument lookat
QUAN	Results quantile analysis on the average day produced by <a href="#">g.analyse.avday</a>
ML5AD	Results ML5 analyses on the average day produced by <a href="#">g.analyse.avday</a>
ML5AD_names	Columns names corresponding to ML5AD
igfullr	Results intensity gradient (ig) analysis on the average day produced by <a href="#">g.analyse.avday</a>
igfullr_names	Columns names corresponding to igfullr
daysummary	object produced by <a href="#">g.analyse.perday</a>
ds_names	column names corresponding to daysummary
includedaycrit	see <a href="#">g.analyse</a>
strategy	see <a href="#">g.analyse</a>
hrs.del.start	see <a href="#">g.analyse</a>
hrs.del.end	see <a href="#">g.analyse</a>
maxdur	see <a href="#">g.analyse</a>
window sizes	see <a href="#">g.getmeta</a>
idloc	see <a href="#">g.analyse</a>
snloc	see <a href="#">g.analyse</a>
wdayname	character with weekdayname
doquan	Boolean whether quantile analysis should be done
qllevels_names	object produced by <a href="#">g.analyse.avday</a>
doiglevels	Boolean to indicate whether iglevels should be calculated
tooshort	0 (file not too short) or 1 (file too short)
InterdailyStability	see <a href="#">g.IVIS</a>
IntradailyVariability	see <a href="#">g.IVIS</a>
IVIS_windowsize_minutes	see <a href="#">g.IVIS</a>
IVIS_epochsize_seconds	see <a href="#">g.IVIS</a>
qwindow	see <a href="#">g.analyse</a>
longitudinal_axis_id	Index of axis for which the angle correlates most strongly across 24 hours as calculated inside <a href="#">g.analyse</a> . For hip worn accelerometer this helps to check which axis was the vertical axis. The estimate may not be informative for other attachment locations.

**Value**

filesummary	summary for the file that was analysed
daysummary	Summary per day for the file that was analysed

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.applymetrics      *Extract metrics from acceleration signals*

---

**Description**

Function to extract metrics from acceleration signal. Not intended for direct use by user

**Usage**

```
g.applymetrics(data,n,sf,ws3,metrics2do,lb=0.2, hb=15)
```

**Arguments**

data	Three column matrix with x, y, and z acceleration data
n	filter order, only needed if a metric is selected that involves a frequency filter
sf	sample frequency
ws3	Epoch size in seconds
metrics2do	Dataframe with Boolean indicator for all metrics whether they should be extracted or not. For instance, metrics2do\$do.bfen = TRUE, indicates that the bfen metric should be extracted
lb	see <a href="#">g.metric</a>
hb	see <a href="#">g.metric</a>

**Value**

Dataframe with metric values in columns average per epoch (ws3)

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
Gx = runif(n=10000,min=0,max=2)
Gy = runif(n=10000,min=1,max=3)
Gz = runif(n=10000,min=0,max=2)
data = cbind(Gx, Gy, Gz)
metrics2do = data.frame(do.bfen=TRUE,do.enmo=TRUE,do.lfenmo=FALSE,
do.en=FALSE,do.hfen=FALSE,do.hfenplus=FALSE,do.mad=FALSE,do.anglex=FALSE,
do.angley=FALSE,do.anglez=FALSE,do.roll_med_acc_x=FALSE,
do.roll_med_acc_y=FALSE,do.roll_med_acc_z=FALSE,
do.dev_roll_med_acc_x=FALSE,do.dev_roll_med_acc_y=FALSE,
do.dev_roll_med_acc_z=FALSE,do.enmoa=FALSE,
do.lfx=FALSE, do.lfy=FALSE, do.lfz=FALSE,
do.hfx=FALSE, do.hfy=FALSE, do.hfz=FALSE,
do.bfx=FALSE, do.bfy=FALSE, do.bfz=FALSE)
extractedmetrics = g.applymetrics(data,n=4,sf=40,ws3=5,metrics2do)
```

---

g.binread	<i>function to read binary files as produced by the accelerometer named 'Genea', not to be confused with the 'GENEActiv' (see package GENEAread for this)</i>
-----------	---

---

**Description**

For reading the binary data as collected with a Genea accelerometer (Unilever Discover, UK). For reading GENEActive binary data, see package GENEAread.

**Usage**

```
g.binread(binfile, start = 0, end = 0)
```

**Arguments**

binfile	filename (required)
start	start point for reading data, this can either be a timestamp "year-month-day hr:min:sec" or a page number (optional)
end	end point for reading data, this can either be a timestamp "year-month-day hr:min:sec" or a page number (optional)

**Details**

If only start is defined then g.binread will read all data beyond start until the end of the file is reached

**Value**

rawxyz	matrix with raw x, y, and, z acceleration values
header	file header
timestamps1	timestamps for rawxyz in seconds since 1970-01-01 00:00
timestamps2	timestamps for rawxyz in day time format
batt.voltage	matrix with battery voltage and corresponding timestamps

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com> Jing Hua Zhao <jinghua.zhao@mrc-epid.cam.ac.uk>

---

g.calibrate	<i>function to estimate calibration error and make recommendation for addressing it</i>
-------------	---

---

**Description**

Function starts by identifying ten second windows of non-movement. Next, the average acceleration per axis per window is used to estimate calibration error (offset and scaling) per axis. The function provides recommended correction factors to address the calibration error and a summary of the callibration procedure.

**Usage**

```
g.calibrate(datafile, spherecrit = 0.3,
minloadcrit = 72,
printsummary = TRUE, chunksize=c(), windowsizes=c(5,900,3600),
selectdaysfile=c(),
dayborder=0, desiredtz = "", ...)
```

**Arguments**

datafile	name of accelerometer file
spherecrit	the minimum required acceleration value (in g) on both sides of 0 g for each axis. Used to judge whether the sphere is sufficiently populated
minloadcrit	the minimum number of hours the code needs to read for the autocalibration procedure to be effective (only sensitive to multitudes of 12 hrs, other values will be ceiled). After loading these hours only extra data is loaded if calibration error has not been reduced to under 0.01 g.
printsummary	if TRUE will print a summary when done
chunksize	number between 0.2 and 1 to specify the size of chunks to be loaded as a fraction of a 12 hour period, e.g. 0.5 equals 6 hour chunks. The default is 1 (12 hrs). For machines with less than 4Gb of RAM memory a value below 1 is recommended.

windowsizes	see <a href="#">g.getmeta</a>
selectdaysfile	see <a href="#">g.part1</a>
dayborder	see <a href="#">g.part1</a>
desiredtz	see <a href="#">g.getmeta</a>
...	Please ignore. Only used by the code internally when called from within g.part1 with selectdaysfile specific.

**Value**

scale	scaling correction values, e.g. c(1,1,1)
offset	offset correction values, e.g. c(0,0,0)
tempoffset	correction values related to temperature, e.g. c(0,0,0)
cal.error.start	absolute difference between Euclidean norm during all non-movement windows and 1 g before autocalibration
cal.error.end	absolute difference between Euclidean norm during all non-movement windows and 1 g after autocalibration
spheredata	average, standard deviation, Euclidean norm and temperature (if available) for all ten second non-movement windows as used for the autocalibration procedure
npoints	number of 10 second no-movement windows used to populate the sphere
nhoursused	number of hours of measurement data scanned to find the ten second time windows with no movement
meantempcal	mean temperature corresponding to the data as used for autocalibration. Only applies to data collected with GENEActiv monitor.

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)> Zhou Fang

**References**

- van Hees VT, Fang Z, Langford J, Assah F, Mohammad A, da Silva IC, Trenell MI, White T, Wareham NJ, Brage S. Auto-calibration of accelerometer data for free-living physical activity assessment using local gravity and temperature: an evaluation on four continents. *J Appl Physiol* (1985). 2014 Aug 7

**Examples**

```
## Not run:
datafile = "C:/myfolder/testfile.bin"

#Apply autocalibration:
C = g.calibrate(datafile)
print(C$scale)
print(C$offset)

## End(Not run)
```



---

`g.create.sp.mat`      *Converts sleep period information. Not intended for direct use*

---

**Description**

Function to convert data into sleep period matrix part of g.part4.R. Not intended for direct use by package user

**Usage**

```
g.create.sp.mat(nsp, spo, sleepdet.t, daysleep=FALSE)
```

**Arguments**

<code>nsp</code>	Integer indicating the number of sleep periods
<code>spo</code>	Empty matrix with overview of sleep periods, 5 columns and as long as nps
<code>sleepdet.t</code>	Part of detected sleep from g.sib.det for one night and one sleep definition
<code>daysleep</code>	Boolean to indicator whether this person woke up after noon (daysleeper)

**Value**

- spo matrix with start and end of each sleep period
- calendardate date corresponding to the day on which the night started
- item wdayname weekdayname

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

`g.createcoordinates`      *Create coordinates for [g.plot](#)*

---

**Description**

Function creates the coordinates for the blocks [g.plot](#) Function not designed for direct use by package user.

**Usage**

```
g.createcoordinates(r, timeline)
```

**Arguments**

r	Vector of zeros and ones reflecting the moments in time when there should be a block (1)
timeline	Vector of time indicators, this can be numbers or actual timestamps The length of timeline needs to match the length of argument r

**Value**

List with two objects: x0 with all the coordinates corresponding to the start of each blocks on the timelines and x1 with all the coordinates corresponding to the end of each block on the timeline

**Author(s)**

Vincent van Hees <v.vanhees@accelting.com>

---

g.cwaread	<i>Function to read .cwa-format files as produced by the accelerometer named 'Axivity'</i>
-----------	--

---

**Description**

For reading .cwa-format data, if you have .wav format data then see function [g.wavread](#)

**Usage**

```
g.cwaread(fileName, start = 0, end = 0, progressBar = FALSE,
  desiredtz = "", configtz = c())
```

**Arguments**

fileName	filename (required)
start	start point for reading data, this can either be a timestamp "year-month-day hr:min:sec" or a page number (optional)
end	end point for reading data, this can either be a timestamp "year-month-day hr:min:sec" or a page number (optional)
progressBar	Is trigger to switch on/off the text progress bar. If progressBar is TRUE then the function displays the progress bar but it works slightly slower
desiredtz	Desired timezone, see documentation <a href="#">g.getmeta</a>
configtz	Only functional for AX3 cwa data at the moment. Timezone in which the accelerometer was configured. Only use this argument if the timezone of configuration and timezone in which recording took place are different.

**Value**

data	dataframe with timestamp, raw x, -y, and, -z acceleration values, temperature, battery and light
header	file header

**Author(s)**

Evgeny Mirkes <em322@leicester.ac.uk> Vincent van Hees <v.vanhees@accelting.com>

---

*g.detecmidnight*      *Detect all midnights in a time series*

---

**Description**

Detect all midnights in a time series

**Usage**

```
g.detecmidnight(time,desiredtz, dayborder)
```

**Arguments**

time	Vector of timestamps, either in iso8601 or in POSIX format
desiredtz	See <a href="#">g.part2</a>
dayborder	see <a href="#">g.analyse</a>

**Value**

Output of the function is list containing the following objects:

- firstmidnight = timestamp of first midnight
- firstmidnighti = index of first midnight
- lastmidnight = timestamp of last midnight
- lastmidnighti = index of last midnight
- midnights = timestamps of midnights
- midnightsi = indeces of midnights

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.dotorcomma	<i>Assesses whether decimals in fileheader are stored with comma or dot separated decimals</i>
--------------	--

---

### Description

The function is used by [g.readaccfile](#) to assess how numeric data should be interpreted

### Usage

```
g.dotorcomma(inputfile,dformat,mon, desiredtz = "", ...)
```

### Arguments

inputfile	full path to inputfile
dformat	Data format code: 1=.bin, 2=.csv, 3=.wav, 4=.cwa
mon	Monitor code (accelorometer brand): 1=GENEA,2=GENEActiv,3=Actigraph, 4=Axivity.
desiredtz	Desired timezone, see documentation <a href="#">g.getmeta</a>
...	Any input arguments needed for function <a href="#">read.myacc.csv</a> if you are working with a non-standard csv formatted files.

### Value

Character object showing how decimals are separated

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

### Examples

```
## Not run:  
decn = g.dotorcomma(inputfile="C:/myfile.bin",dformat=1,mon=2)  
  
## End(Not run)
```

---

`g.downsample`      *Downsample a vector of numeric values at three time resolutions*

---

**Description**

Downsamples a vector of numeric values at three time resolutions: 1 seconds, ws3 seconds, and ws2 second. Function is not intended for direct interaction by package end user

**Usage**

```
g.downsample(sig, fs, ws3, ws2)
```

**Arguments**

<code>sig</code>	Vector of numeric values
<code>fs</code>	Sample frequency
<code>ws3</code>	ws3 epoch size, e.g. 5 seconds
<code>ws2</code>	ws2 epoch size, e.g. 90 seconds

**Value**

List with three object: var1, var2, and var3 corresponding to downsample time series at 1 seconds, ws2 seconds, and ws3 seconds resoluton, respectively

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
sig = runif(n=10000, min=1, max=10)
downsampled_sig = g.downsample(sig, fs=20, ws3=5, ws2=15)
```

---

`g.extractheadervars`      *Extracts header variables from header object*

---

**Description**

Function is not intended for direct interaction by package end user

**Usage**

```
g.extractheadervars(I)
```

**Arguments**

I                      Object produced by [g.inspectfile](#)

**Value**

- ID = participant identifier
- iid = investigator identifier
- HN = handedness
- BodyLocation = Attachment location of the sensor
- SX = sex
- deviceSerialNumber = serial number

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
data(data.inspectfile)
headervars = g.extractheadervars(I=data.inspectfile)
```

---

`g.getbout`                      *function to calculate bouts from vector of binary classes*

---

**Description**

To detect bouts of behaviour in time series. The function is used by [g.analyse](#)

**Usage**

```
g.getbout(x, boutduration, boutcriter=0.8, closedbout=FALSE,
bout.metric=1,ws3=5)
```

**Arguments**

x	vector of zeros and/or ones to be screened for bouts of ones
boutduration	duration of bout in epochs
boutcriter	Minimum percentage of boutduration for which the epoch values are expected to meet the threshold criterium
closedbout	TRUE if you want breaks in bouts to be counted towards time spent in bouts (argument only active for bout.metric 1 and 2)

bout.metric	If value=1 the code uses the MVPA bout definition as has been available since 2014 (see papers by Sabia AJE 2014 and da Silva IJE 2014). Here, the algorithm looks for 10 minute windows in which more than XX percent of the epochs are above mvpathreshold, and then counts the entire window as mvpa. If value=2 the code looks for a group or groups of epochs with a value above mvpathreshold that span a time window of at least mvpadur minutes in which more than boutcriter percent of the epochs are above the threshold. The motivation for the definition 1 was: A person who spends 10 minutes in MVPA with a 2 minute break in the middle is equally active as a person who spends 8 minutes in MVPA without taking a break. Therefore, both should be counted equal and counted as 10 minute MVPA bout. The motivation for the definition 2 is: not counting breaks towards MVPA simplifies interpretation and still counts the two persons in the example as each others equal. If value=3, using sliding window across the data to test bout criteria per window and do not allow for breaks of 1 minute or longer. If value=4, same as 3 but also requires the first and last epoch to require the threshold criteria.
ws3	epoch length in seconds, only needed for bout.metric =3, because it needs to measure how many epochs equal 1 minute breaks

**Value**

x	Vector with binary numbers indicator where bouts where detected
boutcount	Vector with binary numbers indicator where bouts where detected and counted towards time spent in bouts, see argument closedbout for clarification

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
y = g.getbout(x=round(runif(1000,0.4,1)),boutduration = 120,boutcriter=0.9,
  closedbout=FALSE,bout.metric=3,ws3=5)
```

---

g.getidfromheaderobject

*Extracts participant identifier from header object*

---

**Description**

Extracts participant identifier from header object, if it can not be found then the filename is used as identifier. Function is not intended for direct interaction by package end user

**Usage**

```
g.getidfromheaderobject(filename,header,dformat,mon)
```

**Arguments**

filename	File name
header	header object as extracted with <a href="#">g.inspectfile</a>
dformat	Data format code, same as for <a href="#">g.dotorcomma</a>
mon	Monitor code, same as for <a href="#">g.dotorcomma</a>

**Value**

Participant identifier as character

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
## Not run:
g.getidfromheaderobject(filename="C:/myfile.bin",header,dformat=2,mon=2)

## End(Not run)
```

---

`g.getM5L5`

*Extract M5 and L5 from time series*

---

**Description**

Extract M5 and L5 from time series, function used by [g.analyse](#) and not intended for direct use by package user. Please see [g.analyse](#) for further clarification on functionalities

**Usage**

```
g.getM5L5(varnum,ws3,t0_LFMF,t1_LFMF,M5L5res,winhr,qM5L5=c())
```

**Arguments**

varnum	Numeric vector of epoch values
ws3	Small epoch size in seconds
t0_LFMF	Start hour of the day for the M5L5 analyses, e.g. 0 for midnight
t1_LFMF	End hour of the day for the M5L5 analyses, e.g. 24 for midnight
M5L5res	Resolution of hte M5L5 analyses in minutes
winhr	window size of M5L5 analyses, e.g. 5 hours
qM5L5	Percentiles (quantiles) to be calculated over L5 and M5 window.



**Value**

- DAYL5HOUR = Starting time in hours of L5
- DAYL5VALUE = average acceleration during L5
- DAYM5HOUR = Starting time in hours of M5
- DAYM5VALUE = average acceleration during M5
- V5NIGHT = average acceleration between 1am and 6am

**Author(s)**

Vincent T van Hees <v.vanhees@accltelting.com>

**Examples**

```
data(data.getmeta)
g.getM5L5 = function(varnum=data.getmeta,ws3=5,t0_LFMF=0,
t1_LFMF=24,M5L5res=10,winhr=5)
```

---

<code>g.getmeta</code>	<i>function to extract meta-data (features) from data in accelerometer file</i>
------------------------	---

---

**Description**

Reads a accelerometer file in blocks, extracts various features and stores average feature value per short or long epoch. Acceleration and angle metrics are stored at short epoch length. The non-wear indication score, the clipping score, temperature (if available), light (if available), and Euclidean norm are stored at long epoch length. The function has been designed and thoroughly tested with accelerometer files from GENEActiv and GENEActiv. Further, the function should be able to cope with csv-format data procuded by GENEActiv and Actigraph

**Usage**

```
g.getmeta(datafile, desiredtz = "",
windowsizes = c(5, 900, 3600),daylimit = FALSE,
offset = c(0,0,0), scale = c(1,1,1),
tempoffset = c(0,0,0),do.bfen = FALSE, do.enmo = TRUE,
do.lfenmo = FALSE, do.en = FALSE,
do.hfen = FALSE, do.hfenplus = FALSE, do.mad = FALSE,
do.anglex=FALSE,do.anglez=FALSE,do.anglez=FALSE,
do.roll_med_acc_x=FALSE,do.roll_med_acc_y=FALSE,
do.roll_med_acc_z=FALSE,do.dev_roll_med_acc_x=FALSE,
do.dev_roll_med_acc_y=FALSE,do.dev_roll_med_acc_z=FALSE,
do.enmoa = FALSE, do.lfen = FALSE,
do.lfx=FALSE, do.lfy=FALSE, do.lfz=FALSE,
do.hfx=FALSE, do.hfy=FALSE, do.hfz=FALSE,
do.bfx=FALSE, do.bfy=FALSE, do.bfz=FALSE,
lb = 0.2,hb = 15, n = 4,
```

```
meantempcal=c(), chunksize=c(),
selectdaysfile=c(), dayborder=0, dynrange=c(), configtz=c(),
myfun=c(), ...)
```

### Arguments

datafile	name of accelerometer file
desiredtz	desired timezone: see also <a href="http://en.wikipedia.org/wiki/Zone.tab">http://en.wikipedia.org/wiki/Zone.tab</a>
window sizes	Three values to indicate the lengths of the windows as in <code>c(window1,window2,window3)</code> : window1 is the short epoch length in seconds and by default 5 this is the time window over which acceleration and angle metrics are calculated, window2 is the long epoch length in seconds for which non-wear and signal clipping are defined, default 900. However, window3 is the window length of data used for non-wear detection and by default 3600 seconds. So, when window3 is larger than window2 we use overlapping windows, while if window2 equals window3 non-wear periods are assessed by non-overlapping windows. Window2 is expected to be a multitude of 60 seconds.
daylimit	number of days to limit (roughly), if set to FALSE no daylimit will be applied
offset	offset correction value per axis, usage: <code>value = scale(value,center = -offset, scale = 1/scale)</code>
scale	scaling correction value per axis, usage: <code>value = scale(value,center = -offset, scale = 1/scale)</code>
tempoffset	temperature offset correction value per axis, usage: <code>value = scale(value,center = -offset, scale = 1/scale) + scale(temperature, center = rep(averagetemperature,3), scale = 1/tempoffset)</code>
do.bfen	if TRUE, calculate metric BFEN with band-pass filter configuration set by lb and hb
do.enmo	if TRUE (default), calculate metric ENMO with negative values rounded to zero
do.lfenmo	if TRUE, calculate metric LFENMO with low-pass filter configuration set by hb
do.en	if TRUE, calculate metric EN
do.hfen	if TRUE, calculate metric HFEN with low-pass filter configuration set by hb
do.hfenplus	if TRUE, calculate metric HFENplus with band-pass filter configuration set by lb and hb
do.mad	if TRUE, calculate metric MAD (Mean Amplitude Deviarion)
do.anglex	if TRUE, calculate the angle of the x-axis relative to the horizontal plane (degrees) utilizing all three axes
do.angley	if TRUE, calculate the angle of the y-axis relative to the horizontal plane (degrees) utilizing all three axes
do.anglez	if TRUE, calculate the angle of the z-axis relative to the horizontal plane (degrees) utilizing all three axes
do.enmoa	if TRUE (default), calculate metric ENMOa which is equal to metric ENMO but with the absolute taken from the Euclidean norm minus one.
do.roll_med_acc_x	if TRUE, calculate rolling median for the x axis

do.roll_med_acc_y	if TRUE, calculate rolling median for the y axis
do.roll_med_acc_z	if TRUE, calculate rolling median for the z axis
do.dev_roll_med_acc_x	if TRUE, calculate deviations from rolling median for the x axis
do.dev_roll_med_acc_y	if TRUE, calculate deviations from rolling median for the y axis
do.dev_roll_med_acc_z	if TRUE, calculate deviations from rolling median for the z axis
do.lfen	if TRUE, calculate metric EN with low-pass filtered inputted signals using configuration set by hb
do.lfx	if TRUE, calculate average absolute low-pass filtered x-axis with filter configuration set by hb.
do.lfy	if TRUE, calculate average absolute low-pass filtered y-axis with filter configuration set by hb.
do.lfz	if TRUE, calculate average absolute low-pass filtered z-axis with filter configuration set by hb.
do.hfx	if TRUE, calculate average absolute low-pass filtered x-axis with filter configuration set by lb.
do.hfy	if TRUE, calculate average absolute low-pass filtered y-axis with filter configuration set by lb.
do.hfz	if TRUE, calculate average absolute low-pass filtered z-axis with filter configuration set by lb.
do.bfx	if TRUE, calculate average absolute band-pass filtered x-axis with filter configuration set by lb and by hb.
do.bfy	if TRUE, calculate average absolute band-pass filtered y-axis with filter configuration set by lb and by hb.
do.bfz	if TRUE, calculate average absolute band-pass filtered z-axis with filter configuration set by lb and by hb.
lb	lower boundary of the frequency filter (in Hertz)
hb	upper boundary of the frequency filter (in Hertz)
n	order of the frequency filter
meantempcal	mean temperature corresponding to the data as used for autocalibration. If autocalibration is not done or if temperature was not available then leave blank (default)
chunksize	number between 0.2 and 1 to specify the size of chunks to be loaded as a fraction of a 24 hour period, e.g. 0.5 equals 12 hour chunks. The default is 1 (24 hrs). For machines with less than 4 Gb of RAM memory a value below 1 is recommended.
selectdaysfile	see <a href="#">g.part1</a>
dayborder	see <a href="#">g.part1</a>

dynrange	see <a href="#">g.part1</a>
configtz	Only functional for AX3 cwa data at the moment. Timezone in which the accelerometer was configured. Only use this argument if the timezone of configuration and timezone in which recording took place are different.
myfun	External function object to be applied to raw data. See details <a href="#">applyExtFunction</a> .
...	Please ignore. Only used by the code internally when called from within <code>g.part1</code> with <code>selectdaysfile</code> specific.

**Value**

metalong	dataframe with long epoch meta-data: EN, non-wear score, clipping score, temperature
metashort	dataframe with short epoch meta-data: timestamp and metric
tooshort	indicator of whether file was too short for processing (TRUE or FALSE)
corrupt	indicator of whether file was considered corrupt (TRUE or FALSE)

**Author(s)**

Vincent T van Hees <[v.vanhees@accltelting.com](mailto:v.vanhees@accltelting.com)>

**References**

- van Hees VT, Gorzelniak L, Dean Leon EC, Eder M, Pias M, et al. (2013) Separating Movement and Gravity Components in an Acceleration Signal and Implications for the Assessment of Human Daily Physical Activity. *PLoS ONE* 8(4): e61691. doi:10.1371/journal.pone.0061691
- Aittasalo M, Vaha-Ypya H, Vasankari T, Husu P, Jussila AM, and Sievanen H. Mean amplitude deviation calculated from raw acceleration data: a novel method for classifying the intensity of adolescents physical activity irrespective of accelerometer brand. *BMC Sports Science, Medicine and Rehabilitation* (2015).

**Examples**

```
## Not run:
datafile = "C:/myfolder/testfile.bin"

#Extract meta-data:
M = g.getmeta(datafile)

#Inspect first couple of rows of long epoch length meta data:
print(M$metalong[1:5,])

#Inspect first couple of rows of short epoch length meta data:
print(M$metalong[1:5,])

## End(Not run)
```

---

g.getstarttime	<i>Extract start time of a measurement</i>
----------------	--

---

**Description**

Extract start time of a measurement. GGIR calculates all timestamps by using the first timestamp and sample frequency. Not intended for direct use by package user

**Usage**

```
g.getstarttime(datafile, P, header, mon, dformat, desiredtz,
selectdaysfile)
```

**Arguments**

datafile	Full path to data file
P	Object extracted with <a href="#">g.readaccfile</a>
header	File header extracted with <a href="#">g.inspectfile</a>
mon	Same as in <a href="#">g.dotorcomma</a>
dformat	Same as in <a href="#">g.dotorcomma</a>
desiredtz	Same as in <a href="#">g.dotorcomma</a>
selectdaysfile	See <a href="#">g.part1</a>

**Value**

The starttime

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.impute	<i>function to identify invalid periods in the meta-data as generated by <a href="#">g.getmeta</a> and to impute these invalid periods with the average of similar timepoints on other days of the measurement</i>
----------	--

---

**Description**

Functions takes the output from [g.getmeta](#) and information about the study protocol to label impute invalid time segments in the data.

**Usage**

```
g.impute(M, I, strategy = 1, hrs.del.start = 0, hrs.del.end = 0,
maxdur = 0, ndayswindow = 7,desiredtz="", dayborder= 0, TimeSegments2Zero =c())
```

**Arguments**

M	output from <a href="#">g.getmeta</a>
I	output from <a href="#">g.inspectfile</a>
strategy	how to deal with knowledge about study protocol. value = 1 means select data based on hrs.del.start, hrs.del.end, and maxdur. Value = 2 makes that only the data between the first midnight and the last midnight is used for imputation. Value = 3 only selects the most active X days in the files. X is specified by argument ndayswindow
hrs.del.start	how many HOURS after start of experiment did wearing of monitor start?
hrs.del.end	how many HOURS before the end of the experiment did wearing of monitor definitely end?
maxdur	How many DAYS after start of experiment did experiment definitely stop? (set to zero if unknown = default)
ndayswindow	If strategy is set to 3 then this is the size of the window as a number of days
desiredtz	see <a href="#">g.getmeta</a>
dayborder	see <a href="#">g.analyse</a>
TimeSegments2Zero	Optional data.frame to specify which time segments need to be ignored for the imputation, and acceleration metrics to be imputed by zeros. The data.frame is expected to contain two columns named windowstart and windowend, with the start- and end time of the time segment in POSIXlt class.

**Value**

metashort	imputed short epoch variables
rout	matrix to clarify when data was imputed for each long epoch time window and the reason for imputation. Value = 1 indicates imputation. Columns 1 = monitor non wear, column 2 = clipping, column 3 = additional nonwear, column 4 = protocol based exclusion and column5 = sum of column 1,2,3 and 4.
averageday	matrix with n columns for n metrics values and m rows for m short epoch time windows in an average 24 hours period

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
## Not run:
#inspect file:
I = g.inspectfile(datafile)

#autocalibration:
C = g.calibrate(datafile)

#get meta-data:
```

```

M = g.getmeta(datafile)

## End(Not run)

data(data.getmeta)
data(data.inspectfile)

#impute meta-data:
IMP = g.impute(M=data.getmeta, I=data.inspectfile)

```

---

g.inspectfile	<i>function to inspect accelerometer file for brand, sample frequency and header</i>
---------------	--

---

### Description

Inspects accelerometer file for key information, including: monitor brand, sample frequency and file header

### Usage

```
g.inspectfile(datafile, desiredtz = "", ...)
```

### Arguments

datafile	name of data file
desiredtz	Desired timezone, see documentation <a href="#">g.getmeta</a>
...	Any input arguments needed for function <a href="#">read.myacc.csv</a> if you are working with a non-standard csv formatted files.

### Value

header	fileheader
monn	monitor name (genea, geneactive)
monc	monitor brand code (1 = genea; 2 = geneactive, 3 = actigraph)
dformn	data format (bin, csv)
dformc	data format code (1 = bin, 2 = csv)
sf	samplefrequency in Hertz
filename	filename

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

`g.intensitygradient`     *Intensity gradient calculation*

---

### Description

Calculates the intensity gradient based on Rowlands et al. 2018. The function assumes that the user has already calculated the value distribution.

### Usage

```
g.intensitygradient(x,y)
```

### Arguments

<code>x</code>	Numeric vector of mid-points of the bins (mg)
<code>y</code>	Numeric vector of time spent in bins (minutes)

### Value

<code>y_intercept</code>	y-intercept of a linear regression line in log-log space
<code>gradient</code>	Beta coefficient of a linear regression line in log-log space
<code>rsquared</code>	R squared of x and y values in log-log space

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

### References

Rowlands A, Edwardson CL, et al. (2018) Beyond Cut Points: Accelerometer Metrics that Capture the Physical Activity Profile. *MSSE* 50(6):1. doi:10.1249/MSS.0000000000001561

---

`g.IVIS`     *Calculates IV and IS*

---

### Description

To extract interdaily stability and interdaily variability as originally proposed by van Someren. Note that we had to improvise our replication of his metric, because GGIR does not attempt to calculate count values. The implementation in this function has so far not be evaluated yet.

### Usage

```
g.IVIS(Xi, epochsizesecondsXi = 5, IVIS_epochsize_seconds = 3600,
IVIS_windowsize_minutes = 60, IVIS.activity.metric = 1)
```



**Arguments**

`Xi` Vector with acceleration values, e.g. ENMO metric.

`epochsizessecondsXi` Epoch size of the values in `Xi` expressed in seconds.

`IVIS_epochsize_seconds` Epoch size of the Intradaily Variability (IV) and Interdaily Stability (IS) metrics in seconds

`IVIS_windowsize_minutes` Window size of the Intradaily Variability (IV) and Interdaily Stability (IS) metrics in minutes

`IVIS.activity.metric` Metric used for activity calculation. Value = 1, uses continuous scaled acceleration. Value = 2, tries to collapse it into a binary score of rest versus active to try to simulate the original approach.

**Value**

`InterdailyStability`

`IntradailyVariability`

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**References**

- Eus J. W. Van Someren, Dick F. Swaab, Christopher C. Colenda, Wayne Cohen, W. Vaughn McCall & Peter B. Rosenquist. Bright Light Therapy: Improved Sensitivity to Its Effects on Rest-Activity Rhythms in Alzheimer Patients by Application of Nonparametric Methods/Chronobiology International. 1999. Volume 16, issue 4.

**Examples**

```
Xi = abs(rnorm(n = 10000, mean = 0.2))
IVISvariables = g.IVIS(Xi=Xi)
```

---

`g.loadlog`

*Load and clean sleeplog information*

---

**Description**

Loads sleeplog from a csv input file and applies sanity checks before storing the output in a dataframe

**Usage**

```
g.loadlog(loglocation=c(),coln1=c(),colid=c(),nights=c(),
sleeplogidnum=TRUE)
```

**Arguments**

```
loglocation    See g.part4
coln1          See g.part4
colid          See g.part4
nights        See g.part4
sleeplogidnum See g.part4
```

**Value**

Data frame with sleeplog

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
## Not run:
sleeplog = g.loadlog(loglocation="C:/mysleeplog.csv",coln1=2,
colid=1,nights=5,sleeplogidnum=TRUE)

## End(Not run)
```

---

g.metric

*Extract metrics from acceleration signals*

---

**Description**

Function to extract metrics from acceleration signal. Not intended for direct use by package user

**Usage**

```
g.metric(data,n=c()),sf,ii,TW=c(),lb=c(),hb=c(),gravity = 1)
```

**Arguments**

```
data          Three column matrix with x, y, and z acceleration data
n             filter order, only needed if a metric is selected that involves a frequency filter
sf           sample frequency
ii           Integer to indicate which metric should be derived
```

TW	Time window size in samples used if the metric involves a time window
lb	Cut-off frequency corresponding to the lower boundary of frequency filter
hb	Cut-off frequency corresponding to the higher boundary of frequency filter
gravity	Size of gravity, default = 1

**Value**

Vector of metric values at the same time resolution as the input data

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
Gx = runif(n=10000,min=0,max=2)
Gy = runif(n=10000,min=1,max=3)
Gz = runif(n=10000,min=0,max=2)
data = cbind(Gx, Gy, Gz)
EuclideanNorm = g.metric(data,sf=40,ii=3,gravity = 1)
```

---

g.part1

*function to load and pre-process acceleration files*


---

**Description**

Calls function [g.getmeta](#) and [g.calibrate](#), and converts the output to .RData-format which will be the input for [g.part2](#). Here, the function generates a folder structure to keep track of various output files. The reason why these [g.part1](#) and [g.part2](#) are not merged as one generic shell function is because [g.part1](#) takes much longer to and involves only minor decisions of interest to the movement scientist. Function [g.part2](#) on the other hand is relatively fast and comes with all the decisions that directly impact on the variables that are of interest to the movement scientist. Therefore, the user may want to run [g.part1](#) overnight or on a computing cluster, while [g.part2](#) can then be the main playing ground for the movement scientist. Function [g.shell.GGIR](#) provides the main shell that allows for operating [g.part1](#) and [g.part2](#).

**Usage**

```
g.part1(datadir=c(),outputdir=c(),f0=1,f1=c(),
        window sizes = c(5,900,3600),
        desiredtz = "",chunksize=c(),studynome=c(),
        do.enmo = TRUE,do.lfenmo = FALSE,do.en = FALSE,
        do.bfen = FALSE, do.hfen=FALSE, do.hfenplus = FALSE,
        do.mad = FALSE, do.anglex=FALSE, do.angley=FALSE,
        do.anglez=FALSE, do.enmoa=FALSE,
        do.roll_med_acc_x=FALSE, do.roll_med_acc_y=FALSE,
        do.roll_med_acc_z=FALSE, do.dev_roll_med_acc_x=FALSE,
```

```

do.dev_roll_med_acc_y=FALSE, do.dev_roll_med_acc_z=FALSE,
do.lfen = FALSE, do.lfx=FALSE, do.lfy=FALSE, do.lfz=FALSE,
    do.hfx=FALSE, do.hfy=FALSE, do.hfz=FALSE,
    do.bfx=FALSE, do.bfy=FALSE, do.bfz=FALSE,
do.cal = TRUE, lb = 0.2, hb = 15, n = 4,
spherecrit=0.3,minloadcrit=72,
printsummary=TRUE,print.filename=FALSE,overwrite=FALSE,
backup.cal.coef="retrieve",selectdaysfile=c(),dayborder=0,
dynrange=c(), configtz=c(), do.parallel=TRUE, minimumFileSizeMB = 2,
myfun=c(), ...)

```

### Arguments

datadir	Directory where the accelerometer files are stored or list of accelerometer file-names and directories
outputdir	Directory where the output needs to be stored. Note that this function will attempt to create folders in this directory and uses those folder to organise output
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)
window sizes	see <a href="#">g.getmeta</a>
desiredtz	see <a href="#">g.getmeta</a>
chunksize	see <a href="#">g.getmeta</a>
studyname	If the datadir is a folder then the study will be given the name of the data directory. If datadir is a list of filenames then the studyname will be used as name for the analysis
do.bfen	if TRUE, calculate metric BFEN with band-pass filter configuration set by lb and hb, see <a href="#">g.getmeta</a>
do.enmo	if TRUE (default), calculate metric ENMO, see <a href="#">g.getmeta</a>
do.lfenmo	if TRUE, calculate metric LFENMO with low-pass filter configuration set by hb, see <a href="#">g.getmeta</a>
do.en	if TRUE, calculate metric EN, see <a href="#">g.getmeta</a>
do.hfen	if TRUE, calculate metric HFEN with low-pass filter configuration set by hb, see <a href="#">g.getmeta</a>
do.hfenplus	if TRUE, calculate metric HFENplus with band-pass filter configuration set by lb and hb, see <a href="#">g.getmeta</a>
do.mad	if TRUE, calculate metric MAD (Mean Amplitude Deviation), see <a href="#">g.getmeta</a>
do.anglex	if TRUE, calculate the angle of the x-axis relative to the horizontal plane (degrees) utilizing all three axes
do.angley	if TRUE, calculate the angle of the y-axis relative to the horizontal plane (degrees) utilizing all three axes
do.anglez	if TRUE, calculate the angle of the z-axis relative to the horizontal plane (degrees) utilizing all three axes

do.enmoa	if TRUE (default), calculate metric ENMOa which is equal to metric ENMO but with the absolute taken from the Euclidean norm minus one.
do.roll_med_acc_x	see <a href="#">g.getmeta</a>
do.roll_med_acc_y	see <a href="#">g.getmeta</a>
do.roll_med_acc_z	see <a href="#">g.getmeta</a>
do.dev_roll_med_acc_x	see <a href="#">g.getmeta</a>
do.dev_roll_med_acc_y	see <a href="#">g.getmeta</a>
do.dev_roll_med_acc_z	see <a href="#">g.getmeta</a>
do.lfen	see <a href="#">g.getmeta</a>
do.lfx	see <a href="#">g.getmeta</a>
do.lfy	see <a href="#">g.getmeta</a>
do.lfz	see <a href="#">g.getmeta</a>
do.hfx	see <a href="#">g.getmeta</a>
do.hfy	see <a href="#">g.getmeta</a>
do.hfz	see <a href="#">g.getmeta</a>
do.bfx	see <a href="#">g.getmeta</a>
do.bfy	see <a href="#">g.getmeta</a>
do.bfz	see <a href="#">g.getmeta</a>
do.cal	Whether to apply auto-calibration or not, see <a href="#">g.calibrate</a> . Default and recommended setting is TRUE
lb	lower boundary of the frequency filter (in Hertz)
hb	upper boundary of the frequency filter (in Hertz), see <a href="#">g.getmeta</a>
n	order of the frequency filter, see <a href="#">g.getmeta</a>
spherecrit	see <a href="#">g.calibrate</a> the minimum required acceleration value (in g) on both sides of 0 g for each axis. Used to judge whether the sphere is sufficiently populated
minloadcrit	see <a href="#">g.calibrate</a> the minimum number of hours the code needs to read for the autocalibration procedure to be effective (only sensitive to multitudes of 12 hrs, other values will be ceiled). After loading these hours only extra data is loaded if calibration error has not be reduced to under 0.01 g.
printsummary	see <a href="#">g.calibrate</a> if TRUE will print a summary when done
print.filename	Whether to print the filename before before analysing it (default is FALSE). Printing the filename can be useful to investigate problems (e.g. to verify that which file is being read).
overwrite	Overwrite previously generated milestone data by this function for this particular dataset. If FALSE then it will skip the previously processed files (default = FALSE).

<code>backup.cal.coef</code>	Default "retrieve". Option to use backed-up calibration coefficient instead of deriving the calibration coefficients when analysing the same file twice, see details.
<code>selectdaysfile</code>	Optional functionality. Character pointing at a csv file holding the relationship between device serial numbers (first column) and measurement dates of interest (second and third column). The date format should be dd/mm/yyyy. And the first row if the csv file is assumed to have a character variable names, e.g. "serialnumber" "Day1" and "Day2" respectively. Raw data will be extracted and stored in the output directory in a new subfolder named 'raw'.
<code>dayborder</code>	Hour at which days start and end (default = 0), value = 4 would mean 4 am
<code>dynrange</code>	Optional, provide dynamic range for accelerometer data to overwrite hardcoded 6 g for GENE A and 8 g for other brands
<code>configtz</code>	Only functional for AX3 cwa data at the moment. Timezone in which the accelerometer was configured. Only use this argument if the timezone of configuration and timezone in which recording took place are different.
<code>do.parallel</code>	Boolean whether to use multi-core processing (only works if at least 4 CPU cores are available).
<code>minimumFileSizeMB</code>	Minimum File size in MB required to enter processing, default 2MB. This argument can help to avoid having short uninformative files to enter the analyses. Given that a typical accelerometer collects several MBs per hour, the default setting should only skip the very short files.
<code>myfun</code>	External function object to be applied to raw data. See details <a href="#">applyExtFunction</a> .
<code>...</code>	Any input arguments needed for function <a href="#">read.myacc.csv</a> if you are working with a non-standard csv formatted files.

## Details

Argument `backup.cal.coef` has two usecase. Use case 1: If the auto-calibration fails then the user has the option to provide back-up calibration coefficients via this argument. The value of the argument needs to be the name and directory of a csv-spreadsheet with the following column names and subsequent values: 'filename' with the names of accelerometer files on which the calibration coefficients need to be applied in case auto-calibration fails; 'scale.x', 'scale.y', and 'scale.z' with the scaling coefficients; 'offset.x', 'offset.y', and 'offset.z' with the offset coefficients, and; 'temperature.offset.x', 'temperature.offset.y', and 'temperature.offset.z' with the temperature offset coefficients. This can be useful for analysing short lasting laboratory experiments with insufficient sphere data to perform the auto-calibration, but for which calibration coefficients can be derived in an alternative way. It is the users responsibility to compile the csv-spreadsheet. Instead of building this file the user can also

Use case 2: The user wants to avoid performing the auto-calibration repeatedly on the same file. If `backup.cal.coef` value is set to "retrieve" (default) then GGIR will look out for the `data_quality_report.csv` file in the outputfolder QC, which holds the previously generated calibration coefficients. If you do not want this happen, then deleted the `data_quality_report.csv` from the QC folder or set it to value "redo".

**Value**

The function provides no values, it only ensures that the output from other functions is stored in .RData(one file per accelerometer file) in folder structure

**Author(s)**

Vincent T van Hees <vincentvanhees@gmail.com>

**References**

- van Hees VT, Gorzelniak L, Dean Leon EC, Eder M, Pias M, et al. (2013) Separating Movement and Gravity Components in an Acceleration Signal and Implications for the Assessment of Human Daily Physical Activity. PLoS ONE 8(4): e61691. doi:10.1371/journal.pone.0061691
- van Hees VT, Fang Z, Langford J, Assah F, Mohammad A, da Silva IC, Trenell MI, White T, Wareham NJ, Brage S. Auto-calibration of accelerometer data for free-living physical activity assessment using local gravity and temperature: an evaluation on four continents. J Appl Physiol (1985). 2014 Aug 7
- Aittasalo M, Vaha-Ypya H, Vasankari T, Husu P, Jussila AM, and Sievanen H. Mean amplitude deviation calculated from raw acceleration data: a novel method for classifying the intensity of adolescents physical activity irrespective of accelerometer brand. BMC Sports Science, Medicine and Rehabilitation (2015).

**Examples**

```
## Not run:
datafile = "C:/myfolder/mydata"
outputdir = "C:/myresults"
g.part1(datadir,outputdir)

## End(Not run)
```

---

g.part2

*function to analyse and summarize pre-processed output from [g.part1](#)*


---

**Description**

Loads the output from [g.part1](#) and then applies [g.impute](#) and [g.analyse](#), after which the output is converted to .RData-format which will be used by [g.shell.GGIR](#) to generate reports. The variables in these reports are the same variables as described in [g.analyse](#).

**Usage**

```
g.part2(datadir=c(),metadatadir=c(),f0=c(),f1=c()),strategy = 1,
hrs.del.start = 0.5,hrs.del.end = 0.5, maxdur = 7,
includedaycrit = 16, L5M5window = c(0,24), M5L5res = 10,
winhr = 5, qwindow=c(0,24), qlevels = c(0.1),
ilevels = c(0,10), mvpathreshold = c(100),
```

```

boutcriter = 0.8, ndayswindow=7, idloc=1,
do.imp=TRUE, storefolderstructure=FALSE, overwrite=FALSE,
epochvalues2csv=FALSE, mvpadur=c(1,5,10), selectdaysfile=c(),
window.summary.size=10, dayborder=0,
bout.metric=2, closedbout=FALSE, desiredtz="",
IVIS_windowsize_minutes = 60, IVIS_epochsize_seconds = 3600,
iglevels = c(), IVIS.activity.metric=1, TimeSegments2ZeroFile = c(),
qm5L5=c(), do.parallel = TRUE, myfun=c())

```

## Arguments

datadir	Directory where the accelerometer files are stored or list, e.g. "C:/mydata" of accelerometer filenames and directories, e.g. c("C:/mydata/myfile1.bin", "C:/mydata/myfile2.bin").
metadatadir	Directory where the output from <a href="#">g.part1</a> was stored
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)
strategy	how to deal with knowledge about study protocol. value = 1 to select data based on hrs.del.start, hrs.del.end, and maxdur. Value = 2 to only use the data between the first midnight and the last midnight, value = 3 only selects the most active X days in the files. X is specified by argument ndayswindow See also <a href="#">g.impute</a>
hrs.del.start	how many HOURS after start of experiment did wearing of monitor start?, see <a href="#">g.impute</a>
hrs.del.end	how many HOURS before the end of the experiment did wearing of monitor definitely end?, see <a href="#">g.impute</a>
maxdur	how many DAYS after start of experiment did experiment definitely stop? (set to zero if unknown = default), see <a href="#">g.impute</a>
includedaycrit	minimum required number of valid hours in day specific analysis (NOTE: there is no minimum required number of hours per day in the summary of an entire measurement, every available hour is used to make the best possible inference on average metric value per week)
L5M5window	Argument deprecated after version 1.5-24. This argument used to define the start and end time, in 24 hour clock hours, over which L5M5 needs to be calculated. Now this is done with argument qwindow.
M5L5res	resolution of L5 and M5 analysis in minutes (default: 10 minutes)
winhr	Vector of window size(s) (unit: hours) of L5 and M5 analysis (default = 5 hours)
qwindow	see <a href="#">g.analyse</a>
qllevels	array of percentiles for which value needs to be extracted. These need to be expressed as a fraction of 1, e.g. c(0.1, 0.5, 0.75). There is no limit to the number of percentiles. If left empty then percentiles will not be extracted. Distribution will be derived from short epoch metric data, see <a href="#">g.getmeta</a> .
ilevels	Levels for acceleration value frequency distribution in mg, e.g. c(0,100,200) There is no constriction to the number of levels.



mvpthreshold	Threshold for MVPA estimation. Threshold needs to be based on metric ENMO. This can be a single number or an array of numbers, e.g. c(100,120). In the later case the code will estimate MVPA separately for each threshold. If this variable is left blank c() then MVPA is not estimated
boutcriter	The variable boutcriter is a number between 0 and 1 and defines what fraction of a bout needs to be above the mvpthreshold
ndayswindow	If strategy is set to 3 then this is the size of the window as a number of days
idloc	If value = 1 (default) the code assumes that ID number is stored in the obvious header field. If value = 2 the code uses the character string preceding the character '_' in the filename as the ID number
do.imp	Whether to impute missing values (e.g. suspected of monitor non-wear) or not by <a href="#">g.impute</a> . Default and recommended setting is TRUE
storefolderstructure	Store folder structure of the accelerometer data
overwrite	Overwrite previously generated milestone data by this function for this particular dataset. If FALSE then it will skip the previously processed files (default = FALSE).
epochvalues2csv	If TRUE then epoch values are exported to a CSV spreadsheet. Here, non-wear time is imputed where possible (default = FALSE).
mvpadur	default = c(1,5,10). Three bout duration for which MVPA will be calculated
selectdaysfile	Functionality designed for the London Centre of Longitudinal studies. Csv file holding the relation between device serial numbers and measurement days of interest.
dayborder	Hour at which days start and end (default = 0), value = 4 would mean 4am
window.summary.size	Functionality designed for the London Centre of Longitudinal studies. Size in minutes of the summary window
bout.metric	This argument used to be called mvpa.2014 and had TRUE or FALSE as its value. However, it has now become clear that this aspect of the analyses is still very much open for debate. Therefore, I have changed it into an argument where you can specify a metric for bout detection based on a number. A description of these bout metrics can be found in the new function <a href="#">g.getbout</a>
closedbout	See <a href="#">g.getbout</a>
desiredtz	see <a href="#">g.getmeta</a>
IVIS_windowsize_minutes	see function <a href="#">g.IVIS</a>
IVIS_epochsize_seconds	see function <a href="#">g.IVIS</a>
iglevels	see function <a href="#">g.analyse</a>
TimeSegments2ZeroFile	Csv-file holding the data.frame used for argument TimeSegments2Zero in function <a href="#">g.impute</a>

IVIS.activity.metric	see function <a href="#">g.IVIS</a>
qM5L5	see function <a href="#">g.getM5L5</a>
do.parallel	Boolean whether to use multi-core processing (only works if at least 4 CPU cores are available).
myfun	External function object to be applied to raw data, see <a href="#">g.getmeta</a> .

## Value

The function provides no values, it only ensures that other functions are called and that their output is stored in the folder structure as created with [g.part1](#).

## Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

## References

- van Hees VT, Gorzelniak L, Dean Leon EC, Eder M, Pias M, et al. (2013) Separating Movement and Gravity Components in an Acceleration Signal and Implications for the Assessment of Human Daily Physical Activity. PLoS ONE 8(4): e61691. doi:10.1371/journal.pone.0061691
- van Hees VT, Fang Z, Langford J, Assah F, Mohammad A, da Silva IC, Trenell MI, White T, Wareham NJ, Brage S. Auto-calibration of accelerometer data for free-living physical activity assessment using local gravity and temperature: an evaluation on four continents. J Appl Physiol (1985). 2014 Aug 7

## Examples

```
## Not run:
metadatadir = "C:/myresults/output_mystudy"
g.part2(metadatadir)

## End(Not run)
```

---

g.part3	<i>Detection of sustained inactivity periods as needed for sleep detection in g.part4.</i>
---------	--

---

## Description

Function called by `g.shell.GGIR`. It estimates the sustained inactivity periods in each day, which are used as input for `g.part4` which then labels them as nocturnal sleep or day time sustained inactivity periods. Typical users should work with function `g.shell.GGIR` only.

**Usage**

```
g.part3(metadataadir=c(),f0,f1,anglethreshold = 5,timethreshold = 5,
  acc.metric="ENMO", ignorenonwear=TRUE, overwrite=FALSE,
  desiredtz="",constrain2range=TRUE,
  do.part3.pdf=TRUE, do.parallel=TRUE, dayborder=0, myfun=c())
```

**Arguments**

metadataadir	Directory that holds a folder 'meta' and inside this a folder 'basic' which contains the milestone data produced by g.part1. The folderstructure is normally created by g.part1 and g.shell.GGIR will recognise what the value of metadataadir is.
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)
anglethreshold	Angle threshold (degrees) for sustained inactivity periods detection, default = 5
timethreshold	Time threshold (minutes) for sustained inactivity periods detection, default = 5. This can be specified as multiple thresholds, each of which will be implemented. For example, timethreshold = c(5,10)
acc.metric	Which one of the metrics do you want to consider to analyze L5. The metric of interest need to be calculated in M (see <a href="#">g.part1</a> )
ignorenonwear	If TRUE then ignore detected monitor non-wear periods to avoid confusion between monitor non-wear time and sustained inactivity (default = TRUE)
overwrite	Overwrite previously generated milestone data by this function for this particular dataset? If FALSE then it will skip the previously processed files (default = FALSE).
desiredtz	See <a href="#">g.getmeta</a>
constrain2range	Whether or not to constrain the range of threshold used in the diary free Sleep period time window detection
do.part3.pdf	Whether to generate a pdf for part 3 (default is TRUE). Turning this off could speed up the processing.
do.parallel	Boolean whether to use multi-core processing (only works if at least 4 CPU cores are available).
dayborder	See <a href="#">g.part1</a>
myfun	External function object to be applied to raw data. See details <a href="#">applyExtFunction</a> .

**Value**

The function provides no values, it only ensures that other functions are called and that their output is stored in .RData files.

- night nightnumber

- definition definition of sustained inactivity. For example, T10A5 refers to 10 minute window and a 5 degree angle (see paper for further explanation).
- start.time.day timestamp when the day started
- nsib.periods number of sustained inactivity bouts
- tot.sib.dur.hrs total duration of all sustained inactivity bouts
- fraction.night.invalid fraction of the night for which accelerometer data was invalid, e.g. monitor not worn
- sib.period number of sustained inactivity period
- sib.onset.time onset time of sustained inactivity period
- sib.end.time end time of sustained inactivity period

### Author(s)

Vincent T van Hees <v.vanhees@accelting.com>

### References

- van Hees VT, Sabia S, et al. (2015) A novel, open access method to assess sleep duration using a wrist-worn accelerometer, PLoS ONE, November 2015
- van Hees VT, Sabia S, et al. (2018) Estimating sleep parameters using an accelerometer without sleep diary. Scientific Reports.

### Examples

```
## Not run:
metadatadir = "C:/myfolder/meta" # assumes that there is a subfolder in
# metadatadir named 'basic' containing the output from g.part1
g.part3(metadatadir=metadatadir, anglethreshold=5,
timethreshold=5, overwrite=FALSE)

## End(Not run)
```

---

g.part4

*Labels detected sustained inactivity periods by g.part3 as either part of the Sleep Period Time window or not*

---

### Description

Combines output from g.part3 and guider information to estimate sleep variables. See vignette paragraph "Sleep and full day time-use analysis in GGIR" for an elaborate description of the sleep detection.

**Usage**

```
g.part4(datadir=c(),metadatadir=c(),f0=f0,f1=f1,idloc=1,
loglocation = c(),colid = 1,coln1 = 9,nnights = 7,
sleeplogidnum=FALSE,do.visual=FALSE,outliers.only = FALSE,
  excludefirstlast=FALSE,criterror = 1,includenightcrit=16,
  relyonguider=FALSE, relyonsleeplog=FALSE, def.noc.sleep=1,
  storefolderstructure=FALSE,overwrite=FALSE,
  desiredtz="",data_cleaning_file=c(),
  excludefirst.part4=FALSE,excludelast.part4=FALSE)
```

**Arguments**

datadir	Directory where the accelerometer files are stored or list of accelerometer file-names and directories
metadatadir	Directory that holds a folders 'meta' and inside this a folder 'basic' which contains the milestone data produced by g.part1. The folderstructure is normally created by g.part3. When using g.part4 via g.shell.GGIR then g.shell.GGIR will automatically recognise what the value of metadatadir is, so the user does not need to specify this.
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)
idloc	If value = 1 (default) the code assumes that ID number is stored in the obvious header field. If value = 2 the code uses the character string preceding the character '_' in the filename as the ID number
loglocation	Location of the spreadsheet (csv) with sleep log information. The spreadsheet needs to have the following structure: one column for participant ID, and then followed by alternatingly one column for onset time and one column for waking time. There can be multiple sleeplogs in the same spreadsheet. The first row of the spreadsheet needs to be filled with column names, it does not matter what these column names are. Timestamps are to be stored without date as in hh:mm:ss. If onset corresponds to lights out or intention to fall asleep, then it is the end-users responsibility to account for this in the interpretation of the results.
colid	Column number in the sleep log spreadsheet in which the participant ID code is stored (default = 1)
coln1	Column number in the sleep log spreadsheet where the onset of the first night starts
nnights	Number of nights for which sleep log information should be available. It assumes that this is constant within a study. If sleep log information is missing for certain nights then leave these blank
sleeplogidnum	Should the participant identifier as stored in the sleeplog be interpreted as a number (TRUE=default) or a character (FALSE)?
do.visual	If g.part4 is run with do.visual == TRUE then the function will generate a pdf with a visual representation of the overlap between the sleeplog entries and the accelerometer detections. This can be used to visually verify that the sleeplog entries do not come with obvious mistakes.

outliers.only	Relevant for <code>do.visual == TRUE</code> . <code>Outliers.only == FALSE</code> will visualise all available nights in the data. <code>Outliers.only == TRUE</code> will visualise only for nights with a difference in onset or waking time larger than the variable of argument <code>criterror</code> .
excludefirstlast	If <code>TRUE</code> then the first and last night of the measurement are ignored for the sleep assessment.
criterror	Relevant for <code>do.visual == TRUE</code> and <code>outliers.only == TRUE</code> . <code>criterror</code> specifies the number of minimum number of hours difference between sleep log and accelerometer estimate for the night to be included in the visualisation
includenightcrit	Minimum number of valid hours per night (24 hour window between noon and noon)
relyonguider	If <code>TRUE</code> then sleep onset and waking time are defined based on timestamps derived from the guider. If participants were instructed NOT to wear the accelerometer during waking hours then set to <code>TRUE</code> , in all other scenarios set to <code>FALSE</code> (default).
relyonsleeplog	Now replaced by <code>relyonguider</code> . Values provided to argument <code>relyonsleeplog</code> will be passed on to argument <code>relyonguider</code> to not preserve functionality of old R script.
def.noc.sleep	The time window during which sustained inactivity will be assumed to represent sleep, e.g. <code>def.noc.sleep=c(21,9)</code> . This is only used if no sleep log entry is available. If <code>def.noc.sleep</code> is left blank <code>'def.noc.sleep=c()'</code> then the 12 hour window centred at the least active 5 hours of the 24 hour period will be used instead. Here, <code>L5</code> is hardcoded and will not change by changing argument <code>winhr</code> in function <a href="#">g.part2</a> . If <code>def.noc.sleep</code> is filled with a single integer, e.g. <code>def.noc.sleep=c(1)</code> then the window will be detected with the method as described in van Hees et al. 2018 Scientific Reports.
storefolderstructure	Store folder structure of the accelerometer data
overwrite	Overwrite previously generated milestone data by this function for this particular dataset. If <code>FALSE</code> then it will skip the previously processed files (default = <code>FALSE</code> ).
desiredtz	See <a href="#">g.getmeta</a>
data_cleaning_file	Optional path to a csv file you create that holds four columns: <code>ID</code> , <code>day_part5</code> , <code>relyonguider_part4</code> , and <code>night_part4</code> . <code>ID</code> should hold the participant ID. Columns <code>day_part5</code> and <code>night_part4</code> allow you to specify which day(s) and night(s) need to be excluded from part 5 and 4, respectively. So, this will be done regardless of whether the rest of GGIR thinks those day(s)/night(s) are valid. Column <code>relyonguider_part4</code> allows you to specify for which nights part 4 should fully rely on the guider. See also package vignette.
excludefirst.part4	If <code>TRUE</code> then the first night of the measurement are ignored for the sleep assessment.

```
excludelast.part4
```

If TRUE then the last night of the measurement are ignored for the sleep assessment.

### Value

The function does not produce values but generates an RData file in the milestone subfolder ms4.out which includes a dataframe named `nightsummary`. This dataframe is used in `g.report.part4` to create two reports one per night and one per person. See package vignette paragraph "Output part 4" for description of all the variables.

### Author(s)

Vincent T van Hees <v.vanhees@accelting.com>

### References

- van Hees VT, Sabia S, et al. (2018) AEstimating sleep parameters using an accelerometer without sleep diary, Scientific Reports.
- van Hees VT, Sabia S, et al. (2015) A novel, open access method to assess sleep duration using a wrist-worn accelerometer, PLoS ONE.

### Examples

```
## Not run:
metadatadir = "C:/myfolder/meta" # assumes that there is a subfolder in
# metadatadir named 'ms3.out' containing the output from g.part3
g.part4(metatadir=metadatadir)

## End(Not run)
```

---

g.part5

*Merge output from physical activity and sleep analysis into one report*

---

### Description

Function to merge the output from `g.part2` and `g.part4` into one report enhanced with profiling of sleep and physical activity stratified across intensity levels and based on bouted periods as well as non-bouted periods.

### Usage

```
g.part5(datadir=c(), metadatadir=c(), f0=c(), f1=c(), strategy=1,
maxdur=7, hrs.del.start=0, hrs.del.end =0,
loglocation= c(), excludelast.part5=FALSE,
windowsizes=c(5,900,3600),acc.metric="ENMO", boutcriter.mvpa=0.8,
boutcriter.in=0.9, boutcriter.lig=0.8, storefolderstructure=FALSE,
threshold.lig = c(40), threshold.mod = c(100),
```

```

threshold.vig = c(400), timewindow=c("MM","WW"),
boutdur.mvpa = c(1,5,10), boutdur.in = c(10,20,30),
boutdur.lig = c(1,5,10), winhr = 5, M5L5res = 10,
overwrite=FALSE, desiredtz="",
bout.metric=4, dayborder=0, save_ms5rawlevels=FALSE, do.parallel=TRUE,
part5_agg2_60seconds = FALSE, save_ms5raw_format="csv",
save_ms5raw_without_invalid=TRUE,
data_cleaning_file=c(), includedaycrit.part5=2/3)

```

## Arguments

datadir	Directory where the accelerometer files are stored or list of accelerometer file-names and directories
metadatadir	Directory that holds a folders 'meta' and inside this a folder 'basic' which contains the milestone data produced by g.part1. The folderstructure is normally created by g.part1 and g.shell.GGIR will recognise what the value of metadatadir is.
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)
strategy	how to deal with knowledge about study protocol. value = 1 means select data based on hrs.del.start, hrs.del.end, and maxdur. Value = 2 makes that only the data between the first midnight and the last midnight is used for imputation, see <a href="#">g.impute</a>
maxdur	how many DAYS after start of experiment did experiment definitely stop? (set to zero if unknown = default), see <a href="#">g.impute</a>
hrs.del.start	how many HOURS after start of experiment did wearing of monitor start?, see <a href="#">g.impute</a>
hrs.del.end	how many HOURS before the end of the experiment did wearing of monitor definitely end?, see <a href="#">g.impute</a>
loglocation	Location of the spreadsheet (csv) with sleep log information. The spreadsheet needs to have the following structure: one column for participant id, and then followed by alternatingly one column for onset time and one column for waking time. Timestamps are to be stored without date as in 18:20:00. If onset corresponds to lights out or intention to fall asleep, then it is the end-users responsibility to account for this in the interpretation of the results.
excludefirstlast.part5	If TRUE then the first and last night of the measurement are ignored for the sleep assessment.
window sizes	see <a href="#">g.getmeta</a>
acc.metric	Which one of the metrics do you want to consider to describe behaviour. The metric of interest need to be calculated in M (see <a href="#">g.part1</a> )
boutcriter.mvpa	A number between 0 and 1 and defines what fraction of a bout needs to be above the mvpathreshold



boutcriter.in	A number between 0 and 1 and defines what fraction of a bout needs to be below the light threshold
boutcriter.lig	A number between 0 and 1 and defines what fraction of a bout needs to be between the light and moderate threshold
storefolderstructure	Store folder structure of the accelerometer data
threshold.lig	Threshold for light physical activity to separate inactivity from light. Value can be one number or an array of multiple numbers, e.g. threshold.lig =c(30,40). If multiple numbers are entered then analysis will be replicated for each combination of threshold values. Threshold is applied to the first metric in the milestone data, so if you have only specified do.ENMO == TRUE then it will be applied to ENMO.
threshold.mod	Threshold for moderate physical activity to separate light from moderate. Value can be one number or an array of multiple numbers, e.g. threshold.mod =c(100,110). If multiple numbers are entered then analysis will be replicated for each combination of threshold values. Threshold is applied to the first metric in the milestone data, so if you have only specified do.ENMO == TRUE then it will be applied to ENMO.
threshold.vig	Threshold for vigorous physical activity to separate moderate from vigorous. Value can be one number or an array of multiple numbers, e.g. threshold.mod =c(400,500). If multiple numbers are entered then analysis will be replicated for each combination of threshold values. Threshold is applied to the first metric in the milestone data, so if you have only specified do.ENMO == TRUE then it will be applied to ENMO.
timewindow	Timewindow over which summary statistics are derived. Value can be "MM" (midnight to midnight), "WW" (waking time to waking time), or both c("MM","WW").
boutdur.mvpa	Durations of mvpa bouts in minutes to be extracted. The default values is c(1,5,10) and will start with the identification of 10 minute bouts, followed by 5 minute bouts in the rest of the data, and followed by 1 minute bouts in the rest of the data.
boutdur.in	Durations of inactivity bouts in minutes to be extracted. Inactivity bouts are detected in the segments of the data which were not labelled as sleep or MVPA bouts. The default duration values is c(10,20,30), this will start with the identification of 30 minute bouts, followed by 20 minute bouts in the rest of the data, and followed by 10 minute bouts in the rest of the data.
boutdur.lig	Durations of light activity bouts in minutes to be extracted. Light activity bouts are detected in the segments of the data which were not labelled as sleep, MVPA, or inactivity bouts. The default duration values is c(1,5,10), this will start with the identification of 10 minute bouts, followed by 5 minute bouts in the rest of the data, and followed by 1 minute bouts in the rest of the data.
M5L5res	resolution of L5 and M5 analysis in minutes (default: 10 minutes)
overwrite	Overwrite previously generated milestone data by this function for this particular dataset. If FALSE then it will skip the previously processed files (default = FALSE).
desiredtz	see <a href="#">g.getmeta</a>

bout.metric	See documnetion in <a href="#">g.getbout</a> and
dayborder	Hour at which days start and end (default = 0), value = 4 would mean 4am
winhr	see <a href="#">g.getmeta</a>
save_ms5rawlevels	boolean, whether to save the time series classification (levels) as a csv files
do.parallel	Boolean whether to use multi-core processing (only works if at least 4 CPU cores are available).
part5_agg2_60seconds	Boolean whether to use aggregate epochs to 60 seconds as part of the part 5 analysis.
save_ms5raw_format	Character string to specify how data should be stored: either "csv" (default) or "RData". Only used if save_ms5rawlevels is set to TRUE.
save_ms5raw_without_invalid	Boolean to indicate whether to remove invalid days from the time series output files. Only used if save_ms5rawlevels is set to TRUE.
data_cleaning_file	See <a href="#">g.part4</a> . Note that in part 5 this affects both the time series and the csv reports.
includedaycrit.part5	See <a href="#">g.report.part5</a> . Only used in this function if save_ms5rawlevels is TRUE, and it only affects the time series files stored.

## Value

The function does not produce values but generates an RData file in the milestone subfolder ms5.out which includes a dataframe named output. This dataframe is used in [g.report.part5](#) to create two reports one per day and one per person. See package vignette paragraph "Output part 5" for description of all the variables.

## Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

## Examples

```
## Not run:
metadatadir = "C:/myfolder/meta"
g.part5(metadatadir=metadatadir)

## End(Not run)
```

---

*g.part5.addfirstwake* Adds first wake if it is missing in part 4 output.

---

### **Description**

Not intended for direct use by GGIR users. Adds first wake if it is missing in part 4 output as part of [g.part5](#).

### **Usage**

```
g.part5.addfirstwake(ts, summarysleep_tmp2, nightsi, sleeplog,  
ID, Nepochsinhour, Nts, sptwindow_HDCZA_end, ws3new)
```

### **Arguments**

ts  
summarysleep\_tmp2  
  
nightsi  
sleeplog  
ID  
Nepochsinhour  
Nts  
sptwindow\_HDCZA\_end  
  
ws3new

### **Value**

Data.frame ts

### **Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.part5.addsib      *Adds the sustained inactivity bout to the ts series.*

---

**Description**

Not intended for direct use by GGIR users. Adds the sustained inactivity bout to the ts series as part of [g.part5](#).

**Usage**

```
g.part5.addsib(ts,ws3, Nts, S2, desiredtz, j, nightsi)
```

**Arguments**

ts  
ws3  
Nts  
S2  
desiredtz  
j  
nightsi

**Value**

Data.frame ts

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.part5.definedays      *Fix missing night in part 4 output*

---

**Description**

Not intended for direct use by GGIR users. Defines when day windows start and end as part of [g.part5](#).

**Usage**

```
g.part5.definedays(nightsi, wi, summariesleep_tmp2, indjump, nightsi_bu,  
ws3new, qq_backup=c(), ts, Nts, timewindowi, Nwindows)
```

**Arguments**

nightsi  
wi  
summarysleep\_tmp2

indjump  
nightsi\_bu  
ws3new  
qqq\_backup  
ts  
Nts  
timewindowi  
Nwindows

**Value**

List of qqq and qqq\_backup

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

*g.part5.fixmissingnight*  
*Fix missing night in part 4 output*

---

**Description**

Not intended for direct use by GGIR users. If a night is missing in the part4 output then this function tries to fix as part of [g.part5](#).

**Usage**

```
g.part5.fixmissingnight(summarysleep_tmp2, sleeplog=c(), ID)
```

**Arguments**

summarysleep\_tmp2  
Object produced by [g.part4](#)  
sleeplog  
ID

**Value**

Corrected summarysleep\_tmp2 object.

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.part5.onsetwaketiming

*Identify wake and sleeperperiod window timing*

---

**Description**

Not intended for direct use by GGIR users. Labels timing of wakeing up and sleep onset as part of [g.part5](#).

**Usage**

```
g.part5.onsetwaketiming(qqq, ts, min, sec, hour, timewindowi, skiponset, skipwake)
```

**Arguments**

qqq

ts

min

sec

hour

timewindowi

skiponset

skipwake

**Value**

A list with objects: wake, onset, wakei, onsets, skiponset, and skipwake.

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

`g.part5.savetimeseries`*Saves oart 5 time series to csv files*

---

**Description**

Not intended for direct use by GGIR users. Saves oart 5 time series to csv files as part of [g.part5](#).

**Usage**

```
g.part5.savetimeseries(ts, LEVELS, desiredtz, rawlevels_fname,  
save_ms5raw_format="csv",  
save_ms5raw_without_invalid=TRUE,  
DaCleanFile=c(), includedaycrit.part5=2/3, ID=c())
```

**Arguments**`ts``LEVELS``desiredtz` See [g.getmeta](#).`rawlevels_fname``save_ms5raw_format`See [g.part5](#)`save_ms5raw_without_invalid`See [g.part5](#)`DaCleanFile` Content of `data_cleaning_file` as documented in [g.report.part5](#). Only used in this function if `save_ms5rawlevels` is TRUE, and it only affects the time series files stored.`includedaycrit.part5`See [g.report.part5](#). Only used in this function if `save_ms5rawlevels` is TRUE, and it only affects the time series files stored.`ID`If `data_cleaning_file` is used then this argument specifies which participant ID the data correspond with.**Value**

Function does not provide output, it only prepare data for saving and saves it to a file.

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

g.part5.wakesleepwindows

*Label wake and sleeperperiod window*

---

### **Description**

Not intended for direct use by GGIR users. Label wake and sleeperperiod window as part of [g.part5](#).

### **Usage**

```
g.part5.wakesleepwindows(ts, summarysleep_tmp2, desiredtz,  
  nightsi, sleeplog, ws3new, Nts, ID, Nepochsinhour)
```

### **Arguments**

ts	data.frame with time series
summarysleep_tmp2	cleaned output from part 4
desiredtz	
nightsi	
sleeplog	
ws3new	
Nts	
ID	
Nepochsinhour	

### **Value**

Object ts

### **Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>



---

`g.plot` *function to generate a plot for quality check purposes*

---

### Description

Function takes meta-data as generated by [g.getmeta](#) and [g.impute](#) to create a visual representation of imputed time periods

### Usage

```
g.plot(IMP, M, I, durplot)
```

### Arguments

IMP	output from <a href="#">g.impute</a>
M	output from <a href="#">g.getmeta</a>
I	output from <a href="#">g.inspectfile</a>
durplot	number of days to plot

### Value

function only produces a plot, no values

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

### Examples

```
## Not run:
#inspect file:
I = g.inspectfile(datafile)

#autocalibration:
C = g.calibrate(datafile)

#get meta-data:
M = g.getmeta(datafile)

## End(Not run)
data(data.getmeta)
data(data.inspectfile)

#impute meta-data:
IMP = g.impute(M = data.getmeta, I = data.inspectfile, strategy = 1,
hrs.del.start = 0, hrs.del.end = 0, maxdur = 0)

#plot data
g.plot(IMP, M = data.getmeta, I = data.inspectfile, durplot=4)
```

---

`g.plot5` *Generate user-friendly visual report. The first part of the report summarizes important daily metrics in bar plot format. The second part of the report shows the raw data and annotations in 24-hr periods. Angle-z is shown with sleep annotations during the SPT (sleep period time) window. ENMO is shown with daytime inactivity and PA (physical activity) annotations in the lower section of each 24-hr plot. The PA annotations are based on a 10 minute bout metric and 80 of a 10 minute bout of MVPA. Vigorous PA is a short window of time above `threshold.vig` that is part of a bout of MVPA. Light PA is a short window of time above `threshold.lig` that is part of a bout of light PA.*

---

### Description

Function called by [g.shell.GGIR](#) to generate report. Not intended for direct use by user

### Usage

```
g.plot5(metadataadir = c(), dofirstpage = FALSE, viewingwindow = 1,
f0 = c(), f1 = c(), overwrite = FALSE, metric="ENMO",desiredtz = "Europe/London",
threshold.lig = 30, threshold.mod = 100, threshold.vig = 400)
```

### Arguments

<code>metadataadir</code>	See <a href="#">g.part2</a>
<code>dofirstpage</code>	Boolean to indicate whether a first page with histograms summarizing the whole measurement should be added
<code>viewingwindow</code>	See <a href="#">g.shell.GGIR</a>
<code>f0</code>	See <a href="#">g.shell.GGIR</a>
<code>f1</code>	See <a href="#">g.shell.GGIR</a>
<code>overwrite</code>	See <a href="#">g.shell.GGIR</a>
<code>metric</code>	Which one of the metrics do you want to consider to describe behaviour. The metric of interest need to be calculated in M (see <a href="#">g.part1</a> )
<code>desiredtz</code>	See <a href="#">g.getmeta</a>
<code>threshold.lig</code>	See <a href="#">g.part5</a>
<code>threshold.mod</code>	See <a href="#">g.part5</a>
<code>threshold.vig</code>	See <a href="#">g.part5</a>

### Value

No values, this function only generates a plot

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)> Matthew R Patterson <[mpatterson@shimmersensing.com](mailto:mpatterson@shimmersensing.com)>

**Examples**

```
## Not run:
# generate plots for the first 10 files:
g.plot5(metadataadir="C:/output_mystudy/meta/basic",dofirstpage=TRUE,
viewingwindow = 1,f0=1,f1=10,overwrite=FALSE,desiredtz = "Europe/London",
threshold.lig,threshold.mod,threshold.vig)

## End(Not run)
```

g.readaccfile

*Generic function to read large blocks of accelerometer data***Description**

The function is used by [g.getmeta](#) and [g.calibrate](#) to read large blocks of the accelerometer file, which are processed and then deleted. This is needed for memory management.

**Usage**

```
g.readaccfile(filename,blocksize,blocknumber,
selectdaysfile=c()),filequality, decn,dayborder,ws,desiredtz="",
PreviousEndPage=1,inspectfileobject=c(),configtz=c(), ...)
```

**Arguments**

filename	filename
blocksize	Size of blocks (in file pages) to be read
blocknumber	Block number relative to start of file
selectdaysfile	See documentation <a href="#">g.getmeta</a>
filequality	Single row dataframe with columns: filetooshort, filecorrupt, and filedoesnothold-day. All with the value TRUE or FALSE
decn	Character with a dot or a comma, used for interpreting samplefrequency in the file header. decn is derived with <a href="#">g.dotorcomma</a>
dayborder	See documentation <a href="#">g.part1</a>
ws	Larger window size for non-detection, see documentation <a href="#">g.part2</a>
desiredtz	Desired timezone, see documentation <a href="#">g.getmeta</a>
PreviousEndPage	Page number on which previous block ended (automatically assigned within <a href="#">g.getmeta</a> and <a href="#">g.calibrate</a> ).
inspectfileobject	Output from the function <a href="#">g.inspectfile</a> .
configtz	Only functional for AX3 cwa data at the moment. Timezone in which the accelerometer was configured. Only use this argument if the timezone of configuration and timezone in which recording took place are different.
...	Any input arguments needed for function <a href="#">read.myacc.csv</a> if you are working with a non-standard csv formatted files.

**Value**

P=P,filequality=filequality, switchoffLD = switchoffLD

- P Block object extracted from file with format specific to accelerometer brand
- filequality Same as in function arguments
- switchoffLD Boolean to indicate whether it is worth continuing to read the next block of data or not
- endpage Page number on which blocked ends, this will be used as input for argument PreviousEndPage when reading the next block.

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
## Not run:
filequality = data.frame(filetooshort=FALSE, filecorrupt=FALSE,
filedoesnotholdday = FALSE)
output = g.readaccfile(filename="C:/myfile.bin",
locksize=20000, blocknumber=1,
selectdaysfile=c(), filequality=filequality,
                                decn=".", dayborder=0,PreviousEndPage=c())

## End(Not run)
```

---

`g.readtemp_movisens`    *Reads the temperature from movisens files.*

---

**Description**

Reads the temperature from movisens files, resamples it and adds it to the matrix where accelerations are stored

**Usage**

```
g.readtemp_movisens(datafile, desiredtz = "", from = c(), to = c())
```

**Arguments**

<code>datafile</code>	Full path to the folder where the movisens bin files are stored. Note that movisens store a set of bin file in one folder per recording. GGIR will read the pertinent bin file to access to the temperature data.
<code>desiredtz</code>	see <a href="#">g.getmeta</a>
<code>from</code>	Origin point to derive the temperature from movisens files (automatically calculated by GGIR)
<code>to</code>	End point to derive the temperature from movisens files (automatically calculated by GGIR)

**Value**

Data matrix with the temperature values resampled at 64 Hz.

**Examples**

```
## Not run:  
P = g.readtemp_movisens(datafile, desiredtz = "", from = c(), to = c())  
  
## End(Not run)
```

---

g.report.part2	<i>Generate report from milestone data produced by <a href="#">g.part2</a></i>
----------------	--

---

**Description**

Creates report from milestone data produced by [g.part2](#). Not intended for direct use by package user

**Usage**

```
g.report.part2(metadataadir=c(), f0=c(), f1=c(), maxdur = 7,  
selectdaysfile=c())
```

**Arguments**

metadataadir	see <a href="#">g.part2</a>
f0	see <a href="#">g.part2</a>
f1	see <a href="#">g.part2</a>
maxdur	see <a href="#">g.part2</a>
selectdaysfile	see <a href="#">g.part2</a>

**Value**

Function does not produce data, but only writes reports in csv format and visual reports in pdf format

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.report.part4      *Generate report from milestone data produced by [g.part4](#)*

---

### Description

Creates report from milestone data produced by [g.part4](#). Not intended for direct use by package user

### Usage

```
g.report.part4(datadir=c(),metadatadir=c(),loglocation = c(),f0=c(),
  f1=c(),storefolderstructure=TRUE, data_cleaning_file=c())
```

### Arguments

datadir	see <a href="#">g.part4</a>
metadatadir	see <a href="#">g.part4</a>
loglocation	see <a href="#">g.part4</a>
f0	see <a href="#">g.part4</a>
f1	see <a href="#">g.part4</a>
storefolderstructure	see <a href="#">g.part4</a>
data_cleaning_file	see <a href="#">g.part4</a>

### Value

Function does not produce data, but only writes reports in csv format and a visual report in pdf.

The following files are stored in the root of the results folder: part4\_nightsummary\_sleep\_cleaned.csv  
part4\_summary\_sleep\_cleaned.csv

The following files are stored in the folder results/QC: part4\_nightsummary\_sleep\_full.csv part4\_summary\_sleep\_full.csv

If a sleeplog is used \*\_full.csv as stored in the QC folder includes estimates for all nights in the data, and \*\_cleaned.csv in the results folder includes estimates for all nights in the data excluding the nights that did not had a sleeplog entry or had no valid accelerometer data.

If a sleep log is not used then \*\_cleaned.csv includes the nights that are in \*\_full.csv excluding the nights with insufficient data.

If you have a study where the sleeplog was available for a subset of the participants, but you want to include all individuals in your analysis, then use the \*\_full.csv output and clean the night level data yourself by excluding rows with cleaningcode > 1 which are the cases where no or invalid accelerometer data was present.

The above means that for studies with missing sleeplog entries for some individuals and some nights using the \*\_full.csv output and excluding rows (nights) with cleaningcode > 1 will lead to the same

as \*\_cleaned.csv plus sleep estimates for the nights with missing sleeplog, providing that there was enough accelerometer data for those nights.

In other words, \*\_cleaned.csv is perfect if you only want to rely on nights with a sleeplog or if you do not use a sleeplog at all. For all other scenarios We advise using the \*\_full.csv report and to clean it yourself.

See package vignette sections "Sleep analysis" and "Output part 4" for a more elaborative description of the sleep analysis and reporting.

### Author(s)

Vincent T van Hees <v.vanhees@accelting.com>

---

g.report.part5

*Generate report from milestone data produced by [g.part5](#)*

---

### Description

Creates report from milestone data produced by [g.part5](#). Not intended for direct use by package user

### Usage

```
g.report.part5(metadataadir=c(),f0=c(),f1=c(),loglocation=c(),
               includenightcrit=c(),includedaycrit=c(),
               data_cleaning_file=c(),
               includedaycrit.part5=2/3,
               minimum_MM_length.part5=23)
```

### Arguments

metadataadir see [g.part5](#)

f0 see [g.part5](#)

f1 see [g.part5](#)

loglocation see [g.part4](#)

includenightcrit

Despricated as of version 2.0, not used anymore in part 5 report

includedaycrit Despricated as of version 2.0, not used anymore in part 5 report

data\_cleaning\_file

see [g.part4](#)

includedaycrit.part5

Inclusion criteria for number of valid hours, either as expressed as a ratio of 1 or as the number of hours in a 24 hour day.

minimum\_MM\_length.part5

Minimum length in hours of a MM day to be included in the cleaned part 5 results.

**Value**

Function does not produce data, but only writes reports in csv format

The following files are stored in the root of the results folder: part5\_dayssummary\_\* part5\_personsummary\_\*

The following files are stored in the folder results/QC: part5\_dayssummary\_full\_\*

See package vignette paragraph "Waking-waking or 24 hour time-use analysis" and "Output part 5" for a more elaborative description of the full day time-use and analysis and reporting.

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.shell.GGIR

*Shell function for analysing an accelerometer dataset.*

---

**Description**

This function is designed to help users operate all steps of the analysis. It helps to generate and structure milestone data, produces user-friendly reports. The function acts as a shell with calls to [g.part1](#), [g.part2](#), [g.part3](#) and [g.part4](#). Please see these specific functions for clarification on optional input arguments.

**Usage**

```
g.shell.GGIR(mode=1:5,datadir=c(),outputdir=c(),studyname=c(),
f0=1,f1=0, do.report=c(2),overwrite=FALSE,visualreport=FALSE,
viewingwindow=1,configfile=c(),myfun=c(),...)
```

**Arguments**

mode	Specify which of the four parts need to be run, e.g. mode = 1 makes that <a href="#">g.part1</a> is run. Default setting, mode = c(1,2), makes that both part1 and part2 are ran. Note that if mode = c(1,3) then the code will also set do.anglez = TRUE in order to enable sleep detection. If you run part 1 and 3 seperatedly then you need to remember to set argument do.anglez to TRUE when running part1.
datadir	Directory where the accelerometer files are stored or list, e.g. "C:/mydata" of accelerometer filenames and directories, e.g. c("C:/mydata/myfile1.bin", "C:/mydata/myfile2.bin").
outputdir	Directory where the output needs to be stored. Note that this function will attempt to create folders in this directory and uses those folder to keep output
studyname	If the datadir is a folder then the study will be given the name of the data directory. If datadir is a list of filenames then the studyname as specified by this input argument will be used as name for the study
f0	File index to start with (default = 1). Index refers to the filenames sorted in increasing order
f1	File index to finish with (defaults to number of files available)



overwrite	Do you want to overwrite analysis for which milestone data exists? If overwrite=FALSE then milestone data from a previous analysis will be used if available and visual reports will not be created again.
do.report	For which parts to generate a summary spreadsheet: 2 and/or 4. Default is c(2). A report will be generated based on the available milestone data. When creating milestone data with multiple machines it is advisable to turn the report generation off when generating the milestone data, value = c(), and then to merge the milestone data and turn report generation back on while setting overwrite to FALSE.
visualreport	If TRUE then generate visual report based on combined output from part 2 and 4. This is in beta-version at the moment.
viewingwindow	Centre the day as displayed around noon (value = 1) or around midnight (value = 2)
configfile	Configuration file previously generated by g.shell.GGIR. See details.
myfun	External function object to be applied to raw data, see <a href="#">g.getmeta</a> .
...	Any input arguments needed for functions g.part1, g.part2, g.part3 or g.part4. See respective function documentation for further clarification.

## Details

Once you have used g.shell.GGIR and the output directory (outputdir) will be filled with milestone data and results. Function g.shell.GGIR stores all the explicitly entered argument values and default values for the argument that are not explicitly provided in a csv-file named config.csv stored in the root of the output folder. The config.csv file is accepted as input to g.shell.GGIR with argument 'configfile' to replace the specification of all the arguments, except 'datadir' and 'outputdir'.

The practical value of this is that it eases the replication of analysis, because instead of having to share you R script, sharing your config.csv file will be sufficient. Further, the config.csv file contribute to the reproducibility of your data analysis.

Note: When combining a configuration file with explicitly provided argument values, the explicitly provided argument values will overrule the argument values in the configuration file.

## Value

The function provides no values, it only ensures that other functions are called and that their output is stored. Further, a configuration file is stored containing all the argument values used to facilitate reproducibility.

## Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

## References

- van Hees VT, Gorzelniak L, Dean Leon EC, Eder M, Pias M, et al. (2013) Separating Movement and Gravity Components in an Acceleration Signal and Implications for the Assessment of Human Daily Physical Activity. PLoS ONE 8(4): e61691. doi:10.1371/journal.pone.0061691

- van Hees VT, Fang Z, Langford J, Assah F, Mohammad A, da Silva IC, Trenell MI, White T, Wareham NJ, Brage S. Auto-calibration of accelerometer data for free-living physical activity assessment using local gravity and temperature: an evaluation on four continents. *J Appl Physiol* (1985). 2014 Aug 7
- van Hees VT, Sabia S, et al. (2015) A novel, open access method to assess sleep duration using a wrist-worn accelerometer, *PLoS ONE*, November 2015

## Examples

```
## Not run:
mode= c(1,2,3,4)
datadir= "C:/myfolder/mydata"
outputdir= "C:/myresults"
studyname="test"
f0 = 1
f1 = 2
g.shell.GGIR(#-----
             # General parameters
             #-----
             mode=mode,
             datadir=datadir,
             outputdir=outputdir,
             studyname=studyname,
             f0=f0,
             f1=f1,
             overwrite = FALSE,
             do.imp=TRUE,
             idloc=1,
             print.filename=FALSE,
             storefolderstructure = FALSE,
             #-----
             # Part 1 parameters:
             #-----
             window sizes = c(5,900,3600),
             do.cal=TRUE,
             do.enmo = TRUE,
             do.anglez=TRUE,
             chunksize=1,
             printsummary=TRUE,
             #-----
             # Part 2 parameters:
             #-----
             strategy = 1,
             ndayswindow=7,
             hrs.del.start = 1,
             hrs.del.end = 1,
             maxdur = 9,
             includedaycrit = 16,
             L5M5window = c(0,24),
             M5L5res = 10,
             winhr = c(5,10),
             qllevels = c(c(1380/1440),c(1410/1440)),
```

```

qwindow=c(0,24),
ilevels = c(seq(0,400,by=50),8000),
mvpthreshold =c(100,120),
#-----
# Part 3 parameters:
#-----
timethreshold= c(5,10),
anglethreshold=5,
ignorenonwear = TRUE,
#-----
# Part 4 parameters:
#-----
excludefirstlast = FALSE,
includenightcrit = 16,
def.noc.sleep = 1,
loglocation= "D:/sleeplog.csv",
outliers.only = FALSE,
criterror = 4,
relyonsleeplog = FALSE,
sleeplogidnum = TRUE,
colid=1,
coln1=2,
do.visual = TRUE,
nnights = 9,
#-----
# Part 5 parameters:
#-----
# Key functions: Merging physical activity with sleep analyses
threshold.lig = c(30,40,50),
threshold.mod = c(100,120),
threshold.vig = c(400,500),
excludefirstlast = FALSE,
boutcriter = 0.8,
boutcriter.in = 0.9,
boutcriter.lig = 0.8,
boutcriter.mvpa = 0.8,
boutdur.in = c(10,20,30),
boutdur.lig = c(1,5,10),
boutdur.mvpa = c(1,5,10),
timewindow = c("WW"),
#-----
# Report generation
#-----
do.report=c(2,4,5))

## End(Not run)

```

**Description**

Detects sustained inactivity bouts. Function not intended for direct use by package user

**Usage**

```
g.sib.det(M, IMP, I, twd=c(-12,12), anglethreshold = 5,  
          timethreshold = c(5,10), acc.metric = "ENMO",  
          desiredtz="", constrain2range=TRUE, dayborder=0,  
          myfun=c())
```

**Arguments**

M	Object produced by <a href="#">g.getmeta</a>
IMP	Object produced by <a href="#">g.impute</a>
I	Object produced by <a href="#">g.inspectfile</a>
twd	Vector of length 2, indicating the time window to consider as hours relative to midnight.
anglethreshold	See <a href="#">g.part3</a>
timethreshold	See <a href="#">g.part3</a>
acc.metric	Which one of the metrics do you want to consider to analyze L5. The metric of interest need to be calculated in M (see <a href="#">g.part1</a> )
desiredtz	See <a href="#">g.part3</a>
constrain2range	See <a href="#">g.part3</a>
dayborder	See <a href="#">g.part1</a>
myfun	External function object to be applied to raw data. See details <a href="#">applyExtFunction</a> .

**Value**

- output = Dataframe for every epoch a classification
- detection.failed = Boolean whether detection failed
- L5list = L5 for every day (defined from noon to noon)

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.sib.plot	<i>Create plot of sustained inactivity bouts</i>
------------	--

---

**Description**

Function create plot of sustained inactivity bouts for quality check purposes as part of [g.part3](#). Not intended for direct use by package user

**Usage**

```
g.sib.plot(SLE, M, I, plottitle, nightsperpage=7, desiredtz="")
```

**Arguments**

SLE	Output from <a href="#">g.sib.det</a>
M	Output from <a href="#">g.getmeta</a>
I	Output from <a href="#">g.inspectfile</a>
plottitle	Title to be used in the plot
nightsperpage	Number of nights to show per page
desiredtz	See <a href="#">g.part3</a>

**Value**

Function has no output other than the plot

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

g.sib.sum	<i>sustained inactivity bouts detection</i>
-----------	---

---

**Description**

Detects sustained inactivity bouts. Function not intended for direct use by package user

**Usage**

```
g.sib.sum(SLE, M, ignorenonwear=TRUE, desiredtz="")
```

**Arguments**

SLE	Output from <a href="#">g.sib.det</a>
M	Object produced by <a href="#">g.getmeta</a>
ignorenonwear	See <a href="#">g.part3</a>
desiredtz	See <a href="#">g.part3</a>

**Value**

Dataframe with per night and per definition of sustained inactivity bouts the start and end time of each sustained inactivity bout

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.wavread	<i>function to read .wav files as produced by the accelerometer named 'Axivity'</i>
-----------	---

---

**Description**

For reading the wav accelerometer data as collected with an Axivity accelerometer

**Usage**

```
g.wavread(wavfile, start = 1, end = 100, units="minutes")
```

**Arguments**

wavfile	filename (required)
start	start point for reading data, see also units
end	end point for reading data, see also units
units	units used for defining start and end

**Details**

If only start is defined then g.binread will read all data beyond start until the end of the file is reached

**Value**

rawxyz	matrix with raw x, y, and, z acceleration values
header	file header
timestamps	local timestamps for rawxyz

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

---

g.weardec	<i>Detects whether accelerometer is worn</i>
-----------	--

---

**Description**

Uses the object produced by [g.part1](#) to assess whether the accelerometer was worn

**Usage**

```
g.weardec(M, wearthreshold, ws2)
```

**Arguments**

M	Object produced by <a href="#">g.getmeta</a>
wearthreshold	Number of axis that at least need to meet the non-wear criteria
ws2	Large window size used in seconds to apply non-wear detection Small window size not needed, because this is inherent to the object M

**Value**

- r1 Participant id extracted from file
- r2 Night number
- r3 Detected onset of sleep expressed as hours since the previous midnight
- LC fraction of 15 minute windows with more than 5 percent clipping
- LC2 fraction of 15 minute windows with more than 80 percent clipping

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

**Examples**

```
data(data.getmeta)
output = g.weardec(M=data.getmeta, wearthreshold=2, ws2=3600)
```

---

getFirstTimestamp      *Extract first timestamp from GENEActiv file*

---

**Description**

Extract first timestamp from GENEActiv file, only used when using the selectdaysfile argument. Function not designed for direct use by package user.

**Usage**

```
getFirstTimestamp(f, p1)
```

**Arguments**

f	GENEActiv filename
p1	First value of timestamps object

**Value**

POSIX object withstarttime

**Author(s)**

Joe Heywood <j.heywood@ucl.ac.uk>

---

getfolderstructure      *Extracts folderstructure based on data directory.*

---

**Description**

Extracts folderstructure based on data directory. This is used when accelerometer files are stored in a hierarchical folder structure and the user likes to have a reference to the exact position in the folder tree, rather than just the filename. Function not intended for direct use by package user.

**Usage**

```
getfolderstructure(datadir=c(), referencefnames=c())
```

**Arguments**

datadir	Argument datadir as used in various other functions in GGIR
referencefnames	vector with filename to filter on



**Value**

List with items: itemfullfilenamesvector with all full paths to the folders including the name of the file itself itemfoldernamevector with only the names of the folder in which each file is stroed (so only the most distal folder in the folder tree)

**Examples**

```
## Not run:
folderstructure = getfolderstructure(datadir)

## End(Not run)
```

---

getStartEnd	<i>Generate start and end time of a day</i>
-------------	---

---

**Description**

Generate start and end time of a day when working with argument selectdaysfile in [g.part1](#). The user provides a date and a start hour which is used to generate the timestamps of the start hour minutes 5 minutes and the start hour plus 24 hours. Function not designed for direct use by package user.

**Usage**

```
getStartEnd(d, startHour, outputFormat = "%d/%m/%Y %H:%M:%S",
  tz = "Europe/London")
```

**Arguments**

d	character with date (without time) format
startHour	Hour that analysis starts at
outputFormat	Characterstring indicating outputFormat
tz	Same as desiredtz in <a href="#">g.part1</a>

**Value**

Data.frame with two columns: a start time five minutes before startHour on day d and an endtime 24 hours after startHour

**Author(s)**

Joe Heywood <j.heywood@ucl.ac.uk>

**Examples**

```
startandendtime = getStartEnd(d="20/5/2017", startHour=4)
```

---

getStartEndNumeric      *Generate start and end page of a day*

---

### Description

Generate start and end page of a day when working with argument selectdaysfile in [g.part1](#). The user provides a date and a start hour which is used to generate the pages of the start hour minutes 5 minutes and the start hour plus 24 hours. Function not designed for direct use by package user.

### Usage

```
getStartEndNumeric(d, hhr, startHour = 4)
```

### Arguments

d	Character with date (without time) format
hhr	GENEActiv::header.info(f) output
startHour	Hour that analysis starts at

### Value

Data.frame with two columns: a start page five minutes before startHour on day d and an end page 24 hours after startHour

### Author(s)

Joe Heywood <j.heywood@ucl.ac.uk>

### Examples

```
## Not run:
hhr = GENEActiv::header.info("C:/myfile.bin")
mystartandendpage = getStartEndNumeric(d="20/5/2017", hhr, startHour = 4)

## End(Not run)
```

---

get\_nw\_clip\_block\_params

*Set monitor brand specific parameters*

---

### Description

Set monitor brand specific thresholds for non-wear detection, clipping etection, and blocksizes to be loaded. Not designed for direct use by user.

**Usage**

```
get_nw_clip_block_params(chunksize, dynrange, monc, rmc.noise=c(),
sf, dformat, rmc.dynamic_range)
```

**Arguments**

chunksize	See <a href="#">g.calibrate</a>
dynrange	See <a href="#">g.getmeta</a>
monc	See <a href="#">g.inspectfile</a>
rmc.noise	Optional, please see <a href="#">read.myacc.csv</a>
sf	Numeric, sample frequency in Hertz
dformat	See <a href="#">g.dotorcomma</a>
rmc.dynamic_range	Optional, please see <a href="#">read.myacc.csv</a>

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

```
get_starttime_weekday_meantemp_truncdata
```

*Get starttime (adjusted), weekday, mean temp, and adjust data accordingly.*

---

**Description**

Function not intended for direct use by user. Used inside [g.getmeta](#) as an intermediate step between loading the raw data and calibrating it. This step includes extracting the starttime and adjusting it to nearest integer number of long epoch window lengths in an hour, truncating the data accordingly, extracting the corresponding weekday and mean temperature (if temperature is available).

**Usage**

```
get_starttime_weekday_meantemp_truncdata(temp.available, monc,
dformat, data, selectdaysfile, P, header, desiredtz, sf, i,
datafile, ws2, starttime, wday, weekdays, wdayname)
```

**Arguments**

temp.available	Boolean whether temperate is available.
monc	See <a href="#">g.inspectfile</a>
dformat	See <a href="#">g.dotorcomma</a>
data	Data part of <a href="#">g.readaccfile</a> output
selectdaysfile	See <a href="#">g.dotorcomma</a>

P	data loaded from accelerometer file with <a href="#">g.readaccfile</a>
header	Header part of <a href="#">g.readaccfile</a> output
desiredtz	See <a href="#">g.getmeta</a>
sf	Numeric, sample frequency in Hertz
i	Integer index of passed on from <a href="#">g.getmeta</a> to indicate what data block is being read.
datafile	See <a href="#">g.getmeta</a>
ws2	Long epoch length
starttime	Once calculate it is remembered and fed into this function again, such that it does not have to be recalculated.
wday	Once calculate it is remembered and fed into this function again, such that it does not have to be recalculated.
weekdays	Once calculate it is remembered and fed into this function again, such that it does not have to be recalculated.
wdayname	Once calculate it is remembered and fed into this function again, such that it does not have to be recalculated.

**Author(s)**

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

---

identify\_levels      *Identifies levels of behaviour for g.part5 function.*

---

**Description**

Identifies levels of behaviour from acceleration and sustained inactivity siddetection (using angles). Function not intended for direct use by package user.

**Usage**

```
identify_levels(ts, TRLi, TRMi, TRVi,
               boutdur.mvpa, boutcriter.mvpa,
               boutdur.lig, boutcriter.lig,
               boutdur.in, boutcriter.in,
               ws3, bout.metric)
```

**Arguments**

ts                    Data.frame with time series generated in .gpart5

TRLi

TRMi

TRVi

```

boutdur.mvpa
boutcriter.mvpa

boutdur.lig
boutcriter.lig
boutdur.in
boutcriter.in
ws3,bout.metric

```

**Value**

List with items: itemLEVELS itemOLEVELS itemLnames itembc.mvpa itembc.lig itembc.in itemts

**Examples**

```

## Not run:
levels = identify_levels(TRLi,TRMi,TRVi,
                        boutdur.mvpa,boutcriter.mvpa,
                        boutdur.lig,boutcriter.lig,
                        boutdur.in,boutcriter.in,
                        ws3,bout.metric)

## End(Not run)

```

---

is.ISO8601

---

*Check whether character timestamp is in iso8601 format.*


---

**Description**

Checks whether timestamp stored in character format is in ISO8601 format or not

**Usage**

```
is.ISO8601(x)
```

**Arguments**

x                   Timestamps in character format either in ISO8601 or as "yyyy-mm-dd hh:mm:ss".

**Examples**

```

x ="1980-1-1 18:00:00"
is.ISO8601(x)

```

---

isfilelist	<i>Checks whether datadir is a directory or a vector with filenames</i>
------------	---

---

**Description**

Checks whether argument datadir used in various other functions in GGIR is the name of a directory that includes data files or whether it is a vector with the full paths to one or more data files

**Usage**

```
isfilelist(datadir)
```

**Arguments**

datadir	Argument datadir as used in various other functions in GGIR
---------	---

**Value**

Boolean whether it is a list of files (TRUE) or not (FALSE)

**Examples**

```
## Not run:
isitafilelist = isfilelist(datadir)

## End(Not run)
```

---

ismovisens	<i>Checks whether the files to process are collected with movisens accelerometers.</i>
------------	--

---

**Description**

Checks whether the files in the datadir folder are files collected with movisens accelerometers. Note that movisens data are stored in one folder per recording that includes multiple bin-files (instead of one file per recording as usual in other accelerometer brands). Therefore, datadir indicates the directory where all the recording folders are stored, then, GGIR reads the pertinent bin files from every folder.

**Usage**

```
ismovisens(data)
```

**Arguments**

data	Full path to the recording folder (with the bin files inside) or the datadir (where all the recording folders are stored).
------	--

**Value**

Boolean whether it is a movisens file (TRUE) or not (FALSE)

**Examples**

```
## Not run:
is.mv = ismovisens(data)

## End(Not run)
```

---

iso8601chartime2POSIX *Convert iso8601 timestamps to POSIX timestamp*

---

**Description**

To avoid ambiguities when sharing and comparing timestamps. All timestamps are expressed in iso8601 format: [https://en.wikipedia.org/wiki/ISO\\_8601](https://en.wikipedia.org/wiki/ISO_8601) However, to generate plots in R we need to convert them back to POSIX

**Usage**

```
iso8601chartime2POSIX(x, tz)
```

**Arguments**

x	Vector of timestamps in iso8601 in character format
tz	Timezone of data collection, e.g. "Europe/London". See <a href="#">List_of_tz_database_time_zones</a> on Wikipedia for full list.

**Examples**

```
x = "2017-05-07T13:00:00+0200"
tz = "Europe/Amsterdam"
x_converted = iso8601chartime2POSIX(x, tz)
```

---

is\_this\_a\_dst\_night *Check whether the night starting on a calendar date has DST.*

---

**Description**

Tests whether the night that follows the input calendar date is a night with day saving time (DST) and on what hour the time moved.

**Usage**

```
is_this_a_dst_night(calendar_date=c(), tz="Europe/London")
```

**Arguments**

calendar\_date    Character in the format dd/mm/yyyy  
tz                Time zone in "Europe/London" format.

**Value**

dst\_night\_or\_not    If value=0 no DST, if value=1 time moved forward, if value=-1 time moved forward  
dsthour            Either the double hour or the hour that was skipped, this differs between countries

**Examples**

```
test4dst = is_this_a_dst_night("23/03/2014", tz="Europe/London")
```

---

numUnpack

*Simple function using Rcpp*

---

**Description**

Simple function using Rcpp

**Usage**

```
numUnpack(pack)
```

**Arguments**

pack              vector of integer

**Examples**

```
## Not run:  
  numUnpack()  
  
## End(Not run)
```



---

POSIXtime2iso8601      *Convert POSIX to iso8601 timestamp*

---

### Description

To avoid ambiguities when sharing and comparing timestamps. All timestamps are expressed in iso8601 format: [https://en.wikipedia.org/wiki/ISO\\_8601](https://en.wikipedia.org/wiki/ISO_8601)

### Usage

```
POSIXtime2iso8601(x, tz)
```

### Arguments

x	Vector of timestamps in POSIX format
tz	Timezone of data collection, e.g. "Europe/London". See <a href="https://en.wikipedia.org/wiki/List_of_tz_databases">https://en.wikipedia.org/wiki/List_of_tz_databases</a> for full list

### Author(s)

Vincent T van Hees <[v.vanhees@accelting.com](mailto:v.vanhees@accelting.com)>

### Examples

```
## Not run:
x ="2017-05-07 13:15:17 CEST"
tz = "Europe/Amsterdam"
x_converted = POSIXtime2iso8601(x, tz)

## End(Not run)
```

---

read.myacc.csv      *Read custom csv files with accelerometer data*

---

### Description

Loads csv files with accelerometer data and standardises the output format (incl. unit of measurement, timestamp format, header format, and column locations) to make the data compatible with other GGIR functions.

**Usage**

```
read.myacc.csv(rmc.file=c(), rmc.nrow=c(), rmc.skip = c(), rmc.dec=".",
              rmc.firstrow.acc = 1, rmc.firstrow.header=c(),
              rmc.header.length = c(),
              rmc.col.acc = 1:3, rmc.col.temp = c(),
              rmc.col.time=c(),
              rmc.unit.acc = "g", rmc.unit.temp = "C",
              rmc.unit.time = "POSIX",
              rmc.format.time = "%Y-%m-%d %H:%M:%OS",
              rmc.bitrate = c(), rmc.dynamic_range = c(),
              rmc.unsignedbit = TRUE,
              rmc.origin = "1970-01-01",
              rmc.desiredtz = "Europe/London",
              rmc.sf = c(),
              rmc.headername.sf = c(),
              rmc.headername.sn = c(),
              rmc.headername.recordingid = c(),
              rmc.header.structure = c(),
              rmc.check4timegaps = FALSE,
              rmc.col.wear = c(),
              rmc.doresample=FALSE)
```

**Arguments**

<code>rmc.file</code>	Filename of file to be read.
<code>rmc.nrow</code>	Number of rows to read, same as <code>nrow</code> argument in <code>read.csv</code> and in <code>fread</code> .
<code>rmc.skip</code>	Number of rows to skip, same as <code>skip</code> argument in <code>read.csv</code> and in <code>fread</code> .
<code>rmc.dec</code>	Decimal used for numbers, same as <code>skip</code> argument in <code>read.csv</code> and in <code>fread</code> .
<code>rmc.firstrow.acc</code>	First row (number) of the acceleration data.
<code>rmc.firstrow.header</code>	First row (number) of the header. Leave blank if the file does not have a header.
<code>rmc.header.length</code>	If file has header, specify header length (numeric).
<code>rmc.col.acc</code>	Vector with three column (numbers) in which the acceleration signals are stored
<code>rmc.col.temp</code>	Scalar with column (number) in which the temperature is stored. Leave in default setting if no temperature is available. The temperature will be used by <code>g.calibrate</code> .
<code>rmc.col.time</code>	Scalar with column (number) in which the timestamps are stored. Leave in default setting if timestamps are not stored.
<code>rmc.unit.acc</code>	Character with unit of acceleration values: "g", "mg", or "bit"
<code>rmc.unit.temp</code>	Character with unit of temperature values: (K)elvin, (C)elsius, or (F)ahrenheit
<code>rmc.unit.time</code>	Character with unit of timestamps: "POSIX", "UNIXsec" (seconds since origin, see argument <code>origin</code> ), "character", or "ActivPAL" (exotic timestamp format only used in the ActivPAL activity monitor).

<code>rmc.format.time</code>	Format of timestamp, only used for <code>rmc.unit.time</code> : character and POSIX.
<code>rmc.bitrate</code>	Numeric: If unit of acceleration is a bit then provide bit rate, e.g. 12 bit.
<code>rmc.dynamic_range</code>	Numeric, if unit of acceleration is a bit then provide dynamic range deviation in g from zero, e.g. +/-6g would mean this argument needs to be 6. If you give this argument a character value the code will search the file header for elements with a name equal to the character value and use the corresponding numeric value next to it as dynamic range.
<code>rmc.unsignedbit</code>	Boolean, if <code>unsignedbit = TRUE</code> means that bits are only positive numbers. if <code>unsignedbit = FALSE</code> then bits are both positive and negative.
<code>rmc.origin</code>	Origin of time when unit of time is UNIXsec, e.g. 1970-1-1
<code>rmc.desiredtz</code>	Timezone in which device was configured and experiments took place. If experiments took place in a different timezone, then use this argument for the timezone in which the experiments took place and argument <code>configtz</code> to specify where the device was configured (not implemented yet).
<code>rmc.sf</code>	Sample rate in Hertz, if this is stored in the file header then the that will be used instead.
<code>rmc.headername.sf</code>	If file has a header: Row name (character) under which the sample frequency can be found.
<code>rmc.headername.sn</code>	If file has a header: Row name (character) under which the serial number can be found.
<code>rmc.headername.recordingid</code>	If file has a header: Row name (character) under which the recording ID can be found.
<code>rmc.header.structure</code>	Character used to split the header name from the header value, e.g. ":" or " "
<code>rmc.check4timegaps</code>	Boolean to indicate whether gaps in time should be imputed with zeros. Some sensing equipment provides accelerometer with gaps in time. The rest of GGIR is not designed for this, by setting this argument to TRUE the the gaps in time will be filled with zeros.
<code>rmc.col.wear</code>	If external wear detection outcome is stored as part of the data then this can be used by GGIR. This argument specifies the column in which the wear detection (Boolean) is stored.
<code>rmc.doresample</code>	Boolean to indicate whether to resample the data based on the available timestamps and extracted sample rate from the file header

### Value

List with objects data holding the time series of acceleration, and header if it was available in the original file.

**Author(s)**

Vincent T van Hees <v.vanhees@accelting.com>

**Examples**

```
# create test files: No header, with temperature, with time
N = 30
sf = 30
timestamps = as.POSIXlt(Sys.time()+((0:(N-1))/sf),origin="1970-1-1",tz = "Europe/London")
mydata = data.frame(x=rnorm(N), time=timestamps,y=rnorm(N),z=rnorm(N),temp=rnorm(N)+20)
testfile = "testcsv1.csv"
write.csv(mydata, file= testfile, row.names = FALSE)
loadedData = read.myacc.csv(rmc.file=testfile, rmc.nrow=20, rmc.dec=".",
                           rmc.firstrow.acc = 1, rmc.firstrow.header=c(),
                           rmc.col.acc = c(1,3,4), rmc.col.temp = 5, rmc.col.time=2,
                           rmc.unit.acc = "g", rmc.unit.temp = "C", rmc.origin = "1970-01-01")
if (file.exists(testfile)) file.remove(testfile)
```

---

resample

*Simple function using Rcpp*


---

**Description**

Simple function using Rcpp

**Usage**

```
resample(raw, rawTime, time, stop)
```

**Arguments**

raw	stop-by-3 matrix with raw values of x, y and z.
rawTime	vector with stop elements of raw time.
time	array with required time points.
stop	number of the last known point in raw and rawTime

**Examples**

```
## Not run:
resample()

## End(Not run)
```

---

updateBlocksize	<i>Update blocksize of data to be read depending on available memory.</i>
-----------------	---

---

**Description**

Function queries available memory to either lower or increase the blocksize used by function [g.readaccfile](#)

**Usage**

```
updateBlocksize(blocksize, bsc_qc)
```

**Arguments**

blocksize	Number of filepages (binary data) or rows (other dataformats).
bsc_qc	Data.frame with columns time (timestamp from Sys.time) and size (memory size). This is used for housekeeping in <a href="#">g.calibrate</a> and <a href="#">g.getmeta</a>

**Value**

List with blocksize and bsc\_qc, same format as input, although bsc\_qc has one new row.

# Index

- \* **datasets**
  - data.calibrate, 9
  - data.getmeta, 10
  - data.inspectfile, 10
- applyExtFunction, 5, 7, 36, 46, 51, 76
- chartime2iso8601, 6
- check\_myfun, 7
- create\_test\_acc\_csv, 8
- create\_test\_sleeplog\_csv, 9
- createConfigFile, 7
- data.calibrate, 9
- data.getmeta, 10
- data.inspectfile, 10
- datadir2fnames, 11
- g.abr.day.names, 12
- g.analyse, 12, 15–20, 27, 30, 32, 38, 47–49
- g.analyse.avday, 20
- g.analyse.avday (g.analyse.avy), 15
- g.analyse.avy, 15
- g.analyse.perday, 17, 19, 20
- g.analyse.perfile, 19
- g.applymetrics, 21
- g.binread, 4, 22
- g.calibrate, 4, 9, 13, 20, 23, 43, 45, 67, 83, 93
- g.create.sp.mat, 25
- g.createcoordinates, 25
- g.cwaread, 4, 26
- g.deteomidnight, 16–18, 27
- g.dotorcomma, 28, 32, 37, 67, 83
- g.downsample, 29
- g.extractheadervars, 18, 19, 29
- g.getbout, 14, 30, 49, 58
- g.getidfromheaderobject, 31
- g.getM5L5, 14, 16, 18, 32, 50
- g.getmeta, 6, 7, 10, 12–14, 16, 18, 20, 24, 26, 28, 33, 37–39, 43–45, 48–51, 54, 56–58, 63, 65–68, 73, 76, 77, 79, 83, 84, 93
- g.getstarttime, 37
- g.impute, 12, 13, 16, 17, 19, 20, 37, 47–49, 56, 65, 76
- g.inspectfile, 10, 13, 19, 30, 32, 37, 38, 39, 65, 67, 76, 77, 83
- g.intensitygradient, 40
- g.IVIS, 14, 16, 20, 40, 49, 50
- g.loadlog, 41
- g.metric, 21, 42
- g.part1, 5, 11, 24, 35–37, 43, 43, 47, 48, 50, 51, 56, 66, 67, 72, 76, 79, 81, 82
- g.part2, 27, 43, 47, 54, 66, 67, 69, 72
- g.part3, 50, 72, 76, 77
- g.part4, 42, 52, 58, 61, 70–72
- g.part5, 55, 59–64, 66, 71
- g.part5.addfirstwake, 59
- g.part5.addsib, 60
- g.part5.definedays, 60
- g.part5.fixmissingnight, 61
- g.part5.onsetwaketiming, 62
- g.part5.savetimeseries, 63
- g.part5.wakesleepwindows, 64
- g.plot, 25, 65
- g.plot5, 12, 66
- g.readaccfile, 28, 37, 67, 83, 84, 93
- g.readtemp\_movisens, 68
- g.report.part2, 69
- g.report.part4, 70
- g.report.part5, 58, 63, 71
- g.shell.GGIR, 5, 7, 43, 47, 66, 72
- g.sib.det, 75, 77
- g.sib.plot, 77
- g.sib.sum, 77
- g.wavread, 26, 78
- g.weardec, 16, 18, 79
- get\_nw\_clip\_block\_params, 82
- get\_starttime\_weekday\_meantemp\_truncdata,

83  
getFirstTimestamp, 80  
getfolderstructure, 80  
getStartEnd, 81  
getStartEndNumeric, 82  
GGIR (GGIR-package), 4  
GGIR-package, 4  
  
identify\_levels, 84  
is.ISO8601, 85  
is\_this\_a\_dst\_night, 87  
isfilelist, 11, 86  
ismovisens, 86  
iso8601chartime2POSIX, 87  
  
numUnpack, 88  
  
POSIXtime2iso8601, 89  
  
read.myacc.csv, 28, 39, 46, 67, 83, 89  
resample, 92  
  
updateBlocksize, 93