

Package ‘amanida’

October 12, 2022

Title Meta-Analysis for Non-Integral Data

Version 0.2.3

Description Combination of results for meta-analysis using significance and effect size only. P-values and fold-change are combined to obtain a global significance on each metabolite. Produces a volcano plot summarising the relevant results from meta-analysis. Vote-counting reports for metabolites. And explore plot to detect discrepancies between studies at a first glance. Methodology is described in the Llambrich et al. (2021) <[doi:10.1093/bioinformatics/btab591](https://doi.org/10.1093/bioinformatics/btab591)>.

License GPL-3

URL <https://github.com/mariallr/amanida>

Depends R (>= 4.0)

Imports dplyr (>= 1.0.0), ggplot2 (>= 3.3.0), ggrepel (>= 0.9.0), kableExtra (>= 1.3.0), knitr (>= 1.33), magrittr (>= 1.5), methods (>= 3.6.0), readr (>= 1.0.0), readxl (>= 1.0.0), rmarkdown (>= 2.9.0), stats (>= 3.6.0), tibble (>= 3.0.0), tidyverse (>= 1.1.0), tidyverse (>= 1.3.0), webchem (>= 1.1.0)

Suggests markdown, metaboliteIDmapping, testthat, vdiff

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

NeedsCompilation no

Author Maria Llambrich [aut, cre] (<<https://orcid.org/0000-0001-8418-0982>>),
Eudald Correig [aut],
Raquel Cumeras [aut]

Maintainer Maria Llambrich <maria.llambrich@urv.cat>

Repository CRAN

Date/Publication 2022-03-30 06:50:05 UTC

R topics documented:

amanida	2
amanida_palette	3
amanida_read	3
amanida_report	4
amanida_vote	5
compute_amanida	6
explore_plot	7
getsampleDB	8
METATables-class	8
sample_data	8
volcano_plot	9
vote_plot	10
Index	11

amanida

amanida

Description

amanida: A package for Meta-Analysis with non-integral data

Author(s)

Maria Llambrich, Eudald Correig and Raquel Cumeras

Results combination for meta-analysis using only significance and effect size.

- P-values and fold-change are combined to obtain a global significance on each metabolite.
- Produces a volcano plot summarizing the relevant results from meta-analysis.
- Qualitative meta-analysis for metabolites
- Graphical representation of qualitative analysis by bar plot
- Trend explore plot to detect discrepancies between studies at a first glance

amanida_palette	<i>Get nice colour-blind colours</i>
-----------------	--------------------------------------

Description

Get nice colour-blind colours

Usage

```
amanida_palette()
```

Value

vector of colours

amanida_read	<i>Import data</i>
--------------	--------------------

Description

amanida_read imports the data and formats for compute_amanida or amanida_vote functions

Usage

```
amanida_read(file, mode, coln, separator = NULL)
```

Arguments

file	path to file
mode	indicate if data will be quantitative or qualitative. Options are: <ul style="list-style-type: none">• "quan" for quantitative meta-analysis using p-value and fold-change• "qual" for qualitative meta-analysis using trend label
coln	columns names to use. It has to be in order identification, p-values, fold-changes, sample size and reference.
separator	the separator used on file

Details

Note that amanida_read skips rows with missing values or NA. Negatives values for fold-change are transformed to positive (1/value).

Formats compatible are csv, xlsx, xls or txt.

Value

tibble table with data imported

Examples

```
coln <- c("Compound Name", "P-value", "Fold-change", "N total", "References")
input_file <- getsampleDB()
datafile <- amanida_read(input_file, mode = "quan", coln, separator=";")
```

amanida_report	<i>Report</i>
----------------	---------------

Description

amanida_report creates a report from the data using amanida functions

Usage

```
amanida_report(
  input_file,
  separator = NULL,
  analysis_type = NULL,
  column_id,
  pvalue_cutoff = NULL,
  fc_cutoff = NULL,
  votecount_lim,
  path = NULL,
  comp_inf = NULL
)
```

Arguments

input_file	path to the original dataset in xlsx, xls, csv or txt format
separator	indicate the separator used in the input_file parameter
analysis_type	indicate if data will be quantitative, qualitative or both. Options are: <ul style="list-style-type: none"> • "quan-qual" for quantitative and qualitative meta-analysis • "quan" for quantitative meta-analysis using p-value and fold-change • "qual" for qualitative meta-analysis using trend label
column_id	vector containing columns names to use. It has to be in order identification, p-values, fold-changes, sample size and reference.
pvalue_cutoff	numeric value to consider statistical significance
fc_cutoff	numeric value to consider significance for effect size
votecount_lim	minimum numeric value for vote-counting visualization
path	path to the directory where html file is created, otherwise the file will be saved in a temporal folder
comp_inf	complete information of compounds from public databases

Details

This function uses directly the dataset to create a report with the meta-analysis results. In case of quantitative analysis `amanida_report` uses the functions `amanida_read` and `compute_amanida` for analyse the input data. Then the results are showed using `volcano_plot`, `explore_plot` and `vote_plot`.

Value

an html document saved in the working directory

Examples

```
## Not run:
column_id = c("Compound Name", "P-value", "Fold-change", "N total", "References")
input_file <- getsampleDB()

amanida_report(input_file, separator = ";", column_id, analysis_type = "quan",
               pvalue_cutoff = 0.05, fc_cutoff = 4, votecount_lim = 2,
               comp_inf = F)

## End(Not run)
```

amanida_vote

Qualitative meta-analysis

Description

`amanida_vote` performs vote-counting on qualitative data.

Usage

```
amanida_vote(data, comp.inf = F)
```

Arguments

<code>data</code>	data imported using <code>amanida_read</code> function
<code>comp.inf</code>	include compounds IDs from PubChem, InChIKey, SMILES, KEGG, ChEBI, HMDB, Drugbank, Molecular Mass and Molecular Formula.

Details

Vote-counting is computed without trend division. Punctuation of entries is based on trend, up-regulation gives 1, down-regulation give -1 and equal behavior gives 0. Total sum is divided then by the total number of entries on each compound. Compound combination is made with PubChem CID when is available.

Note that `amanida_vote` skips rows with missing values or NA.

Formats compatible are csv, xlsx, xls or txt.

Value

METAtable S4 object with vote-counting for each compound on @slot vote

Examples

```
## Not run:
coln = c("Compound Name", "Behaviour", "References")
input_file <- system.file("extdata", "dataset2.csv", package = "amanida")
data_votes <- amanida_read(input_file, mode = "qual", coln, separator = ";")

vote_result <- amanida_vote(data_votes)

## End(Not run)
```

compute_amanida	<i>Combine statistical results and compute vote-counting</i>
-----------------	--

Description

compute_amanida Combines for the same entry or metabolite the statistical values of p-value and fold-change. Also is computed a vote-counting for each compound. Compound combination is made with PubChem CID when is available.

Usage

```
compute_amanida(datafile, comp.inf = F)
```

Arguments

datafile	data imported using amanida_read function
comp.inf	include compounds IDs from PubChem, InChIKey, SMILES, KEGG, ChEBI, HMDB, Drugbank, Molecular Mass and Molecular Formula

Details

Entries corresponding to metabolites are combined as follows:

- P-values are combined using Fisher method weighted by N and gamma distribution
- Fold-change are combined by weighted mean. Transformation works with fold-change transformed to log scale with base 2.

Vote-counting is computed based on votes. Punctuation of entries is based on trend, up-regulation gives 1, down-regulation give -1 and equal behavior gives 0. Total sum is divided then by the total number of entries on each compound.

Value

METAtable S4 object with p-value combined, fold-change combined and vote-counting for each compound

Examples

```
## Not run:  
data("sample_data")  
  
compute_amanida(sample_data)  
  
## End(Not run)
```

explore_plot

Plot for compounds divergence in reports

Description

explore_plot creates a bar-plot showing the votes divided in up-regulated and down-regulated and the global result for each compound.

Usage

```
explore_plot(data, type = "all", counts = NULL)
```

Arguments

data	an tibble obtained by amanida_read
type	select the subset of data to plot. Options are: <ul style="list-style-type: none">• "all": all data will be displayed• "sub": only data over counts value will be displayed. Need counts value.• "mix": will display data over count value and elements with reports in both trends. Need counts value.
counts	value of vote-counting cut-off. Will be only displayed data over the cut-off.

Details

Sum of votes divided by trend are plotted, then is obtained the total result by compound summing both trends.

Value

a ggplot bar-plot showing the sum of votes for each compound divided by the trend

Examples

```
data("sample_data")  
explore_plot(sample_data, type = "mix", counts = 1)
```

getsampleDB	<i>Function to sample data path</i>
-------------	-------------------------------------

Description

Function to sample data path

Usage

```
getsampleDB()
```

METatables-class	<i>An S4 class to return results from compute_amanida or amanida_vote function</i>
------------------	--

Description

An S4 class to return results from compute_amanida or amanida_vote function

Slots

stat results for statistics combining p-values and fold-changes
vote vote-counting for metabolites

sample_data	<i>Example input data for the amanida function</i>
-------------	--

Description

A dataset containing results from meta-analysis of metabolomic studies

Usage

```
sample_data
```


Format

A data frame with 143 rows and 6 variables:

id Name of the compound under study

pvalue P-value

foldchange Fold-change

N Number of samples of the compound

ref References

trend Trend: 1 (up), -1 (down) or 0 (none)

volcano_plot

Volcano plot of combined results

Description

volcano_plot returns a volcano plot of the combined results on each metabolite obtained by compute_amanida function

Usage

```
volcano_plot(mets, cutoff = NULL)
```

Arguments

mets an S4 METAtables object

cutoff values for p-value and fold-change significance

Details

Results are presented as $-\log_{10}$ for p-value and \log_2 for fold-change. Values over the cut off are labeled. If not cutoff is provided will be used alpha 0.05 for p-value and 1.5 for logarithmic fold-change.

Value

plot of results

Examples

```
## Not run:  
data("sample_data")  
  
amanida_result <- compute_amanida(sample_data)  
volcano_plot(amanida_result)  
  
## End(Not run)
```

`vote_plot`*Bar-plot for compounds vote-counting*

Description

`vote_plot` creates a bar-plot showing the vote-count for each compound.

Usage

```
vote_plot(mets, counts = NULL)
```

Arguments

`mets` an S4 METAtables object obtained by `compute_amanida` or `amanida_vote`.
`counts` value of vote-counting cut-off. Will be only displayed data over the cut-off.

Details

Vote-counting is the sum of number of reports up-regulated and the subtraction of reports down-regulated.

Value

a ggplot bar-plot showing the vote-count per compound

Examples

```
## Not run:  
data("sample_data")  
result <- compute_amanida(sample_data)  
vote_plot(result)  
  
## End(Not run)
```

Index

* datasets

sample_data, 8

amanida, 2

amanida_palette, 3

amanida_read, 3

amanida_report, 4

amanida_vote, 5

compute_amanida, 6

explore_plot, 7

getsampleDB, 8

METAtables (METAtables-class), 8

METAtables-class, 8

sample_data, 8

volcano_plot, 9

vote_plot, 10