

# Package ‘html5’

January 13, 2021

**Type** Package

**Title** Generates HTML Tag Strings for HTML5 Elements Included in Mozilla's Documentation of HTML5

**Version** 0.1.0

**Author** Timothy Conwell

**Maintainer** Timothy Conwell <timconwell@gmail.com>

**Description** Generates HTML tag strings for HTML5 elements included in Mozilla's documentation of HTML5.

Attributes are passed as parameters. If the attribute name is a reserved R word, the attribute is suffixed with `_attr` (ex: `for_attr`).

To declare a DOCTYPE, wrap `html` with function `html_doc()`.

Mozilla's documentation for HTML5 is available here: <<https://developer.mozilla.org/en-US/docs/Web/HTML/Element>>.

Elements marked as obsolete are not included.

**License** GPL (>= 2)

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2021-01-13 15:50:02 UTC

## R topics documented:

a	4
abbr	7
address	9
area	11
article	14
aside	16
audio	18
b	21

base	23
bdi	25
bdo	27
blockquote	30
body	32
br	35
button	37
canvas	40
caption	42
cite	45
code	47
col	49
colgroup	51
data	53
datalist	56
dd	58
del	60
details	62
dfn	65
dialog	67
div	69
dl	71
dt	73
em	76
embed	78
fieldset	80
figcaption	83
figure	85
footer	87
form	89
h1	92
h2	94
h3	96
h4	98
h5	100
h6	103
head	105
header	107
hgroup	109
hr	111
html	113
html_doc	116
i	116
iframe	118
img	121
input	124
ins	128
kbd	131

label . . . . .	133
legend . . . . .	135
li . . . . .	137
link . . . . .	139
main . . . . .	143
map . . . . .	145
mark . . . . .	147
menu . . . . .	149
meta . . . . .	151
meter . . . . .	154
nav . . . . .	156
noscript . . . . .	159
object . . . . .	161
ol . . . . .	164
optgroup . . . . .	166
option . . . . .	168
output . . . . .	171
p . . . . .	173
param . . . . .	175
picture . . . . .	177
pre . . . . .	179
progress . . . . .	182
q . . . . .	184
rb . . . . .	186
rp . . . . .	188
rt . . . . .	190
rtc . . . . .	193
ruby . . . . .	195
s . . . . .	197
samp . . . . .	199
script . . . . .	201
section . . . . .	204
select . . . . .	206
slot . . . . .	209
small . . . . .	211
source . . . . .	213
span . . . . .	216
strong . . . . .	218
style . . . . .	220
sub . . . . .	222
summary . . . . .	225
sup . . . . .	227
table . . . . .	229
tbody . . . . .	231
td . . . . .	233
template . . . . .	236
textarea . . . . .	238
tfoot . . . . .	241

th . . . . .	243
thead . . . . .	246
time . . . . .	248
title . . . . .	250
tr . . . . .	252
track . . . . .	254
u . . . . .	257
ul . . . . .	259
var . . . . .	261
video . . . . .	263
wbr . . . . .	267

<b>Index</b>	<b>270</b>
--------------	------------

---

a	<i>Generate HTML tag for element a</i>
---	--

---

### Description

Generate HTML tag for element a

### Usage

```
a(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    download = NULL,
    draggable = NULL,
    hidden = NULL,
    href = NULL,
    hreflang = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    ping = NULL,
    referrerpolicy = NULL,
    rel = NULL,
```

```

    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    target = NULL,
    title = NULL,
    type = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
download	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
href	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hreflang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>ping</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>referrerpolicy</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>rel</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>target</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>type</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
a(class = "test", "Example")
```

---

abbr

*Generate HTML tag for element abbr*

---

## Description

Generate HTML tag for element abbr

## Usage

```
abbr(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

## Arguments

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| class          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
abbr(class = "test", "Example")
```

---

address	<i>Generate HTML tag for element address</i>
---------	--

---

**Description**

Generate HTML tag for element address

**Usage**

```
address(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
address(class = "test", "Example")
```

---

area

*Generate HTML tag for element area*

---

**Description**

Generate HTML tag for element area

**Usage**

```
area(  
  accesskey = NULL,  
  alt = NULL,  
  autocalitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  coords = NULL,  
  dir = NULL,  
  download = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  href = NULL,  
  hreflang = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,
```

```

    itemtype = NULL,
    lang = NULL,
    part = NULL,
    ping = NULL,
    referrerpolicy = NULL,
    rel = NULL,
    shape = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    target = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>alt</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>coords</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>download</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>href</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hreflang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
ping	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
referrerpolicy	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
rel	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
shape	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
target	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
area(class = "test")
```

---

 article

*Generate HTML tag for element article*


---

**Description**

Generate HTML tag for element article

**Usage**

```
article(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
article(class = "test", "Example")
```

---

aside

*Generate HTML tag for element aside*

---

**Description**

Generate HTML tag for element aside

**Usage**

```
aside(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```



**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
aside(class = "test", "Example")
```

---

audio	<i>Generate HTML tag for element audio</i>
-------	--

---

**Description**

Generate HTML tag for element audio

**Usage**

```
audio(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  autoplay = NULL,
  class = NULL,
  contenteditable = NULL,
  controls = NULL,
  crossorigin = NULL,
  currentTime = NULL,
  dir = NULL,
  disableRemotePlayback = NULL,
  draggable = NULL,
  duration = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    loop = NULL,
    muted = NULL,
    part = NULL,
    preload = NULL,
    slot = NULL,
    spellcheck = NULL,
    src = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autoplay	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
controls	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
crossorigin	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
currentTime	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disableRemotePlayback	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

duration	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
loop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
muted	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
preload	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
audio(class = "test", "Example")
```

---

b	<i>Generate HTML tag for element b</i>
---	--

---

**Description**

Generate HTML tag for element b

**Usage**

```
b(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
b(class = "test", "Example")
```

---

base

*Generate HTML tag for element base*

---

**Description**

Generate HTML tag for element base

**Usage**

```
base(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  href = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    target = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>href</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
target	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
base(class = "test")
```

---

bdi

*Generate HTML tag for element bdi*

---

**Description**

Generate HTML tag for element bdi

**Usage**

```
bdi(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
```

```

id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
bdi(class = "test", "Example")
```

---

bdo

*Generate HTML tag for element bdo*

---

**Description**

Generate HTML tag for element bdo

**Usage**

```

bdo(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
bdo(class = "test", "Example")
```

---

`blockquote`*Generate HTML tag for element `blockquote`*

---

**Description**

Generate HTML tag for element `blockquote`

**Usage**

```
blockquote(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    cite = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                             |  |
|-----------------------------|--|
| <code>...</code>            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| <code>accesskey</code>      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>autocapitalize</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>cite</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
blockquote(class = "test", "Example")
```

---

body

*Generate HTML tag for element body*

---

**Description**

Generate HTML tag for element body

**Usage**

```
body(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  onafterprint = NULL,  
  onbeforeprint = NULL,  
  onbeforeunload = NULL,  
  onblur = NULL,  
  onerror = NULL,  
  onfocus = NULL,  
  onhashchange = NULL,  
  onlanguagechange = NULL,  
  onload = NULL,  
  onmessage = NULL,  
  onoffline = NULL,  
  ononline = NULL,  
  onpopstate = NULL,
```



```

onredo = NULL,
onresize = NULL,
onstorage = NULL,
onundo = NULL,
onunload = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onafterprint	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onbeforeprint	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onbeforeunload	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onblur	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onerror	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onfocus	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onhashchange	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onlanguagechange	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onload	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onmessage	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onoffline	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
ononline	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onpopstate	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onredo	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onresize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onstorage	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onundo	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
onunload	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
body(class = "test", "Example")
```

---

br

---

*Generate HTML tag for element br*


---

**Description**

Generate HTML tag for element br

**Usage**

```
br(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  clear = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
clear	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
br(class = "test")
```

---

button

*Generate HTML tag for element button*

---

**Description**

Generate HTML tag for element button

**Usage**

```
button(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  autofocus = NULL,
  class = NULL,
  contenteditable = NULL,
```

```

dir = NULL,
disabled = NULL,
draggable = NULL,
form = NULL,
formaction = NULL,
formenctype = NULL,
formmethod = NULL,
formnovalidate = NULL,
formtarget = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
name = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
type = NULL,
value = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autofocus	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formaction	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formenctype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formmethod	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formnovalidate	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formtarget	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
button(class = "test", "Example")
```

---

canvas

*Generate HTML tag for element canvas*

---

**Description**

Generate HTML tag for element canvas

**Usage**

```
canvas(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  height = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
```



```

    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    width = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
canvas(class = "test", "Example")
```

---

caption

*Generate HTML tag for element caption*

---

**Description**

Generate HTML tag for element caption

**Usage**

```
caption(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
caption(class = "test", "Example")
```

---

cite	<i>Generate HTML tag for element cite</i>
------	---

---

### Description

Generate HTML tag for element cite

### Usage

```
cite(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
cite(class = "test", "Example")
```

---

code

*Generate HTML tag for element code*

---

**Description**

Generate HTML tag for element code

**Usage**

```
code(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
code(class = "test", "Example")
```

---

col	<i>Generate HTML tag for element col</i>
-----	--

---

**Description**

Generate HTML tag for element col

**Usage**

```
col(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  span = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
span	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
col(class = "test")
```

---

colgroup

*Generate HTML tag for element colgroup*


---

**Description**

Generate HTML tag for element colgroup

**Usage**

```
colgroup(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
```

```

    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    span = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
span	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
colgroup(class = "test")
```

---

data	<i>Generate HTML tag for element data</i>
------	---

---

**Description**

Generate HTML tag for element data

**Usage**

```
data(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
```

```

draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
value = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
data(class = "test", "Example")
```

---

`datalist`*Generate HTML tag for element `datalist`*

---

**Description**

Generate HTML tag for element `datalist`

**Usage**

```
datalist(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                             |  |
|-----------------------------|--|
| <code>...</code>            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| <code>accesskey</code>      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>autocapitalize</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>class</code>          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |



contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
datalist(class = "test", "Example")
```

---

dd

*Generate HTML tag for element dd*

---

**Description**

Generate HTML tag for element dd

**Usage**

```
dd(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
dd(class = "test", "Example")
```

---

del	<i>Generate HTML tag for element del</i>
-----	--

---

**Description**

Generate HTML tag for element del

**Usage**

```
del(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  cite = NULL,
  class = NULL,
  contenteditable = NULL,
  datetime = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
cite	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
datetime	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
del(class = "test", "Example")
```

---

details

*Generate HTML tag for element details*

---

**Description**

Generate HTML tag for element details

**Usage**

```
details(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
```

```

draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
open = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>open</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
details(class = "test", "Example")
```



---

dfn	<i>Generate HTML tag for element dfn</i>
-----	--

---

### Description

Generate HTML tag for element dfn

### Usage

```
dfn(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
dfn(class = "test", "Example")
```

---

dialog

*Generate HTML tag for element dialog*

---

**Description**

Generate HTML tag for element dialog

**Usage**

```
dialog(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  open = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
open	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
dialog(class = "test", "Example")
```

---

div

*Generate HTML tag for element div*

---

**Description**

Generate HTML tag for element div

**Usage**

```
div(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
div(class = "test", "Example")
```

---

dl	<i>Generate HTML tag for element dl</i>
----	---

---

**Description**

Generate HTML tag for element dl

**Usage**

```
dl(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
```

```

    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
dl(class = "test", "Example")
```

---

 dt

*Generate HTML tag for element dt*

---

**Description**

Generate HTML tag for element dt

**Usage**

```

dt(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
dt(class = "test", "Example")
```

---

em

*Generate HTML tag for element em*

---

### Description

Generate HTML tag for element em

### Usage

```
em(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| class          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
em(class = "test", "Example")
```

---

embed

*Generate HTML tag for element embed*

---

**Description**

Generate HTML tag for element embed

**Usage**

```
embed(  
  accesskey = NULL,  
  autocalitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  height = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  src = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  type = NULL,  
  width = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
embed(class = "test")
```

---

fieldset

*Generate HTML tag for element fieldset*

---

**Description**

Generate HTML tag for element fieldset

**Usage**

```
fieldset(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  disabled = NULL,
  draggable = NULL,
  form = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
```



```

    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    name = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
fieldset(class = "test", "Example")
```

---

figcaption	<i>Generate HTML tag for element figcaption</i>
------------	---

---

### Description

Generate HTML tag for element figcaption

### Usage

```
figcaption(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
figcaption(class = "test", "Example")
```

---

figure

*Generate HTML tag for element figure*

---

**Description**

Generate HTML tag for element figure

**Usage**

```
figure(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
figure(class = "test", "Example")
```

---

footer	<i>Generate HTML tag for element footer</i>
--------	---

---

**Description**

Generate HTML tag for element footer

**Usage**

```
footer(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
footer(class = "test", "Example")
```

---

form

*Generate HTML tag for element form*

---

**Description**

Generate HTML tag for element form

**Usage**

```
form(
  ...,
  accept_charset = NULL,
  accesskey = NULL,
  action = NULL,
  autocapitalize = NULL,
  autocomplete = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  enctype = NULL,
  hidden = NULL,
  id = NULL,
```

```

inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
method = NULL,
name = NULL,
novalidate = NULL,
part = NULL,
rel = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
target = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accept_charset	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
action	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocomplete	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

enctype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
method	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
novalidate	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
rel	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
target	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
form(class = "test", "Example")
```

---

h1	<i>Generate HTML tag for element h1</i>
----	---

---

**Description**

Generate HTML tag for element h1

**Usage**

```
h1(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
h1(class = "test", "Example")
```

---

h2

*Generate HTML tag for element h2*

---

**Description**

Generate HTML tag for element h2

**Usage**

```
h2(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
h2(class = "test", "Example")
```

---

h3

*Generate HTML tag for element h3*

---

**Description**

Generate HTML tag for element h3

**Usage**

```
h3(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```



```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
h3(class = "test", "Example")
```

---

h4

*Generate HTML tag for element h4*

---

**Description**

Generate HTML tag for element h4

**Usage**

```
h4(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
```

```

draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
h4(class = "test", "Example")
```

---

h5

*Generate HTML tag for element h5*

---

**Description**

Generate HTML tag for element h5

**Usage**

```

h5(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
h5(class = "test", "Example")
```

---

h6

*Generate HTML tag for element h6*

---

### Description

Generate HTML tag for element h6

### Usage

```
h6(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
h6(class = "test", "Example")
```

---

head

*Generate HTML tag for element head*

---

**Description**

Generate HTML tag for element head

**Usage**

```
head(  
  ...,  
  accesskey = NULL,  
  autocalitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
head(class = "test", "Example")
```

---

header	<i>Generate HTML tag for element header</i>
--------	---

---

**Description**

Generate HTML tag for element header

**Usage**

```
header(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
header(class = "test", "Example")
```

---

hgroup	<i>Generate HTML tag for element hgroup</i>
--------	---

---

**Description**

Generate HTML tag for element hgroup

**Usage**

```
hgroup(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  ...  
)
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
hgroup(class = "test", "Example")
```

---

hr	<i>Generate HTML tag for element hr</i>
----	---

---

**Description**

Generate HTML tag for element hr

**Usage**

```
hr(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
```

```

hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
hr(class = "test")
```

---

html

*Generate HTML tag for element html*

---

**Description**

Generate HTML tag for element html

**Usage**

```

html(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  xmlns = NULL,
  custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
xmlns	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
html(class = "test", "Example")
```

---

html_doc	<i>Generate HTML string with properly declared DOCTYPE.</i>
----------	---

---

**Description**

Generate HTML string with properly declared DOCTYPE.

**Usage**

```
html_doc(..., doctype = "html")
```

**Arguments**

...	A string or strings of HTML element tags.
doctype	A string declaring the DOCTYPE for the HTML content.

**Value**

A HTML document string.

---

i	<i>Generate HTML tag for element i</i>
---	--

---

**Description**

Generate HTML tag for element i

**Usage**

```
i(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
```

```

    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
i(class = "test", "Example")
```

---

iframe	<i>Generate HTML tag for element iframe</i>
--------	---

---

**Description**

Generate HTML tag for element iframe

**Usage**

```
iframe(
  accesskey = NULL,
  allow = NULL,
  allowfullscreen = NULL,
  allowpaymentrequest = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  csp = NULL,
```

```
dir = NULL,  
draggable = NULL,  
height = NULL,  
hidden = NULL,  
id = NULL,  
inputmode = NULL,  
is = NULL,  
itemid = NULL,  
itemprop = NULL,  
itemref = NULL,  
itemscope = NULL,  
itemtype = NULL,  
lang = NULL,  
loading = NULL,  
name = NULL,  
part = NULL,  
referrerpolicy = NULL,  
sandbox = NULL,  
slot = NULL,  
spellcheck = NULL,  
src = NULL,  
srcdoc = NULL,  
style = NULL,  
tabindex = NULL,  
title = NULL,  
width = NULL,  
custom_attr = NULL  
)
```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
allow	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
allowfullscreen	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
allowpaymentrequest	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

csp	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
loading	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
referrerpolicy	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
sandbox	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
srcdoc	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
iframe(class = "test")
```

---

img	<i>Generate HTML tag for element img</i>
-----	--

---

**Description**

Generate HTML tag for element img

**Usage**

```
img(  
  accesskey = NULL,  
  alt = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  crossorigin = NULL,  
  decoding = NULL,  
  dir = NULL,  
  draggable = NULL,  
  height = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,
```

```

is = NULL,
ismap = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
loading = NULL,
part = NULL,
referrerpolicy = NULL,
sizes = NULL,
slot = NULL,
spellcheck = NULL,
src = NULL,
srcset = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
usemap = NULL,
width = NULL,
custom_attr = NULL
)

```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
alt	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
crossorigin	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
decoding	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
ismap	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
loading	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
referrerpolicy	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
sizes	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
srcset	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
usemap	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
img(class = "test")
```

---

input

*Generate HTML tag for element input*


---

**Description**

Generate HTML tag for element input

**Usage**

```
input(
  accept = NULL,
  accesskey = NULL,
  alt = NULL,
  autocapitalize = NULL,
  autocomplete = NULL,
  autofocus = NULL,
  capture = NULL,
  checked = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  dirname = NULL,
  disabled = NULL,
  draggable = NULL,
  form = NULL,
  formaction = NULL,
  formenctype = NULL,
  formmethod = NULL,
  formnovalidate = NULL,
```

```
formtarget = NULL,  
height = NULL,  
hidden = NULL,  
id = NULL,  
inputmode = NULL,  
is = NULL,  
itemid = NULL,  
itemprop = NULL,  
itemref = NULL,  
itemscope = NULL,  
itemtype = NULL,  
lang = NULL,  
list = NULL,  
max = NULL,  
maxlength = NULL,  
min = NULL,  
minlength = NULL,  
multiple = NULL,  
name = NULL,  
part = NULL,  
pattern = NULL,  
placeholder = NULL,  
readonly = NULL,  
required = NULL,  
size = NULL,  
slot = NULL,  
spellcheck = NULL,  
src = NULL,  
step = NULL,  
style = NULL,  
tabindex = NULL,  
title = NULL,  
type = NULL,  
value = NULL,  
width = NULL,  
custom_attr = NULL  
)
```

### Arguments

accept	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
alt	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

autocomplete	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autofocus	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
capture	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
checked	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dirname	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formaction	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formenctype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formmethod	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formnovalidate	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
formtarget	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
list	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
max	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
maxlength	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
min	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
minlength	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
multiple	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
pattern	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
placeholder	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
readonly	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
required	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
size	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
step	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
input(class = "test")
```

---

ins

---

*Generate HTML tag for element ins*


---

**Description**

Generate HTML tag for element ins

**Usage**

```
ins(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  cite = NULL,
  class = NULL,
  contenteditable = NULL,
  datetime = NULL,
  dir = NULL,
```



```

draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
cite	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
datetime	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
ins(class = "test", "Example")
```

---

`kbd`*Generate HTML tag for element kbd*

---

**Description**

Generate HTML tag for element kbd

**Usage**

```
kbd(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                             |  |
|-----------------------------|--|
| <code>...</code>            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| <code>accesskey</code>      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>autocapitalize</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>class</code>          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
kbd(class = "test", "Example")
```

---

label

*Generate HTML tag for element label*

---

**Description**

Generate HTML tag for element label

**Usage**

```
label(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  for_attr = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
for_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
label(class = "test", "Example")
```

---

legend

*Generate HTML tag for element legend*

---

**Description**

Generate HTML tag for element legend

**Usage**

```
legend(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
legend(class = "test", "Example")
```

---

li	<i>Generate HTML tag for element li</i>
----	---

---

**Description**

Generate HTML tag for element li

**Usage**

```
li(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
```

```

    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    value = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
li(class = "test", "Example")
```

---

link

*Generate HTML tag for element link*

---

**Description**

Generate HTML tag for element link

**Usage**

```
link(  
  accesskey = NULL,  
  as = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  crossorigin = NULL,  
  dir = NULL,  
  disabled = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  href = NULL,  
  hreflang = NULL,  
  id = NULL,  
  imagesizes = NULL,  
  imagesrcset = NULL,  
  inputmode = NULL,  
  integrity = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  media = NULL,  
  part = NULL,  
  prefetch = NULL,  
  referrerpolicy = NULL,  
  rel = NULL,  
  sizes = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  type = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

- |                        |   |
|------------------------|---|
| <code>accesskey</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible. |
| <code>as</code>        | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible. |

autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
crossorigin	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
href	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hreflang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
imagesizes	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
imagesrcset	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
integrity	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>media</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>prefetch</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>referrerpolicy</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>rel</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>sizes</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>type</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
link(class = "test")
```

---

main

*Generate HTML tag for element main*

---

### Description

Generate HTML tag for element main

### Usage

```
main(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| class          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
main(class = "test", "Example")
```

---

map

*Generate HTML tag for element map*

---

**Description**

Generate HTML tag for element map

**Usage**

```
map(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  name = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
map(class = "test", "Example")
```

---

mark

*Generate HTML tag for element mark*

---

**Description**

Generate HTML tag for element mark

**Usage**

```
mark(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
mark(class = "test", "Example")
```

---

menu

*Generate HTML tag for element menu*

---

**Description**

Generate HTML tag for element menu

**Usage**

```
menu(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
```

```

    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    type = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
menu(class = "test", "Example")
```

---

meta

*Generate HTML tag for element meta*

---

**Description**

Generate HTML tag for element meta

**Usage**

```
meta(  
  accesskey = NULL,  
  autocapitalize = NULL,  
  charset = NULL,  
  class = NULL,  
  content = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  http_equiv = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  name = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
charset	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
content	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>http_equiv</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>name</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
meta(class = "test")
```

---

meter

*Generate HTML tag for element meter*

---

**Description**

Generate HTML tag for element meter

**Usage**

```
meter(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  form = NULL,  
  hidden = NULL,  
  high = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  low = NULL,  
  max = NULL,  
  min = NULL,  
  optimum = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  value = NULL,
```

```

    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
high	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

low	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
max	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
min	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
optimum	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
meter(class = "test", "Example")
```

---

 nav

*Generate HTML tag for element nav*

---

**Description**

Generate HTML tag for element nav

**Usage**

```

nav(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
nav(class = "test", "Example")
```

---

`noscript`*Generate HTML tag for element noscript*

---

**Description**

Generate HTML tag for element noscript

**Usage**

```
noscript(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

<code>...</code>	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
noscript(class = "test", "Example")
```

---

object

*Generate HTML tag for element object*

---

**Description**

Generate HTML tag for element object

**Usage**

```
object(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  data = NULL,  
  dir = NULL,  
  draggable = NULL,  
  form = NULL,  
  height = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  name = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  type = NULL,  
  typemustmatch = NULL,  
  usemap = NULL,
```

```

    width = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
data	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
height	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
typemustmatch	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
usemap	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
width	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
object(class = "test", "Example")
```

---

ol *Generate HTML tag for element ol*

---

### Description

Generate HTML tag for element ol

### Usage

```
ol(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    reversed = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    start = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    type = NULL,  
    custom_attr = NULL  
)
```

### Arguments

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
reversed	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
start	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
ol(class = "test", "Example")
```

---

optgroup	<i>Generate HTML tag for element optgroup</i>
----------	---

---

**Description**

Generate HTML tag for element optgroup

**Usage**

```
optgroup(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  disabled = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  label = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
```

```

    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

label	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
optgroup(class = "test", "Example")
```

---

option	<i>Generate HTML tag for element option</i>
--------	---

---

**Description**

Generate HTML tag for element option

**Usage**

```
option(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  disabled = NULL,
  draggable = NULL,
```



```

hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
label = NULL,
lang = NULL,
part = NULL,
selected = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
value = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>label</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>selected</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>value</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
option(class = "test", "Example")
```

---

output	<i>Generate HTML tag for element output</i>
--------	---

---

**Description**

Generate HTML tag for element output

**Usage**

```
output(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    for_attr = NULL,  
    form = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    name = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>for_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>form</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>name</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
output(class = "test", "Example")
```

---

p

*Generate HTML tag for element p*

---

**Description**

Generate HTML tag for element p

**Usage**

```
p(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
```

```

    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
p(class = "test", "Example")
```

---

param	<i>Generate HTML tag for element param</i>
-------	--

---

**Description**

Generate HTML tag for element param

**Usage**

```
param(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
```

```

    lang = NULL,
    name = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    value = NULL,
    custom_attr = NULL
)

```

### Arguments

accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
param(class = "test")
```

---

picture

*Generate HTML tag for element picture*

---

**Description**

Generate HTML tag for element picture

**Usage**

```
picture(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
```

```

draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
picture(class = "test", "Example")
```

---

```
pre
```

*Generate HTML tag for element pre*

---

**Description**

Generate HTML tag for element pre

**Usage**

```

pre(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
pre(class = "test", "Example")
```

---

 progress
 

---



---

*Generate HTML tag for element progress*


---

**Description**

Generate HTML tag for element progress

**Usage**

```

progress(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  max = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  value = NULL,
  custom_attr = NULL
)

```

**Arguments**

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>max</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

value	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
progress(class = "test", "Example")
```

---

q	<i>Generate HTML tag for element q</i>
---	--

---

**Description**

Generate HTML tag for element q

**Usage**

```
q(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  cite = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)
```



**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
cite	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
q(class = "test", "Example")
```

---

 rb

*Generate HTML tag for element rb*

---

**Description**

Generate HTML tag for element rb

**Usage**

```
rb(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
rb(class = "test", "Example")
```

---

rp	<i>Generate HTML tag for element rp</i>
----	---

---

**Description**

Generate HTML tag for element rp

**Usage**

```
rp(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
```

```

    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
rp(class = "test", "Example")
```

---

 rt

*Generate HTML tag for element rt*

---

**Description**

Generate HTML tag for element rt

**Usage**

```

rt(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
rt(class = "test", "Example")
```



---

`rtc`*Generate HTML tag for element rtc*

---

**Description**

Generate HTML tag for element rtc

**Usage**

```
rtc(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                             |  |
|-----------------------------|--|
| <code>...</code>            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| <code>accesskey</code>      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>autocapitalize</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>class</code>          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
rtc(class = "test", "Example")
```

---

ruby

*Generate HTML tag for element ruby*

---

**Description**

Generate HTML tag for element ruby

**Usage**

```
ruby(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
ruby(class = "test", "Example")
```

---

s

*Generate HTML tag for element s*


---

**Description**

Generate HTML tag for element s

**Usage**

```
s(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
s(class = "test", "Example")
```

---

samp

*Generate HTML tag for element samp*

---

**Description**

Generate HTML tag for element samp

**Usage**

```
samp(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
samp(class = "test", "Example")
```

---

```
script
```

*Generate HTML tag for element script*

---

**Description**

Generate HTML tag for element script

**Usage**

```
script(
  ...,
  accesskey = NULL,
  async = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
```

```

crossorigin = NULL,
defer = NULL,
dir = NULL,
draggable = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
integrity = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
nomodule = NULL,
nonce = NULL,
part = NULL,
referrerpolicy = NULL,
slot = NULL,
spellcheck = NULL,
src = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
type = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
async	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
crossorigin	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

defer	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
integrity	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
nomodule	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
nonce	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
referrerpolicy	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
script(class = "test", "Example")
```

---

section

*Generate HTML tag for element section*

---

**Description**

Generate HTML tag for element section

**Usage**

```
section(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
section(class = "test", "Example")
```

---

```
select
```

*Generate HTML tag for element select*

---

**Description**

Generate HTML tag for element select

**Usage**

```
select(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  autocomplete = NULL,
  autofocus = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  disabled = NULL,
  draggable = NULL,
```

```

    form = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    multiple = NULL,
    name = NULL,
    part = NULL,
    required = NULL,
    size = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocomplete	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autofocus	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
multiple	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
required	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
size	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
select(class = "test", "Example")
```

---

slot

*Generate HTML tag for element slot*

---

**Description**

Generate HTML tag for element slot

**Usage**

```
slot(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  name = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
slot(class = "test", "Example")
```

---

small

*Generate HTML tag for element small*

---

**Description**

Generate HTML tag for element small

**Usage**

```
small(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
small(class = "test", "Example")
```

---

source

*Generate HTML tag for element source*

---

**Description**

Generate HTML tag for element source

**Usage**

```
source(
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
```

```

    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    media = NULL,
    part = NULL,
    sizes = NULL,
    slot = NULL,
    spellcheck = NULL,
    src = NULL,
    srcset = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    type = NULL,
    custom_attr = NULL
)

```

### Arguments

<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
media	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
sizes	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
srcset	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
source(class = "test")
```

---

span

*Generate HTML tag for element span*

---

### Description

Generate HTML tag for element span

### Usage

```
span(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
span(class = "test", "Example")
```

---

strong

*Generate HTML tag for element strong*

---

**Description**

Generate HTML tag for element strong

**Usage**

```
strong(  
  ...,  
  accesskey = NULL,  
  autocalitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
strong(class = "test", "Example")
```

---

style	<i>Generate HTML tag for element style</i>
-------	--

---

**Description**

Generate HTML tag for element style

**Usage**

```
style(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    media = NULL,
    nonce = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    type = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
media	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
nonce	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
type	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
style(class = "test", "Example")
```

---

sub

*Generate HTML tag for element sub*


---

**Description**

Generate HTML tag for element sub

**Usage**

```

sub(
    ...,
    accesskey = NULL,
    autocapitalize = NULL,
    class = NULL,
    contenteditable = NULL,
    dir = NULL,
    draggable = NULL,
    hidden = NULL,
    id = NULL,
    inputmode = NULL,
    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
sub(class = "test", "Example")
```



summary

*Generate HTML tag for element summary***Description**

Generate HTML tag for element summary

**Usage**

```
summary(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
summary(class = "test", "Example")
```

---

sup

*Generate HTML tag for element sup*

---

**Description**

Generate HTML tag for element sup

**Usage**

```
sup(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
sup(class = "test", "Example")
```

---

table	<i>Generate HTML tag for element table</i>
-------	--

---

**Description**

Generate HTML tag for element table

**Usage**

```
table(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
table(class = "test", "Example")
```

---

tbody

*Generate HTML tag for element tbody*


---

**Description**

Generate HTML tag for element tbody

**Usage**

```
tbody(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
tbody(class = "test", "Example")
```

---

td	<i>Generate HTML tag for element td</i>
----	---

---

**Description**

Generate HTML tag for element td

**Usage**

```
td(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  colspan = NULL,
  contenteditable = NULL,
```

```

dir = NULL,
draggable = NULL,
headers = NULL,
hidden = NULL,
id = NULL,
inputmode = NULL,
is = NULL,
itemid = NULL,
itemprop = NULL,
itemref = NULL,
itemscope = NULL,
itemtype = NULL,
lang = NULL,
part = NULL,
rowspan = NULL,
slot = NULL,
spellcheck = NULL,
style = NULL,
tabindex = NULL,
title = NULL,
custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
colspan	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
headers	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
rowspan	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
td(class = "test", "Example")
```

---

`template`*Generate HTML tag for element template*

---

**Description**

Generate HTML tag for element template

**Usage**

```
template(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

- |                             |  |
|-----------------------------|--|
| <code>...</code>            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| <code>accesskey</code>      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>autocapitalize</code> | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| <code>class</code>          | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |

contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
template(class = "test", "Example")
```

---

textarea

*Generate HTML tag for element textarea*

---

**Description**

Generate HTML tag for element textarea

**Usage**

```
textarea(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  autocomplete = NULL,  
  autofocus = NULL,  
  class = NULL,  
  cols = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  disabled = NULL,  
  draggable = NULL,  
  form = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  maxlength = NULL,  
  minlength = NULL,  
  name = NULL,  
  part = NULL,  
  placeholder = NULL,  
  readonly = NULL,  
  required = NULL,  
  rows = NULL,
```

```

    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    wrap = NULL,
    custom_attr = NULL
)

```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocomplete	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autofocus	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
cols	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
disabled	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
form	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
maxlength	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
minlength	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
name	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
placeholder	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
readonly	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
required	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
rows	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
wrap	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
textarea(class = "test", "Example")
```

---

tfoot

*Generate HTML tag for element tfoot*

---

**Description**

Generate HTML tag for element tfoot

**Usage**

```
tfoot(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
tfoot(class = "test", "Example")
```

---

th	<i>Generate HTML tag for element th</i>
----	---

---

**Description**

Generate HTML tag for element th

**Usage**

```
th(
  ...,
  abbr = NULL,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  colspan = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  headers = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
```

```

    lang = NULL,
    part = NULL,
    rowspan = NULL,
    scope = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
abbr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
colspan	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
headers	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
rowspan	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
scope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
th(class = "test", "Example")
```

---

thead	<i>Generate HTML tag for element thead</i>
-------	--

---

### Description

Generate HTML tag for element thead

### Usage

```
thead(  
    ...,  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
thead(class = "test", "Example")
```

---

time

*Generate HTML tag for element time*

---

**Description**

Generate HTML tag for element time

**Usage**

```
time(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  datetime = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```



**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
datetime	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
time(class = "test", "Example")
```

---

title	<i>Generate HTML tag for element title</i>
-------	--

---

**Description**

Generate HTML tag for element title

**Usage**

```
title(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
```

```

    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
title(class = "test", "Example")
```

---

tr	<i>Generate HTML tag for element tr</i>
----	---

---

**Description**

Generate HTML tag for element tr

**Usage**

```
tr(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
```

```

    is = NULL,
    itemid = NULL,
    itemprop = NULL,
    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
tr(class = "test", "Example")
```

---

track

*Generate HTML tag for element track*

---

**Description**

Generate HTML tag for element track

**Usage**

```
track(  
    accesskey = NULL,  
    autocapitalize = NULL,  
    class = NULL,  
    contenteditable = NULL,  
    default = NULL,  
    dir = NULL,  
    draggable = NULL,  
    hidden = NULL,  
    id = NULL,  
    inputmode = NULL,  
    is = NULL,  
    itemid = NULL,  
    itemprop = NULL,  
    itemref = NULL,  
    itemscope = NULL,  
    itemtype = NULL,  
    kind = NULL,  
    label = NULL,  
    lang = NULL,  
    part = NULL,  
    slot = NULL,  
    spellcheck = NULL,  
    src = NULL,  
    srclang = NULL,  
    style = NULL,  
    tabindex = NULL,  
    title = NULL,  
    custom_attr = NULL  
)
```

**Arguments**

<code>accesskey</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>default</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
kind	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
label	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
src	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
srclang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.



**Value**

A HTML tag string.

**Examples**

```
track(class = "test")
```

---

u

*Generate HTML tag for element u*

---

**Description**

Generate HTML tag for element u

**Usage**

```
u(  
  ...,  
  accesskey = NULL,  
  autocapitalize = NULL,  
  class = NULL,  
  contenteditable = NULL,  
  dir = NULL,  
  draggable = NULL,  
  hidden = NULL,  
  id = NULL,  
  inputmode = NULL,  
  is = NULL,  
  itemid = NULL,  
  itemprop = NULL,  
  itemref = NULL,  
  itemscope = NULL,  
  itemtype = NULL,  
  lang = NULL,  
  part = NULL,  
  slot = NULL,  
  spellcheck = NULL,  
  style = NULL,  
  tabindex = NULL,  
  title = NULL,  
  custom_attr = NULL  
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
u(class = "test", "Example")
```

---

ul	<i>Generate HTML tag for element ul</i>
----	---

---

**Description**

Generate HTML tag for element ul

**Usage**

```
ul(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
```

```

    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
ul(class = "test", "Example")
```

---

var	<i>Generate HTML tag for element var</i>
-----	--

---

**Description**

Generate HTML tag for element var

**Usage**

```
var(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
```

```

    itemref = NULL,
    itemscope = NULL,
    itemtype = NULL,
    lang = NULL,
    part = NULL,
    slot = NULL,
    spellcheck = NULL,
    style = NULL,
    tabindex = NULL,
    title = NULL,
    custom_attr = NULL
)

```

### Arguments

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
autocapitalize	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
class	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
contenteditable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
dir	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
draggable	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
hidden	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
id	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
inputmode	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
is	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemid	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemprop	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemref	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

itemscope	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
itemtype	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
lang	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
part	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
slot	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
spellcheck	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
style	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
tabindex	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
title	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
custom_attr	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
var(class = "test", "Example")
```

---

video

*Generate HTML tag for element video*

---

**Description**

Generate HTML tag for element video

**Usage**

```
video(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  autoPictureInPicture = NULL,
  autoplay = NULL,
  buffered = NULL,
```

```
class = NULL,  
contenteditable = NULL,  
controls = NULL,  
controlslist = NULL,  
crossorigin = NULL,  
currentTime = NULL,  
dir = NULL,  
disablePictureInPicture = NULL,  
disableRemotePlayback = NULL,  
draggable = NULL,  
duration = NULL,  
height = NULL,  
hidden = NULL,  
id = NULL,  
inputmode = NULL,  
intrinsicSize = NULL,  
is = NULL,  
itemid = NULL,  
itemprop = NULL,  
itemref = NULL,  
itemscope = NULL,  
itemtype = NULL,  
lang = NULL,  
loop = NULL,  
muted = NULL,  
part = NULL,  
playsinline = NULL,  
poster = NULL,  
preload = NULL,  
slot = NULL,  
spellcheck = NULL,  
src = NULL,  
style = NULL,  
tabindex = NULL,  
title = NULL,  
width = NULL,  
custom_attr = NULL  
)
```

### Arguments

- |                |  |
|----------------|--|
| ...            | A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible. |
| accesskey      | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |
| autocapitalize | A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.              |



<code>autoPictureInPicture</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>autoplay</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>buffered</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>controls</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>controlslist</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>crossorigin</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>currentTime</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>disablePictureInPicture</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>disableRemotePlayback</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>duration</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>height</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>intrinsicsize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>loop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>muted</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>playsinline</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>poster</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>preload</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>src</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>width</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
video(class = "test", "Example")
```

---

wbr

*Generate HTML tag for element wbr*


---

**Description**

Generate HTML tag for element wbr

**Usage**

```
wbr(
  ...,
  accesskey = NULL,
  autocapitalize = NULL,
  class = NULL,
  contenteditable = NULL,
  dir = NULL,
  draggable = NULL,
  hidden = NULL,
  id = NULL,
  inputmode = NULL,
  is = NULL,
  itemid = NULL,
  itemprop = NULL,
  itemref = NULL,
  itemscope = NULL,
  itemtype = NULL,
  lang = NULL,
  part = NULL,
  slot = NULL,
  spellcheck = NULL,
  style = NULL,
  tabindex = NULL,
  title = NULL,
  custom_attr = NULL
)
```

**Arguments**

...	A string or strings of permitted content for this HTML element tag. The user is responsible for determining what is permissible.
accesskey	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

<code>autocapitalize</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>class</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>contenteditable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>dir</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>draggable</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>hidden</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>id</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>inputmode</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>is</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemid</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemprop</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemref</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemscope</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>itemtype</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>lang</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>part</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>slot</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>spellcheck</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>style</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>tabindex</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>title</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.
<code>custom_attr</code>	A string of permitted content for this HTML attribute. The user is responsible for determining what is permissible.

**Value**

A HTML tag string.

**Examples**

```
wbr(class = "test", "Example")
```

# Index

a, 4  
abbr, 7  
address, 9  
area, 11  
article, 14  
aside, 16  
audio, 18  
  
b, 21  
base, 23  
bdi, 25  
bdo, 27  
blockquote, 30  
body, 32  
br, 35  
button, 37  
  
canvas, 40  
caption, 42  
cite, 45  
code, 47  
col, 49  
colgroup, 51  
  
data, 53  
datalist, 56  
dd, 58  
del, 60  
details, 62  
dfn, 65  
dialog, 67  
div, 69  
dl, 71  
dt, 73  
  
em, 76  
embed, 78  
  
fieldset, 80  
figcaption, 83  
figure, 85  
  
footer, 87  
form, 89  
  
h1, 92  
h2, 94  
h3, 96  
h4, 98  
h5, 100  
h6, 103  
head, 105  
header, 107  
hgroup, 109  
hr, 111  
html, 113  
html\_doc, 116  
  
i, 116  
iframe, 118  
img, 121  
input, 124  
ins, 128  
  
kbd, 131  
  
label, 133  
legend, 135  
li, 137  
link, 139  
  
main, 143  
map, 145  
mark, 147  
menu, 149  
meta, 151  
meter, 154  
  
nav, 156  
noscript, 159  
  
object, 161  
ol, 164

optgroup, 166  
option, 168  
output, 171

p, 173  
param, 175  
picture, 177  
pre, 179  
progress, 182

q, 184

rb, 186  
rp, 188  
rt, 190  
rtc, 193  
ruby, 195

s, 197  
samp, 199  
script, 201  
section, 204  
select, 206  
slot, 209  
small, 211  
source, 213  
span, 216  
strong, 218  
style, 220  
sub, 222  
summary, 225  
sup, 227

table, 229  
tbody, 231  
td, 233  
template, 236  
textarea, 238  
tfoot, 241  
th, 243  
thead, 246  
time, 248  
title, 250  
tr, 252  
track, 254

u, 257  
ul, 259

var, 261

video, 263

wbr, 267