

Package ‘leaflet.extras’

April 21, 2018

Type Package

Title Extra Functionality for 'leaflet' Package

Version 1.0.0

Description The 'leaflet' JavaScript library provides many plugins some of which are available in the core 'leaflet' package, but there are many more. It is not possible to support them all in the core 'leaflet' package. This package serves as an add-on to the 'leaflet' package by providing extra functionality via 'leaflet' plugins.

License GPL-3 | file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.1.0), leaflet (>= 2.0.0)

Imports htmlwidgets, htmltools, stringr, magrittr

Suggests jsonlite, readr

URL <https://github.com/bhaskarvk/leaflet.extras>,
<https://bhaskarvk.github.io/leaflet.extras/>

BugReports <https://github.com/bhaskarvk/leaflet.extras/issues>

RoxygenNote 6.0.1

NeedsCompilation no

Author Bhaskar Karambelkar [aut, cre],
Barret Schloerke [aut],
Bangyou Zheng [ctb] (Leaflet-search and Leaflet-GPS plugin integration),
Robin Cura [ctb] (Fixes for Draw Options),
Markus Voge [ctb] (Enhancements for Draw Options),
Markus Dumke [ctb] (Bounce Marker addition),
Mapbox [ctb, cph] (leaflet-omnivore, csv2geojson, and togeojson libraries),
Henry Thasler [ctb, cph] (Leaflet.Geodesic library),
Dennis Wilhelm [ctb, cph] (Leaflet.StyleEditor library),
Kirolos Risk [ctb, cph] (fuse.js library),
Tim Wisniewski [ctb, cph] (leaflet-choropleth library),

Leaflet [ctb, cph] (leaflet-draw library),
 Alexander Milevski [ctb, cph] (leaflet-draw-drag library),
 John Firebaugh [ctb, cph] (leaflet-fullscreen library),
 Stefano Cudini [ctb, cph] (leaflet-gps library),
 Johannes Rudolph [ctb, cph] (leaflet-hash library),
 Per Liedman [ctb, cph] (leaflet-measure-path library),
 Pavel Shramov [ctb, cph] (leaflet-plugins library),
 Filip Zavadil [ctb, cph] (leaflet-pulse-icon library),
 Stefano Cudini [ctb, cph] (leaflet-search library),
 CliffCloud [ctb, cph] (leaflet-sleep library),
 Ursudio [ctb, cph] (leaflet-webgl-heatmap library),
 Maxime Hadjinlian [ctb, cph] (leaflet.BounceMarker library),
 Vladimir Agafonkin [ctb, cph] (leaflet.heat library),
 Iván Sánchez Ortega [ctb, cph] (leaflet.tilelayer.pouchdbcached
 library),
 Dale Harvey [ctb, cph] (pouchdb-browser library),
 Mike Bostock [ctb, cph] (topojson library)

Maintainer Bhaskar Karambelkar <bhaskarvk@gmail.com>

Repository CRAN

Date/Publication 2018-04-21 21:20:53 UTC

R topics documented:

addAwesomeMarkersDependencies	3
addBingTiles	3
addBootstrapDependency	4
addBounceMarkers	4
addDrawToolbar	5
addFullscreenControl	6
addGeodesicPolylines	7
addGeoJSONv2	9
addHash	15
addHeatmap	16
addResetMapButton	18
addSearchFeatures	19
addSearchOSM	19
addStyleEditor	21
addWebGLHeatmap	22
addWMSLegend	25
debugMap	26
drawShapeOptions	27
enableMeasurePath	29
enableTileCaching	30
gpsOptions	31
leaflet.extras	32
leafletExtrasDependencies	32
propsToHTML	33

addAwesomeMarkersDependencies 3

pulseIconList	34
searchOptions	36
suspendScroll	37
weatherIconList	38

Index 41

addAwesomeMarkersDependencies
Add AwesomeMarkers and related lib dependencies to a map

Description

Add AwesomeMarkers and related lib dependencies to a map

Usage

```
addAwesomeMarkersDependencies(map, libs)
```

Arguments

map	the map widget
libs	char vector with lib names.

addBingTiles *Adds Bing Tiles Layer*

Description

Adds Bing Tiles Layer

Usage

```
addBingTiles(map, apikey = Sys.getenv("BING_MAPS_API_KEY"),  
  imagerySet = c("Aerial", "AerialWithLabels", "CanvasDark", "CanvasLight",  
  "CanvasGray", "Road"), layerId = NULL, group = NULL, ...)
```

Arguments

map	The Map widget
apikey	String. Bing API Key
imagerySet	String. Type of Tiles to display
layerId	String. An optional unique ID for the layer
group	String. An optional group name for the layer
...	Optional Parameters required by the Bing API described at https://msdn.microsoft.com/en-us/library/ff701716.aspx

See Also

Get a Bing Maps API Key: <https://msdn.microsoft.com/en-us/library/ff428642.aspx>

addBootstrapDependency

Add Bootstrap dependency to a map

Description

Add Bootstrap dependency to a map

Usage

```
addBootstrapDependency(map)
```

Arguments

map	the map widget
-----	----------------

addBounceMarkers

Add Bounce Markers to map

Description

Add Bounce Markers to map

Usage

```
addBounceMarkers(map, lat, lng, duration = 1000, height = 100)
```

Arguments

map	map object created by leaflet:leaflet
lat	numeric latitude
lng	numeric longitude
duration	integer scalar: The duration of the animation in milliseconds.
height	integer scalar: Height at which the marker is dropped.

Author(s)

Markus Dumke

See Also

[GitHub: leaflet.bouncemarker](#)

Examples

```
leaflet() %>%
  addTiles() %>%
  addBounceMarkers(49, 11)
```

addDrawToolbar	<i>Adds a Toolbar to draw shapes/points on the map.</i>
----------------	---

Description

Adds a Toolbar to draw shapes/points on the map.

Removes the draw toolbar

Usage

```
addDrawToolbar(map, targetLayerId = NULL, targetGroup = NULL,
  position = c("topleft", "topright", "bottomleft", "bottomright"),
  polylineOptions = drawPolylineOptions(),
  polygonOptions = drawPolygonOptions(),
  circleOptions = drawCircleOptions(),
  rectangleOptions = drawRectangleOptions(),
  markerOptions = drawMarkerOptions(),
  circleMarkerOptions = drawCircleMarkerOptions(), editOptions = FALSE,
  singleFeature = FALSE)
```

```
removeDrawToolbar(map, clearFeatures = FALSE)
```

Arguments

map	The map widget.
targetLayerId	An optional layerId of a GeoJSON/TopoJSON layer whose features need to be editable. Used for adding a GeoJSON/TopoJSON layer and then editing the features using the draw plugin.
targetGroup	An optional group name of a Feature Group whose features need to be editable. Used for adding shapes(markers, lines, polygons) and then editing them using the draw plugin. You can either set layerId or group or none but not both.
position	The position where the toolbar should appear.
polylineOptions	See drawPolylineOptions() . Set to FALSE to disable polyline drawing.
polygonOptions	See drawPolygonOptions() . Set to FALSE to disable polygon drawing.
circleOptions	See drawCircleOptions() . Set to FALSE to disable circle drawing.
rectangleOptions	See drawRectangleOptions() . Set to FALSE to disable rectangle drawing.
markerOptions	See drawMarkerOptions() . Set to FALSE to disable marker drawing.

circleMarkerOptions	See drawCircleMarkerOptions() . Set to FALSE to disable circle marker drawing.
editOptions	By default editing is disable. To enable editing pass editToolbarOptions() .
singleFeature	When set to TRUE, only one feature can be drawn at a time, the previous ones being removed.
clearFeatures	whether to clear the map of drawn features.

Examples

```
leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addDrawToolbar(
    targetGroup = "draw",
    editOptions = editToolbarOptions(
      selectedPathOptions = selectedPathOptions()
    )
  ) %>%
  addLayersControl(
    overlayGroups = c("draw"),
    options = layersControlOptions(collapsed = FALSE)
  ) %>%
  addStyleEditor()

## for more examples see
# browseURL(system.file("examples/draw.R", package = "leaflet.extras"))
```

addFullscreenControl *Add fullscreen control*

Description

Add a fullscreen control button

Usage

```
addFullscreenControl(map, position = "topleft", pseudoFullscreen = FALSE)
```

Arguments

map	The leaflet map
position	position of control: "topleft", "topright", "bottomleft", or "bottomright"
pseudoFullscreen	if true, fullscreen to page width and height

Examples

```
leaflet() %>%
  addTiles() %>%
  addFullscreenControl()
```

addGeodesicPolylines *Add Geodesic Lines*

Description

Add Geodesic Lines

Usage

```
addGeodesicPolylines(map, lng = NULL, lat = NULL, layerId = NULL,
  group = NULL, steps = 10, wrap = TRUE, stroke = TRUE,
  color = "#03F", weight = 5, opacity = 0.5, dashArray = NULL,
  smoothFactor = 1, noClip = FALSE, popup = NULL, popupOptions = NULL,
  label = NULL, labelOptions = NULL, options = pathOptions(),
  highlightOptions = NULL, data = getMapData(map))
```

```
addGreatCircles(map, lat_center = NULL, lng_center = NULL, radius,
  layerId = NULL, group = NULL, steps = 10, wrap = TRUE,
  stroke = TRUE, color = "#03F", weight = 5, opacity = 0.5,
  dashArray = NULL, smoothFactor = 1, noClip = FALSE, popup = NULL,
  popupOptions = NULL, label = NULL, labelOptions = NULL,
  options = pathOptions(), highlightOptions = NULL,
  data = getMapData(map))
```

Arguments

map	map object
lng	vector of longitudes
lat	vector of latitudes
layerId	the layer id
group	the name of the group this raster image should belong to (see
steps	Defines how many intermediate points are generated along the path. More steps mean a smoother path.
wrap	Wrap line at map border (date line). Set to "false" if you want lines to cross the dateline (experimental, see noWrap-example on how to use)
stroke	whether to draw stroke along the path (e.g. the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)

dashArray	a string that defines the stroke dash pattern
smoothFactor	how much to simplify the polyline on each zoom level
noClip	whether to disable polyline clipping (more means better performance and less accurate representation)
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code>)
popupOptions	A Vector of <code>popupOptions</code> to provide popups for security reasons)
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	a list of additional options, intended to be provided by a call to <code>pathOptions()</code>
highlightOptions	Options for highlighting the shape on mouse over.
data	map data
lat_center, lng_center	lat/lng for the center
radius	in meters

Functions

- `addGreatCircles`: Adds a Great Circle to the map

Examples

```

berlin <- c(52.51, 13.4)
losangeles <- c(34.05, -118.24)
santiago <- c(-33.44, -70.71)
tokio <- c(35.69, 139.69)
sydney <- c(-33.91, 151.08)
capetown <- c(-33.91, 18.41)
calgary <- c(51.05, -114.08)
hammerfest <- c(70.67, 23.68)
barrow <- c(71.29, -156.76)

df <- as.data.frame(rbind(hammerfest, calgary, losangeles, santiago, capetown, tokio, barrow))
names(df) <- c("lat", "lng")

leaflet(df) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addGeodesicPolylines(lng = ~lng, lat = ~lat, weight = 2, color = "red",
    steps = 50, opacity = 1) %>%
  addCircleMarkers(df, lat = ~lat, lng = ~lng, radius = 3, stroke = FALSE,
    fillColor = "black", fillOpacity = 1)

## for more examples see
# browseURL(system.file("examples/geodesic.R", package = "leaflet.extras"))

```

 addGeoJSONv2

Adds a GeoJSON/TopoJSON to the leaflet map.

Description

This is a feature rich alternative to the [addGeoJSON](#) & [addTopoJSON](#) with options to map feature properties to labels, popups, colors, markers etc.

Options to customize a Choropleth Legend

Adds a GeoJSON/TopoJSON Choropleth.

Adds a KML to the leaflet map.

Adds a KML Choropleth.

Options for parsing CSV

Adds a CSV to the leaflet map.

Adds a GPX to the leaflet map.

Usage

```
addGeoJSONv2(map, geojson, layerId = NULL, group = NULL,
  markerType = NULL, markerIcons = NULL, markerIconProperty = NULL,
  markerOptions = leaflet::markerOptions(), clusterOptions = NULL,
  clusterId = NULL, labelProperty = NULL,
  labelOptions = leaflet::labelOptions(), popupProperty = NULL,
  popupOptions = leaflet::popupOptions(), stroke = TRUE, color = "#03F",
  weight = 5, opacity = 0.5, fill = TRUE, fillColor = color,
  fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1, noClip = FALSE,
  pathOptions = leaflet::pathOptions(), highlightOptions = NULL)
```

```
legendOptions(title = NULL, position = c("bottomleft", "bottomright",
  "topleft", "topright"), locale = "en-US", numberFormatOptions = list(style
  = "decimal", maximumFractionDigits = 2))
```

```
addGeoJSONChoropleth(map, geojson, layerId = NULL, group = NULL,
  valueProperty, labelProperty = NULL,
  labelOptions = leaflet::labelOptions(), popupProperty = NULL,
  popupOptions = leaflet::popupOptions(), scale = c("white", "red"),
  steps = 5, mode = "q", channelMode = c("rgb", "lab", "hsl", "lch"),
  padding = NULL, correctLightness = FALSE, bezierInterpolate = FALSE,
  colors = NULL, stroke = TRUE, color = "#03F", weight = 1,
  opacity = 0.5, fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1,
  noClip = FALSE, pathOptions = leaflet::pathOptions(),
  highlightOptions = NULL, legendOptions = NULL)
```

```
addKML(map, kml, layerId = NULL, group = NULL, markerType = NULL,
  markerIcons = NULL, markerIconProperty = NULL,
```

```

markerOptions = leaflet::markerOptions(), clusterOptions = NULL,
clusterId = NULL, labelProperty = NULL,
labelOptions = leaflet::labelOptions(), popupProperty = NULL,
popupOptions = leaflet::popupOptions(), stroke = TRUE, color = "#03F",
weight = 5, opacity = 0.5, fill = TRUE, fillColor = color,
fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1, noClip = FALSE,
pathOptions = leaflet::pathOptions(), highlightOptions = NULL)

addKMLChoropleth(map, kml, layerId = NULL, group = NULL, valueProperty,
labelProperty = NULL, labelOptions = leaflet::labelOptions(),
popupProperty = NULL, popupOptions = leaflet::popupOptions(),
scale = c("white", "red"), steps = 5, mode = "q",
channelMode = c("rgb", "lab", "hsl", "lch"), padding = NULL,
correctLightness = FALSE, bezierInterpolate = FALSE, colors = NULL,
stroke = TRUE, color = "#03F", weight = 1, opacity = 0.5,
fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1, noClip = FALSE,
pathOptions = leaflet::pathOptions(), highlightOptions = NULL,
legendOptions = NULL)

csvParserOptions(latfield, lonfield, delimiter = ",")

addCSV(map, csv, csvParserOptions, layerId = NULL, group = NULL,
markerType = NULL, markerIcons = NULL, markerIconProperty = NULL,
markerOptions = leaflet::markerOptions(), clusterOptions = NULL,
clusterId = NULL, labelProperty = NULL,
labelOptions = leaflet::labelOptions(), popupProperty = NULL,
popupOptions = leaflet::popupOptions(), stroke = TRUE, color = "#03F",
weight = 5, opacity = 0.5, fill = TRUE, fillColor = color,
fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1, noClip = FALSE,
pathOptions = leaflet::pathOptions(), highlightOptions = NULL)

addGPX(map, gpx, layerId = NULL, group = NULL, markerType = NULL,
markerIcons = NULL, markerIconProperty = NULL,
markerOptions = leaflet::markerOptions(), clusterOptions = NULL,
clusterId = NULL, labelProperty = NULL,
labelOptions = leaflet::labelOptions(), popupProperty = NULL,
popupOptions = leaflet::popupOptions(), stroke = TRUE, color = "#03F",
weight = 5, opacity = 0.5, fill = TRUE, fillColor = color,
fillOpacity = 0.2, dashArray = NULL, smoothFactor = 1, noClip = FALSE,
pathOptions = leaflet::pathOptions(), highlightOptions = NULL)

```

Arguments

map	the leaflet map widget
geojson	a GeoJSON/TopoJSON URL or file contents in a character vector.
layerId	the layer id
group	the name of the group this raster image should belong to (see the same parameter under addTiles)

markerType	The type of marker. either "marker" or "circleMarker"
markerIcons	Icons for Marker. Can be a single marker using makeIcon or a list of markers using iconList
markerIconProperty	The property of the feature to use for marker icon. Can be a JS function which accepts a feature and returns an index of markerIcons. In either case the result must be one of the indexes of markerIcons.
markerOptions	The options for markers
clusterOptions	if not NULL, markers will be clustered using Leaflet.markercluster ; you can use markerClusterOptions() to specify marker cluster options
clusterId	the id for the marker cluster layer
labelProperty	The property to use for the label. You can also pass in a JS function that takes in a feature and returns a text/HTML content.
labelOptions	A Vector of labelOptions to provide label
popupProperty	The property to use for popup content You can also pass in a JS function that takes in a feature and returns a text/HTML content.
popupOptions	A Vector of popupOptions to provide popups
stroke	whether to draw stroke along the path (e.g. the borders of polygons or circles)
color	stroke color
weight	stroke width in pixels
opacity	stroke opacity (or layer opacity for tile layers)
fill	whether to fill the path with color (e.g. filling on polygons or circles)
fillColor	fill color
fillOpacity	fill opacity
dashArray	a string that defines the stroke dash pattern
smoothFactor	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
noClip	whether to disable polyline clipping
pathOptions	Options for shapes
highlightOptions	Options for highlighting the shape on mouse over. options for each label. Default NULL you can use highlightOptions() to specify highlight options
title	An optional title for the legend
position	legend position
locale	The numbers will be formatted using this locale
numberFormatOptions	Options for formatting numbers
valueProperty	The property to use for coloring
scale	The scale to use from chroma.js
steps	number of breaks

mode	q for quantile, e for equidistant, k for k-means
channelMode	Default "rgb", can be one of "rgb", "lab", "hsl", "lch"
padding	either a single number or a 2 number vector for clipping color values at ends.
correctLightness	whether to correct lightness
bezierInterpolate	whether to use bezier interpolate for determining colors
colors	overrides scale with manual colors
legendOptions	Options to show a legend.
kml	a KML URL or contents in a character vector.
latfield	field name for latitude
lonfield	field name for longitude
delimiter	field separator
csv	a CSV URL or contents in a character vector.
csvParserOptions	options for parsing the CSV. Use csvParserOptions() to supply csv parser options.
gpx	a GPX URL or contents in a character vector.

Examples

```
## addGeoJSONv2
geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/historic-landmarks-points.geojson"
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLGeoJSONHeatmap(
    geoJson, size = 30 , units = "px"
  ) %>%
  addGeoJSONv2(
    geoJson,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 0.7,
    markerOptions = markerOptions(radius = 2)
  )

## for more examples see
# browseURL(system.file("examples/draw.R", package = "leaflet.extras"))
# browseURL(system.file("examples/geojsonv2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))

## addGeoJSONChoropleth
```

```

geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/ward-2012.geojson"
)

leaflet() %>%
  addTiles() %>%
  setView(-77.0369, 38.9072, 11) %>%
  addBootstrapDependency() %>%
  enableMeasurePath() %>%
  addGeoJSONChoropleth(
    geoJson,
    valueProperty = "AREASQMI",
    scale = c("white", "red"),
    mode = "q",
    steps = 4,
    padding = c(0.2, 0),
    labelProperty = "NAME",
    popupProperty = propstoHTMLTable(
      props = c("NAME", "AREASQMI", "REP_NAME", "WEB_URL", "REP_PHONE", "REP_EMAIL", "REP_OFFICE"),
      table.attrs = list(class = "table table-striped table-bordered"),
      drop.na = TRUE
    ),
    color = "#ffffff", weight = 1, fillOpacity = 0.7,
    highlightOptions = highlightOptions(
      weight = 2, color = "#000000",
      fillOpacity = 1, opacity = 1,
      bringToFront = TRUE, sendToBack = TRUE),
    pathOptions = pathOptions(
      showMeasurements = TRUE,
      measurementOptions = measurePathOptions(imperial = TRUE))

## for more examples see
# browseURL(system.file("examples/geojsonv2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/measurePath.R", package = "leaflet.extras"))
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))

## addKML
kml <- readr::read_file(
  system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLKMLHeatmap(kml, size = 20, units = "px") %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1)
  )

```

```

## addKMLChoropleth
kml <- readr::read_file(
  system.file("examples/data/kml/cb_2015_us_state_20m.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  addBootstrapDependency() %>%
  setView(-98.583333, 39.833333, 4) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addKMLChoropleth(
    kml,
    valueProperty = JS(
      'function(feature){
        var props = feature.properties;
        var aland = props.ALAND/100000;
        var awater = props.AWATER/100000;
        return 100*awater/(awater+aland);
      }'
    ),
    scale = "OrRd", mode = "q", steps = 5,
    padding = c(0.2, 0),
    popupProperty = "description",
    labelProperty = "NAME",
    color = "#ffffff", weight = 1, fillOpacity = 1,
    highlightOptions = highlightOptions(
      fillOpacity = 1, weight = 2, opacity = 1, color = "#000000",
      bringToFront = TRUE, sendToBack = TRUE
    ),
    legendOptions = legendOptions(
      title = "% of Water Area",
      numberFormatOptions = list(
        style = "decimal",
        maximumFractionDigits = 2
      )
    )
  )
)

## addCSV
csv <- readr::read_file(
  system.file("examples/data/csv/world_airports.csv.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.DarkMatterNoLabels) %>%
  addCSV(
    csv,
    csvParserOptions("latitude_deg", "longitude_deg"),
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "red", fillOpacity = 1,

```

```

    markerOptions = markerOptions(radius = 0.5))

## addGPX
airports <- readr::read_file(
  system.file("examples/data/gpx/md-airports.gpx.zip", package = "leaflet.extras")
)

leaflet() %>%
  addBootstrapDependency() %>%
  setView(-76.6413, 39.0458, 8) %>%
  addProviderTiles(
    providers$CartoDB.Positron,
    options = providerTileOptions(detectRetina = TRUE)
  ) %>%
  addWebGLGPXHeatmap(airports, size = 20000, group = "airports", opacity = 0.9) %>%
  addGPX(
    airports,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1.5),
    group = "airports"
  )

## for a larger example see
# browseURL(system.file("examples/GPX.R", package = "leaflet.extras"))

```

addHash

Add dynamic URL Hash

Description

Leaflet-hash lets you to add dynamic URL hashes to web pages with Leaflet maps. You can easily link users to specific map views.

Usage

```
addHash(map)
```

Arguments

map	The leaflet map
-----	-----------------

Examples

```

leaflet() %>%
  addTiles() %>%
  addHash()

```

`addHeatmap`*Add a heatmap*

Description

Add a heatmap

Adds a heatmap with data from a GeoJSON/TopoJSON file/url

Adds a heatmap with data from a KML file/url

Adds a heatmap with data from a CSV file/url

Adds a heatmap with data from a GPX file/url

removes the heatmap

clears the heatmap

Usage

```
addHeatmap(map, lng = NULL, lat = NULL, intensity = NULL,  
           layerId = NULL, group = NULL, minOpacity = 0.05, max = 1,  
           radius = 25, blur = 15, gradient = NULL, cellSize = NULL,  
           data = leaflet::getMapData(map))
```

```
addGeoJSONHeatmap(map, geojson, layerId = NULL, group = NULL,  
                  intensityProperty = NULL, minOpacity = 0.05, max = 1, radius = 25,  
                  blur = 15, gradient = NULL, cellSize = NULL)
```

```
addKMLHeatmap(map, kml, layerId = NULL, group = NULL,  
              intensityProperty = NULL, minOpacity = 0.05, max = 1, radius = 25,  
              blur = 15, gradient = NULL, cellSize = NULL)
```

```
addCSVHeatmap(map, csv, csvParserOptions, layerId = NULL, group = NULL,  
              intensityProperty = NULL, minOpacity = 0.05, max = 1, radius = 25,  
              blur = 15, gradient = NULL, cellSize = NULL)
```

```
addGPXHeatmap(map, gpx, layerId = NULL, group = NULL,  
              intensityProperty = NULL, minOpacity = 0.05, max = 1, radius = 25,  
              blur = 15, gradient = NULL, cellSize = NULL)
```

```
removeHeatmap(map, layerId)
```

```
clearHeatmap(map)
```

Arguments

`map` the map widget.

lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from data)
intensity	intensity of the heat. A vector of numeric values or a formula.
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
minOpacity	minimum opacity at which the heat will start
max	maximum point intensity. The default is <code>1.0</code>
radius	radius of each "point" of the heatmap. The default is <code>25</code> .
blur	amount of blur to apply. The default is <code>15</code> . <code>blur=1</code> means no blur.
gradient	palette name from <code>RColorBrewer</code> or an array of colors to be provided to <code>colorNumeric</code> , or a color mapping function returned from <code>colorNumeric</code>
cellSize	the cell size in the grid. Points which are closer than this may be merged. Defaults to <code>'radius / 2'</code> . Set to <code>'1'</code> to do almost no merging.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden
geojson	The geojson or topojson url or contents as string.
intensityProperty	The property to use for determining the intensity at a point. Can be a "string" or a JS function, or <code>NULL</code> .
kml	The KML url or contents as string.
csv	The CSV url or contents as string.
csvParserOptions	options for parsing the CSV. Use <code>csvParserOptions()</code> to supply csv parser options.
gpx	The GPX url or contents as string.

Examples

```
leaflet(quakes) %>%
  addProviderTiles(providers$CartoDB.DarkMatter) %>%
  setView( 178, -20, 5 ) %>%
  addHeatmap(
    lng = ~long, lat = ~lat, intensity = ~mag,
    blur = 20, max = 0.05, radius = 15
  )
```

```
## for more examples see
# browseURL(system.file("examples/heatmaps.R", package = "leaflet.extras"))
kml <- readr::read_file(
  system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addKMLHeatmap(kml, radius = 7) %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1))

## for more examples see
# browseURL(system.file("examples/KML.R", package = "leaflet.extras"))
```

addResetMapButton *Reset map's view to original view*

Description

Reset map's view to original view

Usage

```
addResetMapButton(map)
```

Arguments

map The map widget

Examples

```
leaflet() %>%
  addTiles() %>%
  addResetMapButton()
```

addSearchFeatures *Add a feature search control to the map.*

Description

Add a feature search control to the map.

Removes the feature search control from the map.

Usage

```
addSearchFeatures(map, targetGroups, options = searchFeaturesOptions())
```

```
removeSearchFeatures(map, clearFeatures = FALSE)
```

Arguments

map	a map widget object
targetGroups	A vector of group names of groups whose features need to be searched.
options	Search Options
clearFeatures	Boolean. If TRUE the features that this control searches will be removed too.

Value

modified map

modified map

addSearchOSM *Add a OSM search control to the map.*

Description

Add a OSM search control to the map.

Removes the OSM search control from the map.

Add a Google search control to the map.

Removes the Google search control from the map.

Add a US Census Bureau search control to the map.

Removes the US Census Bureau search control from the map.

Usage

```

addSearchOSM(map, options = searchOptions(autoCollapse = TRUE, minLength = 2))

removeSearchOSM(map)

addReverseSearchOSM(map, showSearchLocation = TRUE, showBounds = FALSE,
  showFeature = TRUE, fitBounds = TRUE, displayText = TRUE,
  group = NULL)

addSearchGoogle(map, apikey = Sys.getenv("GOOGLE_MAP_GEOCODING_KEY"),
  options = searchOptions(autoCollapse = TRUE, minLength = 2))

removeSearchGoogle(map)

addReverseSearchGoogle(map, apikey = Sys.getenv("GOOGLE_MAP_GEOCODING_KEY"),
  showSearchLocation = TRUE, showBounds = FALSE, showFeature = TRUE,
  fitBounds = TRUE, displayText = TRUE, group = NULL)

addSearchUSCensusBureau(map, options = searchOptions(autoCollapse = TRUE,
  minLength = 20))

removeSearchUSCensusBureau(map)

```

Arguments

map	a map widget object
options	Search Options
showSearchLocation	Boolean. If TRUE displays a Marker on the searched location's coordinates.
showBounds	Boolean. If TRUE show the bounding box of the found feature.
showFeature	Boolean. If TRUE show the found feature. Depending upon the feature found this can be a marker, a line or a polygon.
fitBounds	Boolean. If TRUE set maps bounds to queried and found location. For this to be effective one of showSearchLocation, showBounds, showFeature shoule also be TRUE.
displayText	Boolean. If TRUE show a text box with found location's name on the map.
group	String. An optional group to hold all the searched locations and their results.
apikey	String. API Key for Google GeoCoding Service.

Value

modified map
modified map
modified map
modified map

modified map
 modified map
 modified map
 modified map

Examples

```
leaflet() %>%
  addProviderTiles(providers$Esri.WorldStreetMap) %>%
  addResetMapButton() %>%
  addSearchGoogle()

## for more examples see
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
```

addStyleEditor	<i>Add style editor</i>
----------------	-------------------------

Description

Add style editor
 Remove style editor

Usage

```
addStyleEditor(map, position = c("topleft", "topright", "bottomleft",
  "bottomright"), openOnLeafletDraw = TRUE, useGrouping = FALSE, ...)

removeStyleEditor(map)
```

Arguments

map	the map widget
position	position of the control
openOnLeafletDraw	whether to open automatically when used with addDrawToolbar()
useGrouping	Should be false to work with addDrawToolbar()
...	other options. See plugin code

Examples

```

leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addDrawToolbar(
    targetGroup = "draw",
    editOptions = editToolbarOptions(selectedPathOptions = selectedPathOptions())
  ) %>%
  addLayersControl(
    overlayGroups = c("draw"), options = layersControlOptions(collapsed = FALSE)
  ) %>%
  # add the style editor to alter shapes added to map
  addStyleEditor()

```

addWebGLHeatmap	<i>Add a webgl heatmap</i>
-----------------	----------------------------

Description

Add a webgl heatmap

Adds a heatmap with data from a GeoJSON/TopoJSON file/url

Adds a heatmap with data from a KML file/url

Adds a heatmap with data from a CSV file/url

Adds a heatmap with data from a GPX file/url

removes the webgl heatmap

clears the webgl heatmap

Usage

```

addWebGLHeatmap(map, lng = NULL, lat = NULL, intensity = NULL,
  layerId = NULL, group = NULL, size = "30000", units = "m",
  opacity = 1, gradientTexture = NULL, alphaRange = 1,
  data = leaflet::getMapData(map))

```

```

addWebGLGeoJSONHeatmap(map, geojson, layerId = NULL, group = NULL,
  intensityProperty = NULL, size = "30000", units = "m", opacity = 1,
  gradientTexture = NULL, alphaRange = 1)

```

```

addWebGLKMLHeatmap(map, kml, layerId = NULL, group = NULL,
  intensityProperty = NULL, size = "30000", units = "m", opacity = 1,
  gradientTexture = NULL, alphaRange = 1)

```

```

addWebGLCSVHeatmap(map, csv, csvParserOptions, layerId = NULL, group = NULL,
  intensityProperty = NULL, size = "30000", units = "m", opacity = 1,
  gradientTexture = NULL, alphaRange = 1)

```

```
addWebGLGPXHeatmap(map, gpx, layerId = NULL, group = NULL,
  intensityProperty = NULL, size = "30000", units = "m", opacity = 1,
  gradientTexture = NULL, alphaRange = 1)
```

```
removeWebGLHeatmap(map, layerId)
```

```
clearWebGLHeatmap(map)
```

Arguments

map	the map to add pulse Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named lng, long, or longitude (case-insensitively)
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and latitude are used when guessing the latitude column from data)
intensity	intensity of the heat. A vector of numeric values or a formula.
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
size	in meters or pixels
units	either "m" or "px"
opacity	for the canvas element
gradientTexture	Alternative colors for heatmap. allowed values are "skyline", "deep-sea"
alphaRange	adjust transparency by changing to value between 0 and 1
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden
geojson	The geojson or topojson url or contents as string.
intensityProperty	The property to use for determining the intensity at a point. Can be a "string" or a JS function, or NULL.
kml	The KML url or contents as string.
csv	The CSV url or contents as string.
csvParserOptions	options for parsing the CSV. Use <code>csvParserOptions()</code> to supply csv parser options.
gpx	The GPX url or contents as string.

Examples

```

## addWebGLHeatmap
leaflet(quakes) %>%
  addProviderTiles(providers$CartoDB.DarkMatter) %>%
  addWebGLHeatmap(lng = ~long, lat = ~lat, size = 60000)

## for more examples see
# browseURL(system.file("examples/webglHeatmaps.R", package = "leaflet.extras"))
## addWebGLGeoJSONHeatmap
geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/historic-landmarks-points.geojson"
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLGeoJSONHeatmap(
    geoJson, size = 30, units = "px"
  ) %>%
  addGeoJSONv2(
    geoJson,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 0.7,
    markerOptions = markerOptions(radius = 2)
  )

## for more examples see
# browseURL(system.file("examples/geojsonV2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))
## addWebGLKMLHeatmap
kml <- readr::read_file(
  system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>% setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLKMLHeatmap(kml, size = 20, units = "px") %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1))

## addWebGLCSVHeatmap
csv <- readr::read_file(
  system.file("examples/data/csv/world_airports.csv.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.DarkMatterNoLabels) %>%

```



```
addWebGLCSVHeatmap(  
  csv,  
  csvParserOptions("latitude_deg", "longitude_deg"),  
  size = 10, units = "px")  
  
airports <- readr::read_file(  
  system.file("examples/data/gpx/md-airports.gpx.zip", package = "leaflet.extras")  
)  
  
leaflet() %>%  
  addBootstrapDependency() %>%  
  setView(-76.6413, 39.0458, 8) %>%  
  addProviderTiles(  
    providers$CartoDB.Positron,  
    options = providerTileOptions(detectRetina = TRUE)  
  ) %>%  
  addWebGLGPXHeatmap(  
    airports,  
    size = 20000,  
    group = "airports",  
    opacity = 0.9  
  ) %>%  
  addGPX(  
    airports,  
    markerType = "circleMarker",  
    stroke = FALSE, fillColor = "black", fillOpacity = 1,  
    markerOptions = markerOptions(radius = 1.5),  
    group = "airports"  
  )  
  
## for a larger example see  
# browseURL(system.file("examples/GPX.R", package = "leaflet.extras"))
```

addWMSLegend

Add WMS Legend

Description

Add a WMS Legend

Usage

```
addWMSLegend(map, uri, position = "topright", layerId = NULL)
```

Arguments

map	The leaflet map
uri	The legend URI

position position of control: "topleft", "topright", "bottomleft", or "bottomright"
 layerId A unique ID for the Legend

Examples

```
leaflet(
  options = leafletOptions(
    center = c(-33.95293, 20.82824),
    zoom = 14,
    minZoom = 5,
    maxZoom = 18,
    maxBounds = list(
      c(-33.91444, 20.75351),
      c(-33.98731, 20.90626)
    )
  )
) %>%
addWMSTiles(
  baseUrl = paste0(
    "http://maps.kartoza.com/web/?",
    "map=/web/Boosmansbos/Boosmansbos.qgs"
  ),
  layers = "Boosmansbos",
  options = WMSTileOptions(format = "image/png", transparent = TRUE),
  attribution = paste0(
    "(c)<a href= \"http://kartoza.com\">Kartoza.com</a> and ",
    "<a href= \"http://www.ngi.gov.za/\">SA-NGI</a>"
  )
) %>%
addWMSLegend(
  uri = paste0(
    "http://maps.kartoza.com/web/?",
    "map=/web/Boosmansbos/Boosmansbos.qgs&&SERVICE=WMS&VERSION=1.3.0",
    "&SLD_VERSION=1.1.0&REQUEST=GetLegendGraphic&FORMAT=image/jpeg&LAYER=Boosmansbos&STYLE="
  )
)
)
```

debugMap

For debugging a leaflet map

Description

For debugging a leaflet map

Usage

```
debugMap(map)
```

Arguments

map The map widget

drawShapeOptions	<i>Options for drawn shapes</i>
------------------	---------------------------------

Description

- Options for drawn shapes
- Options for drawing polylines
- Options for drawing polygons
- Options for drawing rectangles
- Options for drawing Circles
- Options for drawing markers
- Options for drawing markers
- Options for path when in editMode
- Options for editing shapes

Usage

```
drawShapeOptions(stroke = TRUE, color = "#03f", weight = 1, opacity = 1,
  fill = TRUE, fillColor = "#03f", fillOpacity = 0.4, dashArray = NULL,
  lineCap = NULL, lineJoin = NULL, clickable = TRUE,
  pointerEvents = NULL, smoothFactor = 1, noClip = TRUE)
```

```
drawPolylineOptions(allowIntersection = TRUE, drawError = list(color =
  "#b00b00", timeout = 2500), guidelineDistance = 20,
  maxGuideLineLength = 4000, showLength = TRUE, metric = TRUE,
  feet = TRUE, nautic = FALSE, zIndexOffset = 2000,
  shapeOptions = drawShapeOptions(fill = FALSE), repeatMode = FALSE)
```

```
drawPolygonOptions(showArea = FALSE, metric = TRUE,
  shapeOptions = drawShapeOptions(), repeatMode = FALSE)
```

```
drawRectangleOptions(showArea = TRUE, metric = TRUE,
  shapeOptions = drawShapeOptions(), repeatMode = FALSE)
```

```
drawCircleOptions(showRadius = TRUE, metric = TRUE, feet = TRUE,
  nautic = FALSE, shapeOptions = drawShapeOptions(), repeatMode = FALSE)
```

```
drawMarkerOptions(markerIcon = NULL, zIndexOffset = 2000,
  repeatMode = FALSE)
```

```
drawCircleMarkerOptions(stroke = TRUE, color = "#3388ff", weight = 4,
  opacity = 0.5, fill = TRUE, fillColor = NULL, fillOpacity = 0.2,
  clickable = TRUE, zIndexOffset = 2000, repeatMode = FALSE)
```

```
selectedPathOptions(dashArray = c("10, 10"), weight = 2, color = "black",
  fill = TRUE, fillColor = "black", fillOpacity = 0.6,
  maintainColor = FALSE)
```

```
editToolbarOptions(edit = TRUE, remove = TRUE, selectedPathOptions = NULL,
  allowIntersection = TRUE)
```

Arguments

<code>stroke</code>	Whether to draw stroke along the path. Set it to false to disable borders on polygons or circles.
<code>color</code>	Stroke color.
<code>weight</code>	Stroke width in pixels.
<code>opacity</code>	Stroke opacity.
<code>fill</code>	Whether to fill the path with color. Set it to false to disable filling on polygons or circles.
<code>fillColor</code>	same as color Fill color.
<code>fillOpacity</code>	Fill opacity.
<code>dashArray</code>	A string that defines the stroke dash pattern. Doesn't work on canvas-powered layers (e.g. Android 2).
<code>lineCap</code>	A string that defines shape to be used at the end of the stroke.
<code>lineJoin</code>	A string that defines shape to be used at the corners of the stroke.
<code>clickable</code>	If false, the vector will not emit mouse events and will act as a part of the underlying map.
<code>pointerEvents</code>	Sets the pointer-events attribute on the path if SVG backend is used.
<code>smoothFactor</code>	How much to simplify the polyline on each zoom level. More means better performance and smoother look, and less means more accurate representation.
<code>noClip</code>	Disabled polyline clipping.
<code>allowIntersection</code>	Determines if line segments can cross.
<code>drawError</code>	Configuration options for the error that displays if an intersection is detected.
<code>guidelineDistance</code>	Distance in pixels between each guide dash.
<code>maxGuideLineLength</code>	Maximum length of the guide lines.
<code>showLength</code>	Whether to display the distance in the tooltip.
<code>metric</code>	Determines which measurement system (metric or imperial) is used.
<code>feet</code>	When not metric, use feet instead of yards for display.
<code>nautic</code>	When not metric, not feet, use nautic mile for display.
<code>zIndexOffset</code>	This should be a high number to ensure that you can draw over all other layers on the map.
<code>shapeOptions</code>	Leaflet Polyline options See drawShapeOptions() .

repeatMode	Determines if the draw tool remains enabled after drawing a shape.
showArea	Show the area of the drawn polygon in m ² , ha or km ² . The area is only approximate and become less accurate the larger the polygon is.
showRadius	Show the radius of the drawn circle in m, km, ft (feet), or nm (nautical mile).
markerIcon	Can be either makeIcon() OR makeAwesomeIcon
maintainColor	Whether to maintain shape's original color
edit	Editing enabled by default. Set to false do disable editing.
remove	Set to false to disable removing.
selectedPathOptions	To customize shapes in editing mode pass selectedPathOptions() .

enableMeasurePath *Enables measuring of length of polylines and areas of polygons*

Description

Enables measuring of length of polylines and areas of polygons

Options for measure-path

Adds a toolbar to enable/disable measuring path distances/areas

Usage

```
enableMeasurePath(map)
```

```
measurePathOptions(showOnHover = FALSE, minPixelDistance = 30,  
  showDistances = TRUE, showArea = TRUE, imperial = FALSE)
```

```
addMeasurePathToolbar(map, options = measurePathOptions())
```

Arguments

map	The map widget.
showOnHover	If TRUE, the measurements will only show when the user hovers the cursor over the path.
minPixelDistance	The minimum length a line segment in the feature must have for a measurement to be added.
showDistances	If FALSE, doesn't show distances along line segments of of a polyline/polygon.
showArea	If FALSE, doesn't show areas of a polyline/polygon.
imperial	If TRUE the distances/areas will be shown in imperial units.
options	The measurePathOptions.

Examples

```

geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/ward-2012.geojson"
)

leaflet() %>%
  addTiles() %>%
  setView(-77.0369, 38.9072, 11) %>%
  addBootstrapDependency() %>%
  enableMeasurePath() %>%
  addGeoJSONChoropleth(
    geoJson,
    valueProperty = "AREASQMI",
    scale = c("white", "red"),
    mode = "q",
    steps = 4,
    padding = c(0.2, 0),
    labelProperty = "NAME",
    popupProperty = propstoHTMLTable(
      props = c("NAME", "AREASQMI", "REP_NAME", "WEB_URL", "REP_PHONE", "REP_EMAIL", "REP_OFFICE"),
      table.attrs = list(class = "table table-striped table-bordered"),
      drop.na = TRUE
    ),
    color = "#ffffff", weight = 1, fillOpacity = 0.7,
    highlightOptions = highlightOptions(
      weight = 2, color = "#000000",
      fillOpacity = 1, opacity = 1,
      bringToFront = TRUE, sendToBack = TRUE),
    pathOptions = pathOptions(
      showMeasurements = TRUE,
      measurementOptions = measurePathOptions(imperial = TRUE))

```

enableTileCaching *Enables caching of Tiles*

Description

Enables caching of tiles locally in browser. See <https://github.com/MazeMap/Leaflet.TileLayer.PouchDBCached> for details. In addition to invoking this function, you should also pass useCache=TRUE & crossOrigin=TRUE in the `tileOptions` call and pass that to your `addTiles`'s options parameter.

Usage

```
enableTileCaching(map)
```

Arguments

map The leaflet map

Examples

```
leaflet() %>%
  enableTileCaching() %>%
  addTiles(options = tileOptions(useCache = TRUE, crossOrigin = TRUE))

## for more examples see
# browseURL(system.file("examples/TileLayer-Caching.R", package = "leaflet.extras"))
```

gpsOptions

Options for the GPS Control

Description

Options for the GPS Control

Add a gps to the Map.

Removes the GPS Control

Activate the GPS Control. You should have already added the GPS control before calling this method.

Deactivate the GPS Control. You should have already added the GPS control before calling this method.

Usage

```
gpsOptions(position = "topleft", activate = FALSE, autoCenter = FALSE,
  maxZoom = NULL, setView = FALSE)
```

```
addControlGPS(map, options = gpsOptions())
```

```
removeControlGPS(map)
```

```
activateGPS(map)
```

```
deactivateGPS(map)
```

Arguments

position	Position of the Control
activate	If TRUE activates the GPS on addition.
autoCenter	If TRUE auto centers the map when GPS location changes
maxZoom	If set zooms to this level when auto centering
setView	If TRUE sets the view to the GPS location when found
map	a map widget object
options	Options for the GPS control.

Examples

```
leaflet() %>%  
  addTiles() %>%  
  addControlGPS()
```

leaflet.extras	<i>leaflet.extras: Extra Functionality for 'leaflet' Package.</i>
----------------	---

Description

Description: The 'leaflet' JavaScript library provides many plugins some of which are available in the core 'leaflet' package, but there are many more. It is not possible to support them all in the core 'leaflet' package. This package serves as an add-on to the 'leaflet' package by providing extra functionality via 'leaflet' plugins.

leafletExtrasDependencies	<i>Various leaflet dependency functions for use in downstream packages</i>
---------------------------	--

Description

Various leaflet dependency functions for use in downstream packages

Usage

```
leafletExtrasDependencies
```

Format

An object of class `list` of length 5.

propsToHTML *Converts GeoJSON Feature properties to HTML*

Description

Converts GeoJSON Feature properties to HTML
 Converts GeoJSON Feature properties to HTML Table.
 Customize the leaflet widget style

Usage

```
propsToHTML(props, elem = NULL, elem.attrs = NULL)

propstoHTMLTable(props = NULL, table.attrs = NULL, drop.na = TRUE)

setMapWidgetStyle(map, style = list(background = "transparent"))
```

Arguments

props	A list of GeoJSON Property Keys.
elem	An optional wrapping element e.g. "div".
elem.attrs	An optional named list for the wrapper element properties.
table.attrs	An optional named list for the HTML Table.
drop.na	whether to skip properties with empty values.
map	the map widget
style	a A list of CSS key/value properties.

Examples

```
geoJson <- jsonlite::fromJSON(readr::read_file(
  paste0(
    "https://raw.githubusercontent.com/MinnPost/simple-map-d3",
    "/master/example-data/world-population.geo.json"
  )
))

world <- leaflet(
  options = leafletOptions(
    maxZoom = 5,
    crs = leafletCRS(
      crsClass = "L.Proj.CRS", code = "ESRI:53009",
      proj4def = "+proj=moll +lon_0=0 +x_0=0 +y_0=0 +a=6371000 +b=6371000 +units=m +no_defs",
      resolutions = c(65536, 32768, 16384, 8192, 4096, 2048))) %>%
  addGraticule(style = list(color = "#999", weight = 0.5, opacity = 1, fill = NA)) %>%
  addGraticule(sphere = TRUE, style = list(color = "#777", weight = 1, opacity = 0.25, fill = NA))
```

```

world

# change background to white
world %>%
  setMapWidgetStyle(list(background = "white"))

```

pulseIconList

Make pulse-icon set

Description

Make pulse-icon set

Make Pulse Icon

An icon can be represented as a list of the form `list(color, iconSize, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. NULL values for these arguments will be ignored.

Add Pulse Markers

Usage

```
pulseIconList(...)
```

```
## S3 method for class 'leaflet_pulse_icon_set'
x[i]
```

```
makePulseIcon(color = "#ff0000", iconSize = 12, animate = TRUE,
  heartbeat = 1)
```

```
pulseIcons(color = "#ff0000", iconSize = 12, animate = TRUE,
  heartbeat = 1)
```

```
addPulseMarkers(map, lng = NULL, lat = NULL, layerId = NULL,
  group = NULL, icon = NULL, popup = NULL, popupOptions = NULL,
  label = NULL, labelOptions = NULL, options = leaflet::markerOptions(),
  clusterOptions = NULL, clusterId = NULL,
  data = leaflet::getMapData(map))
```

Arguments

...	icons created from makePulseIcon()
x	icons
i	offset
color	Color of the icon
iconSize	Size of Icon in Pixels.

animate	To animate the icon or not, defaults to TRUE.
heartbeat	Interval between each pulse in seconds.
map	the map to add pulse Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named lng, long, or longitude (case-insensitively)
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and latitude are used when guessing the latitude column from data)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
icon	the icon(s) for markers;
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	options for popup
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Examples

```

iconSet = pulseIconList(
  red = makePulseIcon(color = "#ff0000"),
  blue = makePulseIcon(color = "#0000ff")
)

iconSet[c("red", "blue")]

leaflet() %>%
  addTiles() %>%
  addPulseMarkers(
    lng = -118.456554, lat = 34.078039,
    label = "This is a label",
    icon = makePulseIcon(heartbeat = 0.5)
  )

```

```

)

## for more examples see
# browseURL(system.file("examples/pluseIcon.R", package = "leaflet.extras"))

```

searchOptions *Options for search control.*

Description

Options for search control.
 Customized searchOptions for Feature Search

Usage

```

searchOptions(url = "", sourceData = NULL, jsonpParam = NULL,
  propertyLoc = "loc", propertyName = "title", formatData = NULL,
  filterData = NULL, moveToLocation = TRUE, zoom = 17, buildTip = NULL,
  container = "", minLength = 1, initial = TRUE, casesensitive = FALSE,
  autoType = TRUE, delayType = 400, tooltipLimit = -1,
  tipAutoSubmit = TRUE, firstTipSubmit = FALSE, autoResize = TRUE,
  collapsed = TRUE, autoCollapse = FALSE, autoCollapseTime = 1200,
  textErr = "Location Not Found", textCancel = "Cancel",
  textPlaceholder = "Search...", position = "topleft",
  hideMarkerOnCollapse = FALSE)

searchFeaturesOptions(propertyName = "label", initial = FALSE,
  openPopup = FALSE, ...)

```

Arguments

url	url for search by ajax request, ex: "search.php?q=s". Can be function that returns string for dynamic parameter setting.
sourceData	function that fill _recordsCache, passed searching text by first param and call-back in second.
jsonpParam	jsonp param name for search by jsonp service, ex: "callback".
propertyLoc	field for remapping location, using array: ["latname", "lonname"] for select double fields(ex. ["lat", "lon"]) support dotted format: "prop.subprop.title".
propertyName	property in marker.options(or feature.properties for vector layer) trough filter elements in layer,.
formatData	callback for reformat all data from source to indexed data object.
filterData	callback for filtering data from text searched, params: textSearch, allRecords.
moveToLocation	whether to move to the found location.
zoom	zoom to this level when moving to location

buildTip	function that return row tip html node(or html string), receive text tooltip in first param.
container	container id to insert Search Control.
minLength	minimal text length for autocomplete.
initial	search elements only by initial text.
casesensitive	search elements in case sensitive text.
autoType	complete input with first suggested result and select this filled-in text..
delayType	delay while typing for show tooltip.
tooltipLimit	limit max results to show in tooltip. -1 for no limit..
tipAutoSubmit	auto map panTo when click on tooltip.
firstTipSubmit	auto select first result con enter click.
autoResize	autoresize on input change.
collapsed	collapse search control at startup.
autoCollapse	collapse search control after submit(on button or on tips if enabled tipAutoSubmit).
autoCollapseTime	delay for autoclosing alert and collapse after blur.
textErr	'Location not error message.
textCancel	title in cancel button.
textPlaceholder	placeholder value.
position	"topleft".
hideMarkerOnCollapse	remove circle and marker on search control collapsed.
openPopup	whether to open the popup associated with the feature when the feature is searched for
...	Other options to pass to searchOptions() function.

suspendScroll	<i>Prevents accidental map scrolling when scrolling in a document.</i>
---------------	--

Description

Prevents accidental map scrolling when scrolling in a document.

Usage

```
suspendScroll(map, sleep = TRUE, sleepTime = 750, wakeTime = 750,
  sleepNote = TRUE, hoverToWake = TRUE,
  wakeMessage = "Click or Hover to Wake", sleepOpacity = 0.7)
```

Arguments

map	The leaflet map
sleep	false if you want an unruly map
sleepTime	time(ms) until map sleeps on mouseout
wakeTime	time(ms) until map wakes on mouseover
sleepNote	should the user receive wake instructions?
hoverToWake	should hovering wake the map? (non-touch devices only)
wakeMessage	a message to inform users about waking the map
sleepOpacity	opacity for the sleeping map

Examples

```
leaflet(width = "100%") %>%
  setView(0, 0, 1) %>%
  addTiles() %>%
  suspendScroll()
```

weatherIconList	<i>Make weather-icon set</i>
-----------------	------------------------------

Description

Make weather-icon set

Make Weather Icon

An icon can be represented as a list of the form `list(icon, markerColor, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. NULL values for these arguments will be ignored.

Add Weather Markers

Usage

```
weatherIconList(...)
```

```
## S3 method for class 'leaflet_weather_icon_set'
x[i]
```

```
makeWeatherIcon(icon, markerColor = "red", iconColor = "white",
  extraClasses = NULL)
```

```
weatherIcons(icon, markerColor = "red", iconColor = "white",
  extraClasses = NULL)
```

```
addWeatherMarkers(map, lng = NULL, lat = NULL, layerId = NULL,
  group = NULL, icon = NULL, popup = NULL, popupOptions = NULL,
```

```
label = NULL, labelOptions = NULL, options = leaflet::markerOptions(),
clusterOptions = NULL, clusterId = NULL,
data = leaflet::getMapData(map))
```

Arguments

...	icons created from <code>makeWeatherIcon()</code>
x	icons
i	offset
icon	the weather icon name w/o the "wi-" prefix. For a full list see https://erikflowers.github.io/weather-icons/
markerColor	color of the marker
iconColor	color of the weather icon
extraClasses	Character vector of extra classes.
map	the map to add weather Markers to.
lng	a numeric vector of longitudes, or a one-sided formula of the form <code>~x</code> where <code>x</code> is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)
popupOptions	options for popup
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Examples

```
iconSet = weatherIconList(  
  hurricane = makeWeatherIcon(icon = "hurricane"),  
  tornado = makeWeatherIcon(icon = "tornado")  
)  
  
iconSet[c("hurricane", "tornado")]  
leaflet() %>%  
  addTiles() %>%  
  addWeatherMarkers(  
    lng = -118.456554, lat = 34.078039,  
    label = "This is a label",  
    icon = makeWeatherIcon(  
      icon = "hot",  
      iconColor = "#ffffff77",  
      markerColor = "blue"  
    )  
  )  
)  
  
## for more examples see  
# browseURL(system.file("examples/weatherIcons.R", package = "leaflet.extras"))
```


Index

*Topic **datasets**

leafletExtrasDependencies, 32

[.leaflet_pulse_icon_set
(pulseIconList), 34

[.leaflet_weather_icon_set
(weatherIconList), 38

activateGPS (gpsOptions), 31

addAwesomeMarkersDependencies, 3

addBingTiles, 3

addBootstrapDependency, 4

addBounceMarkers, 4

addControlGPS (gpsOptions), 31

addCSV (addGeoJSONv2), 9

addCSVHeatmap (addHeatmap), 16

addDrawToolbar, 5, 21

addFullscreenControl, 6

addGeodesicPolylines, 7

addGeoJSON, 9

addGeoJSONChoropleth (addGeoJSONv2), 9

addGeoJSONHeatmap (addHeatmap), 16

addGeoJSONv2, 9

addGPX (addGeoJSONv2), 9

addGPXHeatmap (addHeatmap), 16

addGreatCircles (addGeodesicPolylines),
7

addHash, 15

addHeatmap, 16

addKML (addGeoJSONv2), 9

addKMLChoropleth (addGeoJSONv2), 9

addKMLHeatmap (addHeatmap), 16

addLayersControl, 17, 23, 35, 39

addMeasurePathToolbar
(enableMeasurePath), 29

addPulseMarkers (pulseIconList), 34

addResetMapButton, 18

addReverseSearchGoogle (addSearchOSM),
19

addReverseSearchOSM (addSearchOSM), 19

addSearchFeatures, 19

addSearchGoogle (addSearchOSM), 19

addSearchOSM, 19

addSearchUSCensusBureau (addSearchOSM),
19

addStyleEditor, 21

addTiles, 10, 30

addTopoJSON, 9

addWeatherMarkers (weatherIconList), 38

addWebGLCSVHeatmap (addWebGLHeatmap), 22

addWebGLGeoJSONHeatmap
(addWebGLHeatmap), 22

addWebGLGPXHeatmap (addWebGLHeatmap), 22

addWebGLHeatmap, 22

addWebGLKMLHeatmap (addWebGLHeatmap), 22

addWMSLegend, 25

clearGroup, 17, 23, 35, 39

clearHeatmap (addHeatmap), 16

clearWebGLHeatmap (addWebGLHeatmap), 22

colorNumeric, 17

csvParserOptions, 12, 17, 23

csvParserOptions (addGeoJSONv2), 9

deactivateGPS (gpsOptions), 31

debugMap, 26

drawCircleMarkerOptions, 6

drawCircleMarkerOptions
(drawShapeOptions), 27

drawCircleOptions, 5

drawCircleOptions (drawShapeOptions), 27

drawMarkerOptions, 5

drawMarkerOptions (drawShapeOptions), 27

drawPolygonOptions, 5

drawPolygonOptions (drawShapeOptions),
27

drawPolylineOptions, 5

drawPolylineOptions (drawShapeOptions),
27

drawRectangleOptions, 5

- drawRectangleOptions
 - (drawShapeOptions), 27
- drawShapeOptions, 27, 28
- editToolbarOptions, 6
- editToolbarOptions (drawShapeOptions), 27
- enableMeasurePath, 29
- enableTileCaching, 30
- gpsOptions, 31
- highlightOptions, 11
- htmlEscape, 8, 35, 39
- iconList, 11
- labelOptions, 8, 11, 35, 39
- leaflet.extras, 32
- leaflet.extras-package
 - (leaflet.extras), 32
- leaflet::leaflet, 4
- leafletExtrasDependencies, 32
- legendOptions (addGeoJSONv2), 9
- makeAwesomeIcon, 29
- makeIcon, 11, 29
- makePulseIcon, 34
- makePulseIcon (pulseIconList), 34
- makeWeatherIcon, 39
- makeWeatherIcon (weatherIconList), 38
- markerClusterOptions, 11, 35, 39
- measurePathOptions (enableMeasurePath), 29
- pathOptions, 8
- popupOptions, 8, 11
- propsToHTML, 33
- propstoHTMLTable (propsToHTML), 33
- pulseIconList, 34
- pulseIcons (pulseIconList), 34
- removeControlGPS (gpsOptions), 31
- removeDrawToolbar (addDrawToolbar), 5
- removeHeatmap (addHeatmap), 16
- removeSearchFeatures
 - (addSearchFeatures), 19
- removeSearchGoogle (addSearchOSM), 19
- removeSearchOSM (addSearchOSM), 19
- removeSearchUSCensusBureau
 - (addSearchOSM), 19
- removeStyleEditor (addStyleEditor), 21
- removeWebGLHeatmap (addWebGLHeatmap), 22
- searchFeaturesOptions (searchOptions), 36
- searchOptions, 36, 37
- selectedPathOptions, 29
- selectedPathOptions (drawShapeOptions), 27
- setMapWidgetStyle (propsToHTML), 33
- suspendScroll, 37
- tileOptions, 30
- weatherIconList, 38
- weatherIcons (weatherIconList), 38