Package 'openssl'

November 2, 2026

Type Package

Title Toolkit for Encryption, Signatures and Certificates Based on OpenSSL

Version 2.5.0

Description Bindings to OpenSSL libssl and libcrypto, plus custom SSH key parsers. Supports RSA, DSA and EC curves P-256, P-384, P-521, and curve25519. Cryptographic signatures can either be created and verified manually or via x509 certificates. AES can be used in cbc, ctr or gcm mode for symmetric encryption; RSA for asymmetric (public key) encryption or EC for Diffie Hellman. High-level envelope functions combine RSA and AES for encrypting arbitrary sized data. Other utilities include key generators, hash functions (md5, sha1, sha256, etc), base64 encoder, a secure random number generator, and 'bignum' math methods for manually performing crypto calculations on large multibyte integers.

License MIT + file LICENSE

URL https://jeroen.r-universe.dev/openssl

BugReports https://github.com/jeroen/openssl/issues

SystemRequirements OpenSSL >= 1.0.2

VignetteBuilder knitr

Imports askpass

Suggests curl, testthat (>= 2.1.0), digest, knitr, rmarkdown, jsonlite, jose, sodium

Encoding UTF-8

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Jeroen Ooms [aut, cre] (ORCID: <https://orcid.org/0000-0002-4035-0289>), Oliver Keyes [ctb]

Maintainer Jeroen Ooms <jeroenooms@gmail.com>

Repository CRAN

Date/Publication 2026-11-02 17:20:02 UTC

Contents

aes_cbc . . . 2
base64_encode . . . 3
bcrypt_pbkdf . . . 4
bignum . . . 4
cert_verify . . . 5
curve25519 . . . 6
ec_dh . . . 7
encrypt_envelope . . . 8
fingerprint . . . 9
hashing . . . 10
keygen . . . 12
my_key . . . 13
openssl . . . 14
openssl_config . . . 14
pkcs7_encrypt . . . 15
rand_bytes . . . 15
read_key . . . 16
rsa_encrypt . . . 18
signature_create . . . 19
ssl_ctx . . . 20
write_p12 . . . 22
write_pem . . . 23

Index **25**

`aes_cbc` *Symmetric AES encryption*

Description

Low-level symmetric encryption/decryption using the AES block cipher in CBC mode. The key is a raw vector, for example a hash of some secret. When no shared secret is available, a random key can be used which is exchanged via an asymmetric protocol such as RSA. See `rsa_encrypt()` for a worked example or `encrypt_envelope()` for a high-level wrapper combining AES and RSA.

Usage

```
aes_ctr_encrypt(data, key, iv = rand_bytes(16))

aes_ctr_decrypt(data, key, iv = attr(data, "iv"))

aes_cbc_encrypt(data, key, iv = rand_bytes(16))

aes_cbc_decrypt(data, key, iv = attr(data, "iv"))

aes_gcm_encrypt(data, key, iv = rand_bytes(12))
```

```
aes_gcm_decrypt(data, key, iv = attr(data, "iv"))

aes_keygen(length = 16)
```

Arguments

data	raw vector or path to file with data to encrypt or decrypt
key	raw vector of length 16, 24 or 32, e.g. the hash of a shared secret
iv	raw vector of length 16 (aes block size) or NULL. The initialization vector is not secret but should be random
length	how many bytes to generate. Usually 16 (128-bit) or 12 (92-bit) for aes_gcm

Examples

```
# aes-256 requires 32 byte key
passphrase <- charToRaw("This is super secret")
key <- sha256(passphrase)

# symmetric encryption uses same key for decryption
x <- serialize(iris, NULL)
y <- aes_cbc_encrypt(x, key = key)
x2 <- aes_cbc_decrypt(y, key = key)
stopifnot(identical(x, x2))
```

---

base64_encode *Encode and decode base64*

Description

Encode and decode binary data into a base64 string. Character vectors are automatically collapsed into a single string.

Usage

```
base64_encode(bin, linebreaks = FALSE)

base64_decode(text)
```

Arguments

bin	raw or character vector with data to encode into base64
linebreaks	insert linebreaks in the base64 message to make it more readable
text	string with base64 data to decode

Examples

```
input <- charToRaw("foo = bar + 5")
message <- base64_encode(input)
output <- base64_decode(message)
identical(output, input)
```

`bcrypt_pbkdf` *Bcrypt PWKDF*

Description

Password based key derivation function with bcrypt. This is not part of openssl. It is needed to parse private key files which are encoded in the new openssh format.

Usage

```
bcrypt_pbkdf(password, salt, rounds = 16L, size = 32L)
```

Arguments

`password`	string or raw vector with password
`salt`	raw vector with (usually 16) bytes
`rounds`	number of hashing rounds
`size`	desired length of the output key

`bignum` *Big number arithmetic*

Description

Basic operations for working with large integers. The `bignum` function converts a positive integer, string or raw vector into a bignum type. All basic Arithmetic and Comparison operators such as `+`, `-`, `*`, `^`, `%%`, `%/%`, `==`, `!=`, `<`, `<=`, `>` and `>=` are implemented for bignum objects. The Modular exponent (`a^b %% m`) can be calculated using `bignum_mod_exp()` when `b` is too large for calculating `a^b` directly.

Usage

```
bignum(x, hex = FALSE)

bignum_mod_exp(a, b, m)

bignum_mod_inv(a, m)
```

Arguments

x	an integer, string (hex or dec) or raw vector
hex	set to TRUE to parse strings as hex rather than decimal notation
a	bignum value for (a^b %% m)
b	bignum value for (a^b %% m)
m	bignum value for (a^b %% m)

Examples

```
# create a bignum
x <- bignum(123L)
y <- bignum("123456789123456789")
z <- bignum("D41D8CD98F00B204E9800998ECF8427E", hex = TRUE)

# Basic arithmetic
div <- z %/% y
mod <- z %% y
z2 <- div * y + mod
stopifnot(z2 == z)
stopifnot(div < z)
```

---

cert_verify *X509 certificates*

Description

Read, download, analyze and verify X.509 certificates.

Usage

```
cert_verify(cert, root = ca_bundle())

download_ssl_cert(host = "localhost", port = 443, ipv4_only = FALSE)

ca_bundle()
```

Arguments

cert	certificate (or certificate-chain) to be verified. Must be cert or list or path.
root	trusted pubkey or certificate(s) e.g. CA bundle.
host	string: hostname of the server to connect to
port	string or integer: port or protocol to use, e.g: 443 or "https"
ipv4_only	do not use IPv6 connections

Details

The `ca_bundle()` function first looks for the default CA bundle of the system libssl, which may be overridden with the `SSL_CERT_FILE` environment variable. If no system bundle is found, it falls back on the Mozilla CA bundle that was downloaded from https://curl.se/ca/cacert.pem when the package was installed.

See Also

read_cert

Examples

```
# Verify the r-project HTTPS cert
chain <- download_ssl_cert("cran.r-project.org", 443)
print(chain)
cert_data <- as.list(chain[[1]])
print(cert_data$pubkey)
print(cert_data$alt_names)
cert_verify(chain, ca_bundle())

# Write cert in PEM format
cat(write_pem(chain[[1]]))
```

---

curve25519 *Curve25519*

Description

Curve25519 is a recently added low-level algorithm that can be used both for diffie-hellman (called X25519) and for signatures (called ED25519). Note that these functions are only available when building against version 1.1.1 or newer of the openssl library. The same functions are also available in the sodium R package.

Usage

```
read_ed25519_key(x)

read_ed25519_pubkey(x)

read_x25519_key(x)

read_x25519_pubkey(x)

ed25519_sign(data, key)

ed25519_verify(data, sig, pubkey)

x25519_diffie_hellman(key, pubkey)
```

Arguments

x	a 32 byte raw vector with (pub)key data
data	raw vector with data to sign or verify
key	private key as returned by read_ed25519_key or ed25519_keygen
sig	raw vector of length 64 with signature as returned by ed25519_sign
pubkey	public key as returned by read_ed25519_pubkey or key$pubkey

Examples

```
# Generate a keypair
if(openssl_config()$x25519){
key <- ed25519_keygen()
pubkey <- as.list(key)$pubkey

# Sign message
msg <- serialize(iris, NULL)
sig <- ed25519_sign(msg, key)

# Verify the signature
ed25519_verify(msg, sig, pubkey)

# Diffie Hellman example:
key1 <- x25519_keygen()
key2 <- x25519_keygen()

# Both parties can derive the same secret
x25519_diffie_hellman(key1, key2$pubkey)
x25519_diffie_hellman(key2, key1$pubkey)

# Import/export sodium keys
rawkey <- sodium::sig_keygen()
rawpubkey <- sodium::sig_pubkey(rawkey)
key <- read_ed25519_key(rawkey)
pubkey <- read_ed25519_pubkey(rawpubkey)

# To get the raw key data back for use in sodium
as.list(key)$data
as.list(pubkey)$data
}
```

---

ec_dh *Diffie-Hellman Key Agreement*

Description

Key agreement is one-step method of creating a shared secret between two peers. Both peers can independently derive the joined secret by combining his or her private key with the public key from the peer.

Usage

```
ec_dh(key = my_key(), peerkey, password = askpass)
```

Arguments

key	your own private key
peerkey	the public key from your peer
password	passed to read_key for reading protected private keys

Details

Currently only Elliptic Curve Diffie Hellman (ECDH) is implemented.

References

https://wiki.openssl.org/index.php/EVP_Key_Agreement, https://wiki.openssl.org/index.php/Elliptic_Curve_Diffie_Hellman

Examples

```
## Not run:
# Need two EC keypairs from the same curve
alice_key <- ec_keygen("P-521")
bob_key <- ec_keygen("P-521")

# Derive public keys
alice_pub <- as.list(alice_key)$pubkey
bob_pub <- as.list(bob_key)$pubkey

# Both peers can derive the (same) shared secret via each other's pubkey
ec_dh(alice_key, bob_pub)
ec_dh(bob_key, alice_pub)

## End(Not run)
```

---

encrypt_envelope *Envelope encryption*

Description

An envelope contains ciphertext along with an encrypted session key and optionally and initialization vector. The `encrypt_envelope()` generates a random IV and session-key which is used to encrypt the `data` with `AES()` stream cipher. The session key itself is encrypted using the given RSA key (see `rsa_encrypt()`) and stored or sent along with the encrypted data. Each of these outputs is required to decrypt the data with the corresponding private key.

Usage

```
encrypt_envelope(data, pubkey = my_pubkey())

decrypt_envelope(data, iv, session, key = my_key(), password)
```

Arguments

data	raw data vector or file path for message to be signed. If hash == NULL then data must be a hash string or raw vector.
pubkey	public key or file path. See read_pubkey().
iv	16 byte raw vector returned by encrypt_envelope.
session	raw vector with encrypted session key as returned by encrypt_envelope.
key	private key or file path. See read_key().
password	string or a function to read protected keys. See read_key().

References

https://wiki.openssl.org/index.php/EVP_Asymmetric_Encryption_and_Decryption_of_an_Envelope

Examples

```
# Requires RSA key
key <- rsa_keygen()
pubkey <- key$pubkey
msg <- serialize(iris, NULL)

# Encrypt
out <- encrypt_envelope(msg, pubkey)
str(out)

# Decrypt
orig <- decrypt_envelope(out$data, out$iv, out$session, key)
stopifnot(identical(msg, orig))
```

---

fingerprint *OpenSSH fingerprint*

Description

Calculates the OpenSSH fingerprint of a public key. This value should match what you get to see when connecting with SSH to a server. Note that some other systems might use a different algorithm to derive a (different) fingerprint for the same keypair.

Usage

```
fingerprint(key, hashfun = sha256)
```

Arguments

key	a public or private key
hashfun	which hash function to use to calculate the fingerprint

Examples

```
mykey <- rsa_keygen()
pubkey <- as.list(mykey)$pubkey
fingerprint(mykey)
fingerprint(pubkey)

# Some systems use other hash functions
fingerprint(pubkey, sha1)
fingerprint(pubkey, sha256)

# Other key types
fingerprint(dsa_keygen())
```

---

hashing *Vectorized hash/hmac functions*

Description

All hash functions either calculate a hash-digest for key == NULL or HMAC (hashed message authentication code) when key is not NULL. Supported inputs are binary (raw vector), strings (character vector) or a connection object.

Usage

```
sha1(x, key = NULL)

sha224(x, key = NULL)

sha256(x, key = NULL)

sha384(x, key = NULL)

sha512(x, key = NULL)

keccak(x, size = 256, key = NULL)

sha2(x, size = 256, key = NULL)

sha3(x, size = 256, key = NULL)

md4(x, key = NULL)
```

```
md5(x, key = NULL)

blake2b(x, key = NULL)

blake2s(x, key = NULL)

ripemd160(x, key = NULL)

multihash(x, algos = c("md5", "sha1", "sha256", "sha384", "sha512"))
```

Arguments

x	character vector, raw vector or connection object.
key	string or raw vector used as the key for HMAC hashing
size	must be equal to 224 256 384 or 512
algos	string vector with names of hashing algorithms

Details

The most efficient way to calculate hashes is by using input connections, such as a file() or url() object. In this case the hash is calculated streamingly, using almost no memory or disk space, regardless of the data size. When using a connection input in the multihash function, the data is only read only once while streaming to multiple hash functions simultaneously. Therefore several hashes are calculated simultanously, without the need to store any data or download it multiple times.

Functions are vectorized for the case of character vectors: a vector with n strings returns n hashes. When passing a connection object, the contents will be stream-hashed which minimizes the amount of required memory. This is recommended for hashing files from disk or network.

The sha2 family of algorithms (sha224, sha256, sha384 and sha512) is generally recommended for sensitive information. While sha1 and md5 are usually sufficient for collision-resistant identifiers, they are no longer considered secure for cryptographic purposes.

In applications where hashes should be irreversible (such as names or passwords) it is often recommended to use a random *key* for HMAC hashing. This prevents attacks where we can lookup hashes of common and/or short strings. See examples. A common special case is adding a random salt to a large number of records to test for uniqueness within the dataset, while simultaneously rendering the results incomparable to other datasets.

The blake2b and blake2s algorithms are only available if your system has libssl 1.1 or newer.

NB R base file() function has a poor default raw = FALSE which causes files to get altereted (e.g. decompressed) when reading. Use file(path, raw = TRUE) to get the hash of the file as it exists on your disk.

References

Digest types: https://docs.openssl.org/1.1.1/man1/dgst/

Examples

```
# Support both strings and binary
md5(c("foo", "bar"))
md5("foo", key = "secret")

hash <- md5(charToRaw("foo"))
as.character(hash, sep = ":")

# Compare to digest
digest::digest("foo", "md5", serialize = FALSE)

# Other way around
digest::digest(cars, skip = 0)
md5(serialize(cars, NULL))

# Stream-verify from connections (including files)
myfile <- system.file("CITATION")
md5(file(myfile, raw = TRUE))
md5(file(myfile, raw = TRUE), key = "secret")

## Not run: check md5 from: http://cran.r-project.org/bin/windows/base/old/3.1.1/md5sum.txt
md5(url("http://cran.r-project.org/bin/windows/base/old/3.1.1/R-3.1.1-win.exe"))
## End(Not run)

# Use a salt to prevent dictionary attacks
sha1("admin") # googleable
sha1("admin", key = "random_salt_value") #not googleable

# Use a random salt to identify duplicates while anonymizing values
sha256("john") # googleable
sha256(c("john", "mary", "john"), key = "random_salt_value")
```

---

keygen *Generate Key pair*

Description

The keygen functions generate a random private key. Use `as.list(key)$pubkey` to derive the corresponding public key. Use write_pem to save a private key to a file, optionally with a password.

Usage

```
rsa_keygen(bits = 2048)

dsa_keygen(bits = 1024)

ec_keygen(curve = c("P-256", "P-384", "P-521"))

x25519_keygen()
```

```
ed25519_keygen()
```

Arguments

bits	bitsize of the generated RSA/DSA key
curve	which NIST curve to use

Examples

```
# Generate keypair
key <- rsa_keygen()
pubkey <- as.list(key)$pubkey

# Write/read the key with a passphrase
write_pem(key, "id_rsa", password = "supersecret")
read_key("id_rsa", password = "supersecret")
unlink("id_rsa")
```

---

my_key *Default key*

Description

The default user key can be set in the USER_KEY variable and otherwise is ~/.ssh/id_rsa. Note that on Windows we treat ~ as the windows user home (and not the documents folder).

Usage

```
my_key()

my_pubkey()
```

Details

The my_pubkey() function looks for the public key by appending .pub to the above key path. If this file does not exist, it reads the private key file and automatically derives the corresponding pubkey. In the latter case the user may be prompted for a passphrase if the private key is protected.

Examples

```
# Set random RSA key as default
key <- rsa_keygen()
write_pem(key, tmp <- tempfile(), password = "")
rm(key)
Sys.setenv("USER_KEY" = tmp)

# Check the new keys
print(my_key())
print(my_pubkey())
```

openssl *Toolkit for Encryption, Signatures and Certificates based on OpenSSL*

Description

Bindings to OpenSSL libssl and libcrypto, plus custom SSH pubkey parsers. Supports RSA, DSA and NIST curves P-256, P-384 and P-521. Cryptographic signatures can either be created and verified manually or via x509 certificates. The AES block cipher is used in CBC mode for symmetric encryption; RSA for asymmetric (public key) encryption. High-level envelope methods combine RSA and AES for encrypting arbitrary sized data. Other utilities include key generators, hash functions (`md5()`, `sha1()`, `sha256()`, etc), `base64()` encoder, a secure random number generator, and `bignum()` math methods for manually performing crypto calculations on large multibyte integers.

Author(s)

Jeroen Ooms, Oliver Keyes

See Also

Useful links:

- https://jeroen.r-universe.dev/openssl
- Report bugs at https://github.com/jeroen/openssl/issues

openssl_config *OpenSSL Configuration Info*

Description

Shows libssl version and configuration information.

Usage

```
openssl_config()

fips_mode()
```

Details

Note that the "fips" flag in `openssl_config` means that FIPS is supported, but it does not mean that it is currently enforced. If supported, it can be enabled in several ways, such as a kernel option, or setting an environment variable `OPENSSL_FORCE_FIPS_MODE=1`. The `fips_mode()` function shows if FIPS is currently enforced.

pkcs7_encrypt *Encrypt/decrypt pkcs7 messages*

Description

Encrypt or decrypt messages using PKCS7 smime format. Note PKCS7 only supports RSA keys.

Usage

```
pkcs7_encrypt(message, cert, pem = TRUE)

pkcs7_decrypt(input, key, der = is.raw(input))
```

Arguments

message	text or raw vector with data to encrypt
cert	the certificate with public key to use for encryption
pem	convert output pkcs7 data to PEM format
input	file path or string with PEM or raw vector with p7b data
key	private key to decrypt data
der	assume input is in DER format (rather than PEM)

See Also

encrypt_envelope

rand_bytes *Generate random bytes and numbers with OpenSSL*

Description

this set of functions generates random bytes or numbers from OpenSSL. This provides a cryptographically secure alternative to R's default random number generator. `rand_bytes` generates `n` random cryptographically secure bytes

Usage

```
rand_bytes(n = 1)

rand_num(n = 1)
```

Arguments

n	number of random bytes or numbers to generate

References

OpenSSL manual: https://docs.openssl.org/1.1.1/man3/RAND_bytes/

Examples

```
rnd <- rand_bytes(10)
as.numeric(rnd)
as.character(rnd)
as.logical(rawToBits(rnd))

# bytes range from 0 to 255
rnd <- rand_bytes(100000)
hist(as.numeric(rnd), breaks=-1:255)

# Generate random doubles between 0 and 1
rand_num(5)

# Use CDF to map [0,1] into random draws from a distribution
x <- qnorm(rand_num(1000), mean=100, sd=15)
hist(x)

y <- qbinom(rand_num(1000), size=10, prob=0.3)
hist(y)
```

---

read_key *Parsing keys and certificates*

Description

The read_key function (private keys) and read_pubkey (public keys) support both SSH pubkey format and OpenSSL PEM format (base64 data with a --BEGIN and ---END header), and automatically convert where necessary. The functions assume a single key per file except for read_cert_bundle which supports PEM files with multiple certificates.

Usage

```
read_key(file, password = askpass, der = is.raw(file))

read_pubkey(file, der = is.raw(file))

read_cert(file, der = is.raw(file))

read_cert_bundle(file)

read_pem(file)
```

Arguments

file	Either a path to a file, a connection, or literal data (a string for pem/ssh format, or a raw vector in der format)
password	A string or callback function to read protected keys
der	set to TRUE if file is in binary DER format

Details

Most versions of OpenSSL support at least RSA, DSA and ECDSA keys. Certificates must conform to the X509 standard.

The password argument is needed when reading keys that are protected with a passphrase. It can either be a string containing the passphrase, or a custom callback function that will be called by OpenSSL to read the passphrase. The function should take one argument (a string with a message) and return a string. The default is to use readline which will prompt the user in an interactive R session.

Value

An object of class cert, key or pubkey which holds the data in binary DER format and can be decomposed using as.list.

See Also

download_ssl_cert

Examples

```
## Not run: # Read private key
key <- read_key("~/.ssh/id_rsa")
str(key)

# Read public key
pubkey <- read_pubkey("~/.ssh/id_rsa.pub")
str(pubkey)

# Read certificates
txt <- readLines("https://curl.se/ca/cacert.pem")
bundle <- read_cert_bundle(txt)
print(bundle)

## End(Not run)
```

rsa_encrypt *Low-level RSA encryption*

Description

Asymmetric encryption and decryption with RSA. Because RSA can only encrypt messages smaller than the size of the key, it is typically used only for exchanging a random session-key. This session key is used to encipher arbitrary sized data via a stream cipher such as aes_cbc. See encrypt_envelope or pkcs7_encrypt for a high-level wrappers combining RSA and AES in this way.

Usage

```
rsa_encrypt(data, pubkey = my_pubkey(), oaep = FALSE)

rsa_decrypt(data, key = my_key(), password = askpass, oaep = FALSE)

rsa_sign(hash, key = my_key(), password = askpass)
```

Arguments

data	raw vector of max 245 bytes (for 2048 bit keys) with data to encrypt/decrypt
pubkey	public key or file path. See read_pubkey().
oaep	if TRUE, changes padding to EME-OAEP as defined in PKCS #1 v2.0
key	private key or file path. See read_key().
password	string or a function to read protected keys. See read_key().
hash	raw vector of length 16, 20, or 32 (md5/sha1/sha256)

Details

Note that rsa_sign is a legacy function that does not enforce FIPS-mode. It is safer to the more general signature_create, unless you specifically want to bypass FIPS.

Examples

```
# Generate test keys
key <- rsa_keygen()
pubkey <- key$pubkey

# Encrypt data with AES
tempkey <- rand_bytes(32)
iv <- rand_bytes(16)
blob <- aes_cbc_encrypt(system.file("CITATION"), tempkey, iv = iv)

# Encrypt tempkey using receivers public RSA key
ciphertext <- rsa_encrypt(tempkey, pubkey)

# Receiver decrypts tempkey from private RSA key
```

```
tempkey <- rsa_decrypt(ciphertext, key)
message <- aes_cbc_decrypt(blob, tempkey, iv)
out <- rawToChar(message)
```

---

signature_create *Signatures*

Description

Sign and verify a message digest. RSA supports both MD5 and SHA signatures whereas DSA and EC keys only support SHA. ED25591 can sign any payload so you can set hash to NULL to sign the raw input data.

Usage

```
signature_create(data, hash = sha1, key = my_key(), password = askpass)

signature_verify(data, sig, hash = sha1, pubkey = my_pubkey())

ecdsa_parse(sig)

ecdsa_write(r, s)
```

Arguments

data	raw data vector or file path for message to be signed. If hash == NULL then data must be a hash string or raw vector.
hash	the digest function to use. Must be one of md5(), sha1(), sha256(), sha512() or NULL.
key	private key or file path. See read_key().
password	string or a function to read protected keys. See read_key().
sig	raw vector or file path for the signature data.
pubkey	public key or file path. See read_pubkey().
r	bignum value for r parameter
s	bignum value for s parameter

Details

The ecdsa_parse and ecdsa_write functions convert (EC)DSA signatures between the conventional DER format and the raw (r,s) bignum pair. Most users won't need this, it is mostly here to support the JWT format (which does not use DER).

Examples

```
# Generate a keypair
key <- rsa_keygen()
pubkey <- key$pubkey

# Sign a file
data <- system.file("DESCRIPTION")
sig <- signature_create(data, sha256, key = key)
stopifnot(signature_verify(data, sig, sha256, pubkey = pubkey))

# Sign raw data
data <- serialize(iris, NULL)
sig <- signature_create(data, sha256, key = key)
stopifnot(signature_verify(data, sig, sha256, pubkey = pubkey))

# Sign a hash
md <- md5(data)
sig <- signature_create(md, hash = sha256, key = key)
stopifnot(signature_verify(md, sig, hash = sha256, pubkey = pubkey))
#
# ECDSA example
data <- serialize(iris, NULL)
key <- ec_keygen()
pubkey <- key$pubkey
sig <- signature_create(data, sha256, key = key)
stopifnot(signature_verify(data, sig, sha256, pubkey = pubkey))

# Convert signature to (r, s) parameters and then back
params <- ecdsa_parse(sig)
out <- ecdsa_write(params$r, params$s)
identical(sig, out)
```

---

ssl_ctx *Hooks to manipulate the SSL context for curl requests*

Description

These functions allow for manipulating the SSL context from inside the CURLOPT_SSL_CTX_FUNCTION callback using the curl R package. Note that this is not fully portable and will only work on installations that use matching versions of libssl (see details). It is recommended to only use this locally and if what you need cannot be accomplished using standard libcurl TLS options, e.g. those listed in `curl::curl_options('ssl')` or `curl::curl_options('tls')`.

Usage

```
ssl_ctx_add_cert_to_store(ssl_ctx, cert)

ssl_ctx_set_verify_callback(ssl_ctx, cb)

ssl_ctx_curl_version_match()
```

Arguments

ssl_ctx	pointer object to the SSL context provided in the ssl_ctx_function callback.
cert	certificate object, e.g from read_cert or download_ssl_cert.
cb	callback function with 1 parameter (the server certificate) and which returns TRUE (for proceed) or FALSE (for abort).

Details

Curl allows for setting an option called ssl_ctx_function: this is a callback function that is triggered during the TLS initiation, before any https connection has been made. This serves as a hook to let you manipulate the TLS configuration (called SSL_CTX for historical reasons), in order to control how to curl will validate the authenticity of server certificates for upcoming TLS connections.

Currently we provide 2 such functions: ssl_ctx_add_cert_to_store injects a custom certificate into the trust-store of the current TLS connection. But most flexibility is provided via ssl_ctx_set_verify_callback which allows you to override the function that is used by validate if a server certificate should be trusted. The callback will receive one argument cert and has to return TRUE or FALSE to decide if the cert should be trusted.

By default libcurl re-uses connections, hence the cert validation is only performed in the first request to a given host. Subsequent requests use the already established TLS connection. For testing, it can be useful to set forbid_reuse in order to make a new connection for each request, as done in the examples below.

System compatibility

Passing the SSL_CTX between the curl and openssl R packages only works if they are linked to the same version of libssl. Use ssl_ctx_curl_version_match to test if this is the case. On Debian / Ubuntu you need to build the R curl package against libcurl4-openssl-dev, which is usually the case. On Windows you would need to set CURL_SSL_BACKEND=openssl in your ~/.Renviron file. On MacOS things are complicated because it uses LibreSSL instead of OpenSSL by default. You can make it work by compiling the curl R package from source against the homebrew version of curl and then then set CURL_SSL_BACKEND=openssl in your ~/.Renviron file. If your curl and openssl R packages use different versions of libssl, the examples may segfault due to ABI incompatibility of the SSL_CTX structure.

Examples

```
## Not run:
# Example 1: accept your local snakeoil https cert
mycert <- openssl::download_ssl_cert('localhost')[[1]]

# Setup the callback
h <- curl::new_handle(ssl_ctx_function = function(ssl_ctx){
  ssl_ctx_add_cert_to_store(ssl_ctx, mycert)
}, verbose = TRUE, forbid_reuse = TRUE)

# Perform the request
req <- curl::curl_fetch_memory('https://localhost', handle = h)
```

```
# Example 2 using a custom verify function
verify_cb <- function(cert){
  id <- cert$pubkey$fingerprint
  cat("Server cert from:", as.character(id), "\n")
  TRUE # always accept cert
}

h <- curl::new_handle(ssl_ctx_function = function(ssl_ctx){
  ssl_ctx_set_verify_callback(ssl_ctx, verify_cb)
}, verbose = TRUE, forbid_reuse = TRUE)

# Perform the request
req <- curl::curl_fetch_memory('https://localhost', handle = h)

## End(Not run)
```

`write_p12` *PKCS7 / PKCS12 bundles*

Description

PKCS7 and PKCS12 are container formats for storing multiple certificates and/or keys.

Usage

```
write_p12(
  key = NULL,
  cert = NULL,
  ca = NULL,
  name = NULL,
  password = NULL,
  path = NULL
)

write_p7b(ca, path = NULL)

read_p12(file, password = askpass)

read_p7b(file, der = is.raw(file))
```

Arguments

`key`	a private key
`cert`	certificate that matches `key`
`ca`	a list of certificates (the CA chain)
`name`	a friendly title for the bundle

password	string or function to set/get the password.
path	a file where to write the output to. If NULL the output is returned as a raw vector.
file	path or raw vector with binary PKCS12 data to parse
der	set to TRUE for binary files and FALSE for PEM files

Details

The PKCS#7 or P7B format is a container for one or more certificates. It can either be stored in binary form or in a PEM file. P7B files are typically used to import and export public certificates.

The PKCS#12 or PFX format is a binary-only format for storing the server certificate, any intermediate certificates, and the private key into a single encryptable file. PFX files are usually found with the extensions .pfx and .p12. PFX files are typically used to import and export certificates with their private keys.

The PKCS formats also allow for including signatures and CRLs but this is quite rare and these are currently ignored.

---

write_pem *Export key or certificate*

Description

The write_pem functions exports a key or certificate to the standard base64 PEM format. For private keys it is possible to set a password.

Usage

```
write_pem(x, path = NULL, password = NULL)

write_der(x, path = NULL)

write_pkcs1(x, path = NULL, password = NULL)

write_ssh(pubkey, path = NULL)

write_openssh_pem(key, path = NULL)
```

Arguments

x	a public/private key or certificate object
path	file to write to. If NULL it returns the output as a string.
password	string or callback function to set password (only applicable for private keys).
pubkey	a public key
key	a private key

Details

The pkcs1 format is the old legacy format used by OpenSSH. PKCS1 does not support the new ed25519 keys, for which you need `write_openssh_pem`. For non-ssh clients, we recommend to simply use `write_pem` to export keys and certs into the recommended formats.

Examples

```
# Generate RSA keypair
key <- rsa_keygen()
pubkey <- key$pubkey

# Write to output formats
write_ssh(pubkey)
write_pem(pubkey)
write_pem(key, password = "super secret")
```

Index

AES block cipher, *14*
AES(), *8*
aes_cbc, 2, *18*
aes_cbc_decrypt *(*aes_cbc*)*, 2
aes_cbc_encrypt *(*aes_cbc*)*, 2
aes_ctr_decrypt *(*aes_cbc*)*, 2
aes_ctr_encrypt *(*aes_cbc*)*, 2
aes_gcm_decrypt *(*aes_cbc*)*, 2
aes_gcm_encrypt *(*aes_cbc*)*, 2
aes_keygen *(*aes_cbc*)*, 2
Arithmetic, *4*
asymmetric (public key), *14*

base64(), *14*
base64_decode *(*base64_encode*)*, 3
base64_encode, 3
bcrypt_pbkdf, 4
bignum, 4
bignum(), *14*
bignum_mod_exp *(*bignum*)*, 4
bignum_mod_exp(), *4*
bignum_mod_inv *(*bignum*)*, 4
blake2b *(*hashing*)*, 10
blake2s *(*hashing*)*, 10

ca_bundle *(*cert_verify*)*, 5
cert_verify, 5
certificates, *14*
certificates *(*cert_verify*)*, 5
Comparison, *4*
connections, *11*
curve25519, 6

decrypt_envelope *(*encrypt_envelope*)*, 8
download_ssl_cert, *17*, *21*
download_ssl_cert *(*cert_verify*)*, 5
dsa_keygen *(*keygen*)*, 12

ec_dh, 7
ec_keygen *(*keygen*)*, 12
ecdsa_parse *(*signature_create*)*, 19
ecdsa_write *(*signature_create*)*, 19
ed25519_keygen *(*keygen*)*, 12
ed25519_sign *(*curve25519*)*, 6
ed25519_verify *(*curve25519*)*, 6
encrypt *(*rsa_encrypt*)*, 18
encrypt_envelope, 8, *15*, *18*
encrypt_envelope(), *2*, *8*
envelope, *14*
envelope *(*encrypt_envelope*)*, 8

file(), *11*
fingerprint, 9
fips_mode *(*openssl_config*)*, 14

hash *(*hashing*)*, 10
hashing, 10
hmac *(*hashing*)*, 10

keccak *(*hashing*)*, 10
key generators, *14*
keygen, 12

mac *(*hashing*)*, 10
md4 *(*hashing*)*, 10
md5 *(*hashing*)*, 10
md5(), *14*, *19*
multihash, *11*
multihash *(*hashing*)*, 10
my_key, 13
my_pubkey *(*my_key*)*, 13

openssl, 14
openssl-package *(*openssl*)*, 14
openssl_config, 14
option, *21*

pfx *(*write_p12*)*, 22
pkcs12 *(*write_p12*)*, 22
pkcs7_decrypt *(*pkcs7_encrypt*)*, 15
pkcs7_encrypt, 15, *18*

pubkey, *14*

rand_bytes, 15
rand_num *(*rand_bytes*)*, 15
random number generator, *14*
read_cert, *6*, *21*
read_cert *(*read_key*)*, 16
read_cert_bundle *(*read_key*)*, 16
read_ed25519_key *(*curve25519*)*, 6
read_ed25519_pubkey *(*curve25519*)*, 6
read_key, *8*, 16
read_key(), *9*, *18, 19*
read_p12 *(*write_p12*)*, 22
read_p7b *(*write_p12*)*, 22
read_pem *(*read_key*)*, 16
read_pubkey *(*read_key*)*, 16
read_pubkey(), *9*, *18, 19*
read_x25519_key *(*curve25519*)*, 6
read_x25519_pubkey *(*curve25519*)*, 6
ripemd160 *(*hashing*)*, 10
rsa *(*rsa_encrypt*)*, 18
rsa_decrypt *(*rsa_encrypt*)*, 18
rsa_encrypt, 18
rsa_encrypt(), *2*, *8*
rsa_keygen *(*keygen*)*, 12
rsa_sign, *18*
rsa_sign *(*rsa_encrypt*)*, 18

sha1 *(*hashing*)*, 10
sha1(), *14*, *19*
sha2 *(*hashing*)*, 10
sha224 *(*hashing*)*, 10
sha256 *(*hashing*)*, 10
sha256(), *14*, *19*
sha3 *(*hashing*)*, 10
sha384 *(*hashing*)*, 10
sha512 *(*hashing*)*, 10
sha512(), *19*
signature_create, *18*, 19
signature_verify *(*signature_create*)*, 19
signatures, *14*
signatures *(*signature_create*)*, 19
ssl_ctx, 20
ssl_ctx_add_cert_to_store, *21*
ssl_ctx_add_cert_to_store *(*ssl_ctx*)*, 20
ssl_ctx_curl_version_match, *21*
ssl_ctx_curl_version_match *(*ssl_ctx*)*, 20
ssl_ctx_set_verify_callback, *21*
ssl_ctx_set_verify_callback *(*ssl_ctx*)*, 20

url(), *11*

write_der *(*write_pem*)*, 23
write_openssh_pem *(*write_pem*)*, 23
write_p12, 22
write_p7b *(*write_p12*)*, 22
write_pem, *12*, 23
write_pkcs1 *(*write_pem*)*, 23
write_ssh *(*write_pem*)*, 23

x25519_diffie_hellman *(*curve25519*)*, 6
x25519_keygen *(*keygen*)*, 12